



NOTES:

ELECTRICAL:

1. VOLTAGE RATING
2. CURRENT RATING
3. CONTACT RESISTANCE
4. INSULATION RESISTANCE
5. DIELECTRIC STRENGTH

MECHANICAL:

1. HOUSING&INSERT MATERIAL
2. CONTACT MATERIAL
3. PLATING
4. OPERATING LIFE
5. MATING/UNMATING FORCE
6. RETENTION STRENGTH

- 1. 125 VAC RMS.
- 1.5 AMP.
- 20 MILLIOHMS MAX.
- 1000 MEGOHMS MIN @ 500 VDC
- 1000 V AC OR 1500V DC RMS @ 0.5mA 50 Hz / 60 Hz 1 Minute
- (SEE TABLE) UL 94V-0.
- PHOSPHOR BRONZE $\phi 0.46mm$.
- GOLD PLATING OVER NICKEL.
- 750 CYCLES MIN.
- 30N MAX.
- SON FOR 60S±5S.

ENVIRONMENTAL:

1. STORAGE: -40°C TD +85°C RELATIVE HUMIDITY<80%.
 2. OPERATION: -40°C TD +85°C.
- MATES WITH MODULAR PLUG CONFIRMING TO FCC PART 68, SUBPART F.

- 电气特性:**
1. 额定电压: 125 VAC RMS
 2. 额定电流: 1.5 AMP
 3. 接触电阻: 20mΩ MAX
 4. 绝缘电阻: 1000MΩ@100V 500VDC
 5. 耐压强度: 1000 V AC 或 1500V DC RMS @ 0.5mA 50 Hz 或 60 Hz 一分钟

结构特性:

1. 基板材料: (见屏飞表接) 0.94V-0
 2. 零件材料: 磷青铜, $\phi 0.46mm$
 3. 零件电镀: 表面镀金(见零件表接), 镀层: 4.可溶性: 最少750次插拔.
 5. 插入/拔出力: 30N MAX
 6. 配合精度: 50μ 60μ ±5μ.
- 环境特性:**
1. 储存温度: -40°C ~ +85°C
 2. 工作温度: -40°C ~ +85°C
 3. 相对湿度: <80%

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	TITLE:	CLIENT P/N	UNIT	SCALE	free	REV.	A	KYD0
CHECKED:	DATE:	RJ11-6P/6C 全塑 弯插 (AJ007) 无铭	C2902899	mm	SCALE	free	REV.	A	KYD0
DRAWN:	DATE:	深圳市灿科盟实业有限公司	CHANKUANGMENT INDUSTRYCO., LTD	mm	SCALE	free	REV.	A	KYD0
LXF	2011-01-13	深圳市灿科盟实业有限公司	CHANKUANGMENT INDUSTRYCO., LTD	mm	SCALE	free	REV.	A	KYD0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Connectors / Ethernet Connectors](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#)
[GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#)
[GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#)
[AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102277](#) [AX102651](#) [AX102660](#) [AX104024](#)
[203475](#) [J0026D01ENL](#) [PC4D0018P](#) [KIT38082NI](#) [8949-B88/6](#) [2-6609208-5](#) [30-8956](#) [30-8964-100](#) [SM85](#) [17-103540](#) [191587](#) [PDI-68-RV](#)
[PHP-8P8C-S-5](#)