



NOTES:

MATERIAL :

- 1 HOUSING MATERIAL
- 2 CONTACT MATERIAL
- 3 PLATING
- ELECTRICAL:
- 1 VOLTAGE RATING
- 2 CURRENT RATING
- 3 CONTACT RESISTANCE
- 4 INSULATION RESISTANCE
- 5 DIELECTRIC WITHSTANDING RESISTANCE
- MECHANICAL:
- 1 DURABILITY
- 2 PCB RETENTION PRE-SOLDER
- ENVIRONMENTAL:
- 1 STORAGE
- 2 OPERATION

- : GLASS FILLED POLYESTER UL94V-0.
- : PHOSPHOR BRONZE Ø0.46mm
- : GOLD PLATING OVER NICKEL.
- : 25 VAC RMS
- : 15 AMP.
- : 30 MILLIOHMS MAX.
- : 500 MEGOHMS MIN @ 500V DC.
- : 1000V AC RMS 50Hz 1MIN.
- : 750 CYCLES MIN.
- : 1 LB MIN.
- : -40°~+85°
- : 0° TO 70°.

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	TITLE:
CHECKED:	DATE:	RJ45-8P/8C 双磁胎 1*2 弯插 短体 全搜 带灯
DRAWN:	DATE:	P/N
SXA	2018-10-28	5JA-1X2-8P8C-LED
		UNIT
		mm
		SCALE
		free
		REV.
		A
		HT04

深圳市如科盟实业有限公司
CHANKIT™ CHANKLEMENT INDUSTRYCO., LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Connectors / Ethernet Connectors](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[RJE231881317T](#) [MP1010RX-1000](#) [MP44RX-1000](#) [GAX-3-66](#) [GAX-8-62](#) [93606-0253](#) [GD-A-44](#) [GDCX-PA-66-50](#) [GDCX-PN-64](#) [GDCX-PN-66](#) [GDCX-PN-66-50](#) [GDLX-A-66](#) [GDLX-A-88](#) [GDLX-N-66](#) [GDLX-S-88K](#) [GDTX-S-88-50](#) [GDX-PA-1010](#) [GLX-N-1010M-BLK](#) [GLX-N-44M](#) [GLX-S-88M-BLK](#) [GMX-N-1010](#) [GMX-S-1010](#) [GMX-S-66](#) [GMX-SMT2-N-1010](#) [GMX-SMT2-N-64-50](#) [GMX-SMT2-S6-88](#) [GMX-SMT4-N-88](#) [GPX-2-64](#) [GRT1-BT1-5](#) [GSGX-N-2-88](#) [GSX-NS2-88-3.05](#) [GSX-NS2-88-3.05-50](#) [GSX-NS-88-3.05-30](#) [GSX-NS-88-3.05-50](#) [GSX-NS-88-3.68](#) [1-1775629-2](#) [GWLX-S-88-GR](#) [GWLX-S9-88-YG](#) [1300500326](#) [1300500227](#) [1300530003](#) [1300570002](#) [1324640-4](#) [RJ11FTVC2G](#) [RJ11FTVC2N](#) [RJFTVX2SA1G](#) [132764-001](#) [1400000](#) [1413176](#) [1413235](#)