



PC Board Layout  
Component Side Shown

NOTES:

MATERIAL:

- 1 HOUSING MATERIAL
  - 2 CONTACT MATERIAL
  - 3 PLATING
  - 4 SHIELD
- ELECTRICAL:
- 1 VOLTAGE RATING
  - 2 CURRENT RATING
  - 3 CONTACT RESISTANCE
  - 4 INSULATION RESISTANCE
  - 5 DIELECTRIC WITHSTANDING RESISTANCE
- MECHANICAL:
- 1 DURABILITY
  - 2 PCB RETENTION PRE-SOLDER
- ENVIRONMENTAL:
- 1 STORAGE
  - 2 OPERATION

- 125 VAC RMS
- 15 AMP
- 30 MILLIOHMS MAX.
- 500 MEGOHMS MIN @ 500V DC
- 1000V AC RMS 50HZ MIN
- 750 CYCLES MIN
- 1 LB MIN
- 40°C~+85°C
- 0°C TO 70°C

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:
CHECKED:	DATE:
DRAWN:	DATE:
ZYJ	2016-10-19

深圳市灿科盟实业有限公司  
Ckmtw CHANKLEMENT INDUSTRYCO., LTD

TITLE:

RJ45-8P/8C 2\*4P 八胞胎 弯插 带屏蔽 带灯 带弹片  
(5)JB-2X4-8P8C-LED-S-E

PART. NO.	R-RJ45R08P-C802
UNIT	mm
SCALE	Free
FILE NO.	Ckmtw-RJ45-0113
REV.	A
	HY04

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Modular Connectors / Ethernet Connectors](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#)  
[GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#)  
[GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#)  
[AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102277](#) [AX102651](#) [AX102660](#) [AX104024](#)  
[203475](#) [PC4D0018P](#) [KIT38082NI](#) [8949-B88/6](#) [2-6609208-5](#) [30-8956](#) [30-8964-100](#) [SM85](#) [SM99S01VBNN04G7](#) [17-103540](#) [191587](#) [PDI-68-RV](#) [PHP-8P8C-S-5](#)