


RECOMMENDED PCB LAYOUT
COMPONENT SIDE VIEW



SPECIFICATION
 Current Rate: 3Amp
 Contact Resistance: 20mΩ MAX.at DC 1A
 Insulation Resistance: 1000MΩ MIN.atDC500V
 Dielectric Strength: AC500V PER minute
 Operation Temperature: -40°to +105°

MATERIAL
 Insulator: Polyester , UL94V-0
 Standard: PA6T
 CONTACT: Phosphor Bronze
 Contact plated: Gold Over Nickel
 Color: Black

APPROVED:	DATE:	C 深圳市灿科盟实业有限公司 kmtw CHANKEMENG INDUSTRYCO., LTD			
CHECKED:	DATE:	TITLE: 220S-2*4P H=5.0 封闭式 (U型)			
DRAWN:	DATE:	CLIENT P/N	21UB08PBB101		
LYF	2021-04-01	UNIT	mm	SCALE	free
TOLERANCE TABLE		FILE NO.	S0490000266		
.0	±0.20	REV.	A		
.00	±0.10				
.000	±0.05				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [D-Sub Standard Connectors](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[015-0339-000](#) [015-0341-000](#) [015-0349-000](#) [015-0350-000](#) [015-8544-011](#) [015-8755-001](#) [017041-0005](#) [020419-0104](#) [609-25P](#) [609-9P](#)
[M24308/2-23Z](#) [CT0-24-10SC](#) [CT0-36-3PC](#) [CT0E20-8PS](#) [CT0F16S-1PS](#) [CT0TA16-11SXCA232](#) [CT1E20-19SS](#) [CT2-10SL-3SC](#) [CT2-14S-](#)
[2PCA34](#) [CT2-18-11PCAU](#) [CT2-22-19SC](#) [CT2-36-5PC](#) [CT6-10SL-3SC](#) [CT6-10SL-4SC](#) [CT6-14S-2SC](#) [CT6-16-12SC](#) [CT6-18-10PSA206](#)
[CT6-18-10PSA232](#) [CT6-18-11PXSA206](#) [CT6-18-11PXSA232](#) [CT6-22-10PS](#) [CT6-24-5PC](#) [CT6-9767-18-8-18-4SS](#) [CT6E14S-5SC](#)
[CT6E14SA7SC](#) [CT6E20-14SS](#) [CT6E22-14PC](#) [CT6E22-14PS](#) [CT6E22-19PS](#) [CT6E22-22PS](#) [CT6E24-10SC](#) [CT6F16S-1SC](#) [CT6FA10SL-4PS](#)
[CT6LA20-19PC](#) [CT6M20-19SS](#) [CT6NSB4-20-8SS](#) [CT6TC14S-6SCAU](#) [CT6TC14S-7PS](#) [6STD15SCT99S40X](#) [6STF09PCM05B70X](#)