



规格说明: Specifications:
电气特性 Electrical

- 1. 额定电流: Current Rating
1. 5A/contact terminal
- 2. 额定电压: Voltage Rating
30V DC
- 3. 接触阻抗: Contact Resistance
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding
Voltage:
500 V AC For one minuter
- 5. 绝缘阻抗: Insulation Resistance
1000MEGA ohms MIN

原材料: Raw material

- 1. 塑胶: Plastic cement:
Hing Temperature Thermoplastics
PBT/LCP Black/White
- 2. 端子: Contact: Copper Alloy C2680
- 3. 外壳: Shell: SPC/ Copper Alloy C2680
- 电镀 Electroplate
- 1. 端子: Contact: Plated Gold in Mating

Area:

- Tin On Solder Tails
- 2. 外壳: Shell:
Nickel Plating

APPROVED:	DATE:	 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRY CO., LTD
CHECKED:	DATE:	
DRAWN: SXA		

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

TITLE:		USB-A/F-1*4P 母头 全贴 无卷边			
PROD. P/N	C2895042	UNIT	mm	SCALE	free
FILE NO.	U-USBAM04P-F001	REV.	A	HLW0	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[950](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#)
[1734082-1](#) [30-470](#) [30-489](#) [30-541](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTVSCCG](#) [1-1734084-2](#) [10135326-001LF](#) [4198](#) [USB-A-D-VT](#)
[USB-A-S-RA-TSMT](#) [1310-1023-02](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [17-200011](#) [UB-20AFMM-LL7A01](#) [1040870124](#) [CAP-](#)
[WCCMLPB1](#) [CAP-WCCMLPC1](#) [2274475-3](#) [UB-20BMFA-SL8001](#) [914-614A2025S10200](#) [USB3FTV7SAGF059](#) [ZX40-B-5S-1500-](#)
[STDA\(30\)](#) [GSB3116344HR](#) [USB3FTV2SAZNF459](#) [USB3FTV7SAZNF459](#) [U221-041N-1WVS62-F5D](#) [HYCW153-USBD05-500B](#)
[HYCW219-USBD05-075B](#) [HYCW148-USBD05-117B](#) [HYCW149-USBD05-740B](#) [HYCW204-USBD05-108B](#) [HYCW214-USBA04-113B](#)
[HYCW213-USBA04-113B](#) [UB-20AMFM-SL7A01](#) [KMMX-BSMT35S-1-B30TR](#) [2345986-1](#)