



SPECIFICATIONS
 Current rating: 2A AC/DC
 Voltage rating: 250V AC/DC
 Contact resistance: 30mΩ max.
 Withstand voltage: 800V AC/min
 Insulation resistance: 1000MΩ/min.
 Temperature range: -25°C~+85°C
 Applicable PC board thickness:
 0.031"~0.063"(0.8~1.6)

Material:
 Part No: 8-44
 Insulator: PA66 UL94V-2
 Contact: Brass
 Finish: Tin Plated

Poles	Part No.	A	B	C
8	2008R-2*4P-1K	6.0	9.0	10.0
10	2008R-2*6P-1K	8.0	11.0	12.0
12	2008R-2*6P-1K	10.0	13.0	14.0
14	2008R-2*7P-1K	12.0	15.0	16.0
16	2008R-2*8P-1K	14.0	17.0	18.0
18	2008R-2*8P-1K	16.0	19.0	20.0
20	2008R-2*10P-1K	18.0	21.0	22.0
22	2008R-2*11P-1K	20.0	23.0	24.0
24	2008R-2*12P-1K	22.0	25.0	26.0
26	2008R-2*13P-1K	24.0	27.0	28.0
28	2008R-2*14P-1K	26.0	29.0	30.0
30	2008R-2*15P-1K	28.0	31.0	32.0
32	2008R-2*16P-1K	30.0	33.0	34.0
34	2008R-2*17P-1K	32.0	35.0	36.0
36	2008R-2*18P-1K	34.0	37.0	38.0
38	2008R-2*19P-1K	36.0	39.0	40.0
40	2008R-2*20P-1K	38.0	41.0	42.0

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED: _____ DATE: _____
 CHECKED: _____ DATE: _____
 DRAWN: LYP

DATE: 2014-06-26
 TITLE: 2008R-2*5P 带扣



PROD. P/N C3025470
 UNIT mm SCALE free
 FILE NO. W-2006R10P-B000 REV. A KLD0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [M90C108951C](#)
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-024-10-](#)
[001000](#) [803-93-012-10-001000](#)