



SPECIFICATIONS
 Current rating: 3A AC/DC
 Voltage rating: 250V AC/DC
 Contact resistance: 20mΩ max.
 Withstand voltage: 1000V AC/min
 Insulation resistance: 1000MΩ/min.
 Temperature range: -25°C~+85°C
 Applicable PC board thickness: 0.063"(1.6)

Material:
 Part No: 2~16
 Post: Brass, Tin/plated
 Base: Nylon66 UL94V-2

Poles	Part No.	Dimension mm	
		A	B
2	2501S-2P	2.50	7.50
3	2501S-3P	5.00	10.00
4	2501S-4P	7.50	12.50
5	2501S-5P	10.00	15.00
6	2501S-6P	12.50	17.50
7	2501S-7P	15.00	20.00
8	2501S-8P	17.50	22.50
9	2501S-9P	20.00	25.00
10	2501S-10P	22.50	27.50
11	2501S-11P	25.00	30.00
12	2501S-12P	27.50	32.50
13	2501S-13P	30.00	35.00
14	2501S-14P	32.50	37.50
15	2501S-15P	35.00	40.00
16	2501S-16P	37.50	42.50

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED: _____ DATE: _____
 CHECKED: _____ DATE: _____
 DRAWN: YAN

深圳市如科盟实业有限公司
 CHANTW CHANKLEMENT INDUSTRYCO., LTD

TITLE: 2501S-XP 3TK

PROD. P/N /
 UNIT mm SCALE free
 FILE NO. Chantw-2501-0016 REV. A KL00

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)
[001000](#)