



P. C. B LAYOUT

SPECIFICATIONS

Current rating: 3A AC/DC
 Voltage rating: 250V AC/DC
 Contact resistance: 20mΩ max.
 Withstand voltage: 1000V AC/min
 Insulation resistance: 1000MΩ/min.
 Temperature range: -25° C~+85° C

Material:

Part No: 2~15

Post: Brass. Tin/plated

Base: Nylon66 UL94V-0

Poles	Part No	Dimension mm		
		A	B	C
2	2503S-2P	2.50	6.0	7.50
3	2503S-3P	5.00	8.5	10.00
4	2503S-4P	7.50	11	12.50
5	2503S-5P	10.00	13.5	15.00
6	2503S-6P	12.50	16	17.50
7	2503S-7P	15.00	18.5	20.00
8	2503S-8P	17.50	21	22.50
9	2503S-9P	20.00	23.5	25.00
10	2503S-10P	22.50	26	27.50
11	2503S-11P	25.00	28.5	30.00
12	2503S-12P	27.50	31	32.50
13	2503S-13P	30.00	33.5	35.00
14	2503S-14P	32.50	36	37.50
15	2503S-15P	35.00	38.5	40.00

TOLERANCE TABLE	
.0	±0.30
.00	±0.15
.000	±0.05

APPROVED:	DATE:	 深圳市灿科盟实业有限公司 CHANKEMENG INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
LYF	2008-04-07	2503S-XP
CLIENT P/N		SCALE
UNIT	mm	free
FILE NO.	Ckmtw-2503-0003	REV.
		A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)
[001000](#)