



SPECIFICATION

Current rating: 5A AC/DC

Voltage rating: 250V AC/DC

Contact resistance: 20m Ω max.

Withstand voltage: 1500V AC/min.

Insulation resistance: 1000M Ω /min.

Temperature range: -25 $^{\circ}$ C ~ +85 $^{\circ}$ C

Material:

Part No:2~12

Post:Brass.Tin/plated

Base:Nylon66 UL94V-0 or V-2

Poles	Part NO.	Dimension (mm)	
		A	B
2P	W-3962S02P-0000	3.96	7.92
3P	W-3962S03P-0000	7.92	11.88
4P	W-3962S04P-0000	11.88	15.84
5P	W-3962S05P-0000	15.84	19.80
6P	W-3962S06P-0000	19.80	23.76
7P	W-3962S07P-0000	23.76	27.72
8P	W-3962S08P-0000	27.72	31.68
9P	W-3962S09P-0000	31.68	35.64
10P	W-3962S10P-0000	35.64	39.60
11P	W-3962S11P-0000	39.60	43.56
12P	W-3962S12P-0000	43.56	47.52
13P	W-3962S13P-0000	47.52	51.48

TOLERANCE TABLE

.0	± 0.30
.00	± 0.20
.000	± 0.05

APPROVED:	DATE:	Ckmtw 深圳市灿科盟实业有限公司 CHANKEMENG INDUSTRYCO., LTD			
CHECKED:	DATE:	TITLE: 3962S-7P			
DRAWN:	DATE:	CLIENT P/N	C2940223		
LYF	2008-04-07	UNIT	mm	SCALE	free
		FILE NO.	Ckmtw-3962-0020	REV.	A WDOO

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#)
[622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-015LF](#)
[66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#)
[80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)
[803-43-024-10-001000](#)