



SPECIFICATION

1. Rating : DC 30V 1.0A;
2. Contact resistance: $\leq 0.03 \Omega$;
3. Insulation resistance: $\geq 100M \Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.

PIN	$\phi 2.0$	$\phi 2.5$
APPD.		✓

包装要求:

1. 每500PCS装1PE袋, 每箱入数可视订单量大小调整.
2. 每袋贴上一张合格标签、ROHS标签, 外箱贴上产品标签

6	COVER	1	PBT UL 94V-0	BLACK
5	HOUSING	1	PBT UL 94V-0	BLACK
4	PIN	1	C3604	NI PLATED
3	TIP SPRING	1	SHELL	Sn PLATED
2	TERMINAL	1	C2680	Sn PLATED
1	SHUNT SPRING	1	C2680	Sn PLATED
LTR	PART NAME	QTY	MATERIAL	FINISH

TOLERANCE TABLE

.0	± 0.20
.00	± 0.10
.000	± 0.05

APPROVED:	DATE:	Ckmtw 深圳市灿科盟实业有限公司 CHANKEMENG INDUSTRYCO., LTD			
CHECKED:	DATE:	TITLE: DC JACK 电源座 (DC-00050)			
DRAWN:	DATE:	CLIENT P/N	C840489		
luli-Liu	2015-04-25	UNIT	mm	SCALE	free
		FILE NO.	Z-DC00R02P-2500	REV.	A ZZDZ

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[B04P-VL-VN-1.8](#) [1600206-1](#) [163-0308-EX](#) [163-4012-EX](#) [163-4117-EX](#) [163-7421](#) [163-MJ22-EX](#) [171-0721-EX](#) [KLDX-SMT-0202-BPTR](#)
[163-0179-EX](#) [163-1000-EX](#) [163-4007-EX](#) [163-4015-EX](#) [171-0722-E](#) [171-7391](#) [K596](#) [KLD-0201-BC](#) [KPPX-D](#) [4C6831AX](#) [TS3PNJ](#)
[E16550-0008](#) [VLP-08V-1](#) [DC PLUG-P1M-P1MR](#) [XT90IPW22-M](#) [09758](#) [09442](#) [AS120-M](#) [09759](#) [09760](#) [CP30240](#) [TAMIYA-M](#) [TAMIYA-](#)
[MT1](#) [TAMIYA-MT2](#) [4840.1200](#) [4840.2202](#) [C5080HI-04P-18 + C5080HI-C](#) [JC-138](#) [JC-210](#) [JPO-25 \(FC6814\)](#) [JYO-26 \(FC6811\)](#) [JYO-29](#)
[\(FC68102\)](#) [KLB 3](#) [KLBM 3](#) [KLBPS 3](#) [KLS 10 SCHWARZ](#) [KLS 40 SCHWARZ](#) [KPJXHT-4S](#) [DC-10A FC68148](#) [DC-10B \(FC68149\)](#)
[WKLS 2](#) [WKLS 40](#)