G-Series TOGGLE SWITCHES

General purpose workhorses with options tailored to meet most any need. Ratings to 20A 277VAC, international approvals, various actuator, bushing, termination, and circuit choices allow this toggle switch to easily integrate into a variety of different applications. The G-Series is appropriate for usage in low voltage DC applications.



Product Highlights:

- · Ratings to 20A 277VAC available
- · Metal bat or nylon bat/paddle actuator styles
- · UL, CSA and VDE approvals for select circuits
- Suitable for low voltage 12/24V DC

Typical Applications:

- Marine
- Food Service
- Generator
- Industrial Control
- Office Automation



Carling Technologies, Inc. 60 Johnson Avenue, Plainville, CT 06062 Email: sales@carlingtech.com Application Support: team2@carlingtech.com Phone: 860.793.9281 Fax: 860.793.9231

www.carlingtech.com

Dielectric Strength

UL/CSA: 1000V - live to dead metal parts & opposite polarity VDE: 4000V - live to dead metal parts; 1250V - opposite polarity & across open contacts

Electrical Life

50,000 cycles - maintained 25,000 cycles - momentary

Operating Temperature

32°F to 185°F (0° to 85°C)

	2G 1 Base Part 1	M51 -	- 73		
Single Pole in 10A 250VAC, solder lug 2GA50 6GA5A 6GA5L 2GB50 6GC5A 6GC5A 6GC5A 6GC5A 6GC5L 10A 250VAC, 2GA90 2GB90 Additional ratir	Double Pole base 15A 125VAC, 3/4 HP .250 tab scre 2GA51 2GA 2GA55 6GA 6GA5B 6GA 2GB51 2GB 2GC51 2GC 2GC51 2GC 6GC5B 6GC 6GC5M 6GC 15A 125VAC, 12 (6)A 2GB91 2GA91 - 2GS91 -	w term. 154 On-None-Off 155 On-None-Off 155 On-None-Off 154 On-None-On 155 On-None-On 155 On-Off-On 155 (On)-Off-(On) 150 (On)-Off-(On) 150 (On)-Off-(On) 0n-None-Off On-None-Off On-None-Off On-Off-On 0n-Off-On 124 250VAC, 1HP 12	Double Pole solder lug 2GK50 f 6GK5A 2GL50) 6GL5A 2GM50 6GM5L CVDE Approved 7 2GK90 2GK90 2GL90 2GM90	.250 tab sc 2GK51 20 6GK5B 60 6GK5M 60 2GL51 20 6GL5B 60 2GM51 20 6GM5B 60 6GM5B 60	rew term. 3K54 3K5E 3K5S 3L54 3L5E 3M54 3M5E 3M5S
2 ACTUATOR BAT PADDLE ⁵ BAT ² PADDLE ²	STYLE 4 unsealed 73 NBL3 D-3B-B -	sealed 78 NBL8 - D-4B-B	toggle length 0.687 0.687 0.687 0.687 0.687	bushing le 0.465 0.465 0.379 0.379	ngth


Notes 1

Not available with 73 or NBL3 style toggles, T55 with 78 and NBL8 style toggles.

2 3 All nylon bushing and toggle. Consult factory for .187 tab, wire lead and combination screw/tab/solder lug termination callouts.

Additional actuator options available. Consult factory. Nylon toggle with black ebanol plated bushing. Indicates momentary function.

4 5 ()



*Manufacturer reserves the right to change product specification without prior notice.

Authorized Sales Representatives and Distributors

Click on a region of the map below to find your local representatives and distributors or visit *www.carlingtech.com/findarep*.



About Carling

Founded in 1920, Carling Technologies is a leading manufacturer of electrical and electronic switches and assemblies, circuit breakers, electronic controls, power distribution units, and multiplexed power distribution systems. With four ISO9001 and IATF16949 registered manufacturing facilities and technical sales offices worldwide, Carling Technologies Sales, Service and Engineering teams do much more than manufacture electrical components, they engineer powerful solutions! To learn more about Carling please visit www.carlingtech.com/company-profile.

To view all of Carling's environmental, quality, health & safety certifications please visit **www.carlingtech.com/environmental-certifications**

Worldwide Headquarters

Carling Technologies, Inc. 60 Johnson Avenue, Plainville, CT 06062 Phone: 860.793.9281 Fax: 860.793.9231 Email: sales@carlingtech.com

Northern Region Sales Office: nrsm@carlingtech.com Southeast Region Sales Office: sersm@carlingtech.com Midwest Region Sales Office: mrsm@carlingtech.com West Region Sales Office: wrsm@carlingtech.com Latin America Sales Office: larsm@carlingtech.com

Asia-Pacific Headquarters

Carling Technologies, Asia-Pacific Ltd., Suite 1607, 16/F Tower 2, The Gateway, Harbour City, 25 Canton Road, Tsimshatsui, Kowloon, Hong Kong Phone: Int + 852-2737-2277 Fax: Int + 852-2736-9332 Email: sales@carlingtech.com.hk

Shenzhen, China: shenzhen@carlingtech.com Shanghai, China: shanghai@carlingtech.com Pune, India: india@carlingtech.com Kaohsiung, Taiwan: taiwan@carlingtech.com Yokohama, Japan: japan@carlingtech.com

Europe | Middle East | Africa Headquarters

Carling Technologies LTD 4 Airport Business Park, Exeter Airport, Clyst Honiton, Exeter, Devon, EX5 2UL, UK **Phone:** Int + 44 1392.364422 **Fax:** Int + 44 1392.364477 **Email:** Itd.sales@carlingtech.com

Germany: gmbh@carlingtech.com France: sas@carlingtech.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Gate Drivers category:

Click to view products by Carling manufacturer:

Other Similar products are found below :

 00053P0231
 8967380000
 56956
 CR7E-30DB-3.96E(72)
 57.404.7355.5
 LT4936
 57.904.0755.0
 5803-0901
 58410
 5882900001
 00600P0005

 00-9050-LRPP
 00-9090-RDPP
 5951900000
 01-1003W-10/32-15
 LTILA6E-1S-WH-RC-FN12VXCR1
 0131700000
 00-2240
 LTP70N06

 LVP640
 0158-624-00
 5J0-1000LG-SIL
 020017-13
 LY1D-2-5S-AC120
 LY2-0-US-AC120
 LY2-US-AC240
 LY3-UA-DC24
 00-5150

 00576P0020
 00600P0010
 LZNQ2M-US-DC5
 LZNQ2-US-DC12
 LZP40N10
 00-8196-RDPP
 00-8274-RDPP
 00-8275-RDNP
 00-8609

 RDPP
 00-8722-RDPP
 00-8869-RDPP
 00-9051-RDPP
 00-9091-LRPP
 00-9291-RDPP
 0207100000
 60100564

 01312
 0134220000
 6035
 M15730061
 00-9051-RDPP
 00-9091-LRPP
 00-9291-RDPP
 0207100000
 60100564