



Embed +60 Years of Wireless Expertise & Performance Into Your Connected Solution

THE CEL ADVANTAGE



Performance

- Best in class wireless connectivity
- Lowest system power consumption
- Product testing & verification



AcCErate TTM

- 2-day in-person training
- Quick start guides/resources
- Fast prototyping



Commercial Grade Quality & Reliability

- 100% RF tested w/traceability
- Extensive JESD22 qualifications
- No field failures, RMAs, truck rolls...



Technical Support & Expertise

- HW, FW, Antenna design guides
- Comprehensive design reviews
- Certification/compliance



Home Automation



Building Automation



Connected Lighting



Industrial




Smart Energy



High-performance & Ultra Low-power Wi-Fi & BT for Hosted Applications

- Based on Qualcomm's QCA9377-x
- Dual-band 1x1 802.11 b/g/n/a/ac Wave2 & BT5.0
- SDIO and USB interface options
- +20dBm
- On-board and external antenna options
- Miniature form factor
- Industrial Temp.
- Drivers: Linux, Windows 10, and Android



COMING SOON

Multi-Protocol IoT Connectivity Solution

- Based on Qualcomm's QCA4020 chip set
- Wi-Fi, BLE, ZigBee, Thread
 - ▶ Dual-band 1x1 802.11 a/b/g/n
 - ▶ BLE5.0
 - ▶ ZB 3.0
 - ▶ Thread v1.1
- Implementation options:
 - ▶ Hostless...Integrated Cortex-M4F, SRAM, Flash & peripherals for application, ThreadX and FreeRTOS
 - ▶ Hosted...SDIO/SPI/UART interfaces for external host MCU, driver source code and APIs
- Dedicated CPUs for Wi-Fi and 802.15.4 stacks
- Concurrent Wi-Fi and 802.15.4 operation
- Coexistence manager
- Low power Wi-Fi and 802.15.4 operation modes
- Pre-integrated s/w for HomeKit and OCF, AWS IoT SDK, and Microsoft Azure IoT Device SDK



Low-Power IoT Module

- Based on Realtek 8710
- 1T1R 802.11 b/g/n
- ARM Cortex M4F
- FreeRTOS, Arm Mbed
- On-board and external antenna options



PRODUCT OFFERINGS & TECHNICAL INFORMATION



Based on EM3588 SoC



Based on EM357 SoC



Based on EFR32MG12 SoC



MeshConnect Products

	EM358x Mini Modules		EM357 Mini Modules		ZB3212F6R Multi-Mode	EM35x USB Sticks	
	Standard	Extended Range	Standard	Extended Range	Standard	Standard	Extended Range
MCU	2405 to 2480 MHz / DSSS / IEEE 802.15.4		2405 to 2480 MHz / DSSS / IEEE 802.15.4		2405 to 2480 MHz / DSSS / IEEE 802.15.4	2405 to 2480 MHz / DSSS / IEEE 802.15.4	
Radio Parameters	Silicon Labs™ EM3588 32 bit, ARM® Cortex™ - M3		Silicon Labs™ EM357 32 bit, ARM® Cortex™ - M3		Silicon Labs™ EFR32MG12 32 bit, ARM® Cortex™ - M4	Silicon Labs™ EM35x 32 bit, ARM® Cortex™ - M3	
Transceiver Chipset	512 kB Flash, 64 kB RAM		192 kB Flash, 12 kB RAM		1MB Flash, 256kB RAM	192 kB Flash, 12 kB RAM	
Memory on Chip	-		-		-	1 MB Flash	
Supplemental Memory	Up to 23		Up to 22		Up to 24	N/A	
Inputs/Outputs	USB 2.0 (full speed)		-		-	USB 2.0 (full speed)	
USB	Zigbee, Thread		Zigbee		Zigbee, Thread, BTLE	USB, Zigbee, Thread	
Protocol	✓		✓		✓	✓	
Mesh Networks	250 kbps		250 kbps		250kbps	250 kbps	
Over-the-Air Data Rate	128-bit AES Encryption		128-bit AES Encryption		128/256-bit AES Encryption	128-bit AES Encryption	
Over-the-Air Security	EmberZNet PRO™ (ZigBee PRO)		EmberZNet PRO™ (ZigBee PRO)		EmberZNet PRO™	EmberZNet PRO™ (ZigBee PRO)	
Software/ZigBee Stack	+ 8 dBm	+ 20 dBm	+ 8 dBm	+ 20 dBm	+20dBm	+ 8 dBm	+ 20 dBm
Tx Output Power	- 100 dBm	- 103 dBm	- 100 dBm	- 103 dBm	-101dBm	- 100 dBm	- 103 dBm
Rx Sensitivity	+108 dB	+123 dB	+108 dB	+123 dB	+121dBm	+108 dB	+123 dB
RF Link Budget	2.1 to 3.6 V		2.1 to 3.6 V		2.4-3.8V	4.0 to 5.25 V	
Power Supply Voltage	30mA	34mA	30mA	34mA	12mA	51mA	55mA
Rx Current	44mA	150mA	44mA	150mA	120mA	65mA	165mA
Tx Current@Max Power	2.4µA		1.0µA		.43uA	0.24µA	
Sleep/Suspend Current	23.9 x 16.6 x 3.9mm (0.94 x 0.655 x 0.152in)		23.9 x 16.6 x 3.9mm (0.94 x 0.655 x 0.152in)		23.9x16.6.x3.9mm	52.7 x 24.9 x 9.98 mm (2.075 x 0.984 x 0.393in)	
Dimensions	✓	✓	✓	✓	✓	-	-
Footprint Compatible	✓	✓	✓	✓	✓	✓	✓
Integrated Antenna	✓	✓	✓	✓	✓	-	-
RF Port for External Antenna	-40°C to 85°C		-40°C to 85°C		-40°C to +85°C	-30°C to 70°C	
Temperature Range	✓	✓	✓	✓	✓	✓	✓
FCC	✓	✓	✓	✓	✓	✓	✓
IC	✓	-	✓	-	-	✓	-
CE	✓	✓	✓	✓	✓	✓	✓
RoHS	✓	✓	✓	✓	✓	✓	✓
CERTIFICATIONS	ZICM3588SP0-1	ZICM3588SP2-2	ZICM357SP0-1	ZICM357SP2-2	ZB3212F6R4SP2-1,-1C	ZM357S-USB	ZM357S-USB-LR
Part Numbers	ZICM3588SP0-1C*	ZICM3588SP2-2C*	ZICM357SP0-1C*	ZICM357SP2-2C*			

* Part numbers ending in **SP0-1C** have an RF port for external antennas and are not FCC, IC or CE certified. Part numbers ending in **SP2-2C** have an RF port for external antennas and are FCC and IC certified for a Nearson S181AH-2450S antenna.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Zigbee Modules - 802.15.4 category](#):

Click to view products by [CEL manufacturer](#):

Other Similar products are found below :

[XBP24-ASI-080](#) [ATZB-RF-212B-0-CNR](#) [34560-894](#) [32411](#) [32416](#) [32406](#) [E18-MS1PA2-PCB](#) [ZTU\(ujzh\)](#) [BB-WCD1H2102H](#) [BB-WCD1H3001HP100](#) [BB-WSD2C31010](#) [BB-WSD2M31010](#) [BB-WSK-SLM-2](#) [BB-WSD2C21150](#) [BB-WSK-CBM-2](#) [20848674](#) [BB-WSD2M3101P2K](#) [WSD2M06010](#) [ATZB-X0-256-3-0-C](#) [BB-WCD1H2102H](#) [BB-WSD2C21150](#) [BB-WSD2M31010](#) [WSD2CTJ](#) [WSD2MD2](#) [WPMM1A01A](#) [WPMM1A02A](#) [WPMM1A05A](#) [ATZB-RF-233-1-CR](#) [ATSAMR21G18-MR210UA](#) [ATSAMR21G18-MR210UAT](#) [MRF24J40MA-I/RM](#) [AX-SF10-ANT21-868-B1](#) [AX-SF10-MINI21-868-B1](#) [24572054](#) [114990002](#) [EM351-MOD-ANT-T](#) [EM351-MOD-RF-T](#) [EM351-MOD-LR-RF-T](#) [EM357-MOD-ANT-T](#) [ETRX3587HR-LRS](#) [WPMM1A00A](#) [ZICM35XSPX-PF-1](#) [ATZB-RF-212B-0-CN](#) [WMPR1A00B1A2](#) [WMPR1A02B1A2](#) [WMPR1A00B1A1](#) [WMPR1A02B1A1](#) [WPMM1A04A](#) [WPMM1A01B](#) [WPMM1A02AS01](#)