


SILICON ZENER DIODES 1.0 WATT, 3.3 THRU 100 VOLT 5% TOLERANCE





www.centralsemi.com

### DESCRIPTION:

The CENTRAL SEMICONDUCTOR 1N4728A series silicon Zener diode is a highly reliable voltage regulator designed for use in industrial, commercial, entertainment and computer applications.

#### MARKING: FULL PART NUMBER

MAXIMUM RATINGS:
Power Dissipation (T <sub>A</sub> =50°C)
Operating and Storage Temperature

SYMBOL		UNITS
PD	1.0	W
T <sub>J</sub> , T <sub>stg</sub>	-65 to +200	°C

**ELECTRICAL CHARACTERISTICS:** (T<sub>A</sub>=25°C) V<sub>F</sub>=1.2V MAX @ I<sub>F</sub>=200mA (for all types)

ТҮРЕ	ZENER VOLTAGE V <sub>Z</sub> @ I <sub>ZT</sub>		AGE CURE		MAXIMUM ZENER IMPEDANCE		MAX REVI CURI	RSE	MAXIMUM DC CURRENT	MAXIMUM TEMPERATURE COEFFICIENT @ <sup>I</sup> ZT	
	MIN	NOM	MAX	IZT	Z <sub>ZT</sub> @ I <sub>ZT</sub>	z <sub>zk</sub> (	<sup>D</sup> <sup>I</sup> ZK	I <sub>R</sub> @	≥ v <sub>R</sub>	IZM	ΘV <sub>Z</sub>
	v	v	v	mA	Ω	Ω	mA	μA	٧	mA	% / °C
1N4728A	3.135	3.3	3.465	76	10	400	1.0	100	1.0	1380	-0.08 to -0.05
1N4729A	3.420	3.6	3.780	69	10	400	1.0	100	1.0	1260	-0.08 to -0.05
1N4730A	3.705	3.9	4.095	64	9.0	400	1.0	50	1.0	1190	-0.07 to -0.02
1N4731A	4.085	4.3	4.515	58	9.0	400	1.0	10	1.0	1070	-0.07 to -0.01
1N4732A	4.465	4.7	4.935	53	8.0	500	1.0	10	1.0	970	-0.03 to +0.04
1N4733A	4.845	5.1	5.355	49	7.0	550	1.0	10	1.0	890	-0.01 to +0.04
1N4734A	5.320	5.6	5.880	45	5.0	600	1.0	10	2.0	810	0 to +0.045
1N4735A	5.890	6.2	6.510	41	2.0	700	1.0	10	3.0	730	+0.01 to +0.055
1N4736A	6.460	6.8	7.140	37	3.5	700	1.0	10	4.0	660	+0.015 to +0.06
1N4737A	7.125	7.5	7.875	34	4.0	700	0.5	10	5.0	605	+0.02 to +0.065
1N4738A	7.790	8.2	8.610	31	4.5	700	0.5	10	6.0	550	+0.03 to +0.07
1N4739A	8.645	9.1	9.555	28	5.0	700	0.5	10	7.0	500	+0.035 to +0.075
1N4740A	9.500	10	10.50	25	7.0	700	0.25	10	7.6	454	+0.04 to +0.08
1N4741A	10.45	11	11.55	23	8.0	700	0.25	5.0	8.4	414	+0.045 to +0.08
1N4742A	11.40	12	12.60	21	9.0	700	0.25	5.0	9.1	380	+0.045 to +0.085
1N4743A	12.35	13	13.65	19	10	700	0.25	5.0	9.9	344	+0.05 to +0.085
1N4744A	14.25	15	15.75	17	14	700	0.25	5.0	11.4	304	+0.055 to +0.09
1N4745A	15.20	16	16.80	15.5	16	700	0.25	5.0	12.2	285	+0.055 to +0.09
1N4746A	17.10	18	18.90	14	20	750	0.25	5.0	13.7	250	+0.06 to +0.09
1N4747A	19.00	20	21.00	12.5	22	750	0.25	5.0	15.2	225	+0.06 to +0.09
1N4748A	20.90	22	23.10	11.5	23	750	0.25	5.0	16.7	205	+0.06 to +0.095
1N4749A	22.80	24	25.20	10.5	25	750	0.25	5.0	18.2	190	+0.06 to +0.095
1N4750A	25.65	27	28.35	9.5	35	750	0.25	5.0	20.6	170	+0.06 to +0.095

R2 (14-October 2013)

#### 1N4728A THRU 1N4764A




#### SILICON ZENER DIODES 1.0 WATT, 3.3 THRU 100 VOLT 5% TOLERANCE

### ELECTRICAL CHARACTERISTICS - Continued: (T<sub>A</sub>=25°C) V<sub>F</sub>=1.2V MAX @ I<sub>F</sub>=200mA (for all types)

TYPE		ZENER VOLTAGE VZ @ IZT		TEST CURRENT	MAXIMUM ZENER IMPEDANCE		MAXIMUM REVERSE CURRENT		MAXIMUM DC CURRENT	MAXIMUM TEMPERATURE COEFFICIENT <sup>@ I</sup> ZT	
	MIN	NOM	MAX	lzт	Z <sub>ZT</sub> @ I <sub>ZT</sub>	Z <sub>ZK</sub> @	<sup>@</sup> <sup>I</sup> zĸ	I <sub>R</sub> @	≥ v <sub>R</sub>	Izм	ΘVZ
	v	v	v	mA	Ω	Ω	mA	μA	V	mA	% / °C
1N4751A	28.50	30	31.50	8.5	40	1.0K	0.25	5.0	22.8	150	+0.06 to +0.095
1N4752A	31.35	33	34.65	7.5	45	1.0K	0.25	5.0	25.1	135	+0.06 to +0.095
1N4753A	34.20	36	37.80	7.0	50	1.0K	0.25	5.0	27.4	125	+0.06 to +0.095
1N4754A	37.05	39	40.95	6.5	60	1.0K	0.25	5.0	29.7	115	+0.06 to +0.095
1N4755A	40.85	43	45.15	6.0	70	1.5K	0.25	5.0	32.7	110	+0.06 to +0.095
1N4756A	44.65	47	49.35	5.5	80	1.5K	0.25	5.0	35.8	95	+0.06 to +0.095
1N4757A	48.45	51	53.55	5.0	95	1.5K	0.25	5.0	38.8	90	+0.06 to +0.095
1N4758A	53.20	56	58.80	4.5	110	2.0K	0.25	5.0	42.6	80	+0.06 to +0.095
1N4759A	58.90	62	65.10	4.0	125	2.0K	0.25	5.0	47.1	70	+0.06 to +0.095
1N4760A	64.60	68	71.40	3.7	150	2.0K	0.25	5.0	51.7	65	+0.06 to +0.095
1N4761A	71.25	75	78.75	3.3	175	2.0K	0.25	5.0	56.0	60	+0.06 to +0.095
1N4762A	77.90	82	86.10	3.0	200	3.0K	0.25	5.0	62.2	55	+0.06 to +0.095
1N4763A	86.45	91	95.55	2.8	250	3.0K	0.25	5.0	69.2	50	+0.06 to +0.095
1N4764A	95.00	100	105.0	2.5	350	3.0K	0.25	5.0	76.0	45	+0.06 to +0.095

#### **DO-41 CASE - MECHANICAL OUTLINE**



DIMENSIONS							
	INC	HES	MILLIM	ETERS			
SYMBOL	MIN	MAX	MIN	MAX			
A	0.026	0.034	0.65	0.86			
В	0.138	0.205	3.50	5.21			
С	0.079	0.107	2.00	2.72			
D	1.000	-	25.40	-			
DO-41 (REV: R2)							

R2 (14-October 2013)

www.centralsemi.com

## **OUTSTANDING SUPPORT AND SUPERIOR SERVICES**

#### **PRODUCT SUPPORT**

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- · Consolidated shipping options

#### **DESIGNER SUPPORT/SERVICES**

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities

ss your design challenges.

· Custom product packing

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits

Custom bar coding for shipments

Custom product and package development

#### **REQUESTING PRODUCT PLATING**

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

#### CONTACT US

#### **Corporate Headquarters & Customer Support Team**

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <u>www.centralsemi.com/terms</u>





http://www.centralsemi.com

## Product End of Life Notification

PDN ID:	PDN01010 Rev:001
Notification Date:	2/15/19
Last Buy Date:	5/02/16
Last Shipment Date	11/02/16

Summary:1 watt, high voltage (75V thru 100V), glass body Zener diodes manufactured in the DO-41 and MELF packages are discontinued and now classified as End of Life (EOL). Rev:001 of PDN#010010, February 15, 2019, is being issued to add 1N4761A omitted from the original PDN.

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

Central Part Number	<b>Replacement</b>
CLL4762A BK	N/A, Stock Only
CLL4762A TR	N/A, Stock Only
CLL4762C BK	N/A, Stock Only
CLL4762C TR	N/A, Stock Only
CLL4763A BK	N/A, Stock Only
CLL4763A TR	N/A, Stock Only
CLL4764 TR	N/A, Stock Only
CLL4764A BK	N/A, Stock Only
CLL4764A TR	N/A, Stock Only
1N4761A BK	N/A, Stock Only
1N4761A TR	N/A, Stock Only
1N4762A BK	N/A, Stock Only
1N4762A TR	N/A, Stock Only
1N4763A BK	N/A, Stock Only
1N4763A TR	N/A, Stock Only
1N4764 BK	N/A, Stock Only
1N4764 TR	N/A, Stock Only
1N4764A BK	N/A, Stock Only
1N4764A TR	N/A, Stock Only

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.



# Product End of Life Notification

PDN ID:	PDN01045
Notification Date:	8/19/16
Last Buy Date:	2/19/17
Last Shipment Date	8/19/17

Summary: The 1N4728A, 1N4729A, 1N4730A, and 1N4731A, 1 watt Zener diodes in the DO-41 case are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement	_
1N4728A BK	N/A	
1N4728A TR	N/A	
1N4729A BK	N/A	
1N4729A TR	N/A	
1N4730A BK	N/A	
1N4730A TR	N/A	
1N4730C BK	N/A	
1N4731A BK	N/A	
1N4731A TR	N/A	

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Zener Diodes category:

Click to view products by Central Semiconductor manufacturer:

Other Similar products are found below :

 RKZ13B2KG#P1
 RKZ5.6B2KJ#R1
 DL5234B
 EDZTE6113B
 1N4682
 1N4691
 1N4693
 1N4732A
 1N4736A
 1N4750A
 1N4759ARL

 1N5241B
 1N5365B
 1N5369B
 1N747A
 1N959B
 1N964B
 1N966B
 1N968B
 1N972B
 NTE5121A
 NTE5147A
 NTE5152A
 NTE5155A

 NTE5164A
 JANS1N4974US
 1N4692
 1N4700
 1N4702
 1N4704
 1N4711
 1N4737A
 1N4745ARL
 1N4752A
 1N4752ARL

 1N4760ARL
 1N5221B
 1N5231B-TR
 1N5236B
 1N5241BTR
 1N5242BTR
 1N5350B
 1N964BRL
 RKZ5.1BKU#P6

 3SMAJ5946B-TP
 3SMBJ5925B-TP
 3SMBJ5925B-TP
 3SMBJ5925B-TP
 3SMBJ5925B-TP