2N5457 2N5458 2N5459

SILICON N-CHANNEL JFETS



www.centralsemi.com

The CENTRAL SEMICONDUCTOR 2N5457, 2N5458, and 2N5459 are silicon N-Channel JFETs designed for switching and amplifier applications.



MARKING: FULL PART NUMBER

MAXIMUM RATINGS: (T _A =25°C)	SYMBOL		UNITS
Drain-Source Voltage	V_{DS}	25	V
Drain-Gate Voltage	V_{DG}	25	V
Gate-Source Voltage	V_{GS}	25	V
Continuous Gate Current	I_{G}	10	mA
Power Dissipation	P_{D}	310	mW
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to +150	°C

 $\textbf{ELECTRICAL CHARACTERISTICS:} \ (T_{\mbox{\scriptsize A}} = 25^{\circ}\mbox{C unless otherwise noted})$


	<u>2N5457</u>		2N5458		2N5459			
SYMBOL	TEST CONDITIONS	MIN	MAX	MIN	MAX	MIN	MAX	UNITS
I _{GSS}	V _{GS} =15V	-	1.0	-	1.0	-	1.0	nA
I _{GSS}	V _{GS} =15V, T _A =100°C	-	200	-	200	-	200	nA
IDSS	V _{DS} =15V	1.0	5.0	2.0	9.0	4.0	16	mA
BVGSS	I _G =10μA	25	-	25	-	25	-	V
V _{GS(OFF)}	V _{DS} =15V, I _D =10nA	0.5	6.0	1.0	7.0	2.0	8.0	V
C _{rss}	V_{DS} =15V, V_{GS} =0, f=1.0MHz	-	3.0	-	3.0	-	3.0	pF
C _{iss}	V_{DS} =15V, V_{GS} =0, f=1.0MHz	-	7.0	-	7.0	-	7.0	pF
9 _{fs}	V_{DS} =15V, V_{GS} =0, f=1.0kHz	1.0K	5.0K	1.5K	5.5K	2.0K	6.0K	μS
9 _{os}	V_{DS} =15V, V_{GS} =0, f=1.0kHz	-	50	-	50	-	50	μS

2N5457 2N5458 2N5459

SILICON **N-CHANNEL JFETS**



TO-92 CASE - MECHANICAL OUTLINE



DIMENSIONS						
	INCHES		MILLIMETERS			
SYMBOL	MIN	MAX	MIN	MAX		
A (DIA)	0.175	0.205	4.45	5.21		
В	0.170	0.210	4.32	5.33		
С	0.500	-	12.70	-		
D	0.016	0.022	0.41	0.56		
Е	0.100		2.54			
F	0.050		1.27			
G	0.125	0.165	3.18	4.19		
Н	0.080	0.105	2.03	2.67		
	0.015		0.38			

TO-92 (REV: R1)

LEAD CODE:

- 1) Drain 2) Source
- 3) Gate

R1

MARKING:

FULL PART NUMBER



OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- · Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- · PbSn plating options
- · Package details
- · Application notes
- · Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (001)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for JFET category:

Click to view products by Central Semiconductor manufacturer:

Other Similar products are found below:

MCH3914-8-TL-H F5606 2SK2394-6-TB-E CPH5901G-TL-E MCH3914-7-TL-H MCH5908H-TL-E CPH5902G-TL-E CPH5905G-TL-E CPH5905H-TL-E 2SK2394-7-TB-E NSVJ2394SA3T1G 2N3819 PN4393 MMBFJ176 2N4393 U311 2N5397 2SK208-GR(TE85L,F)

MMBF4393LT1G J176_D74Z IF4500 SMP4338 SMP147 SMP4117 SMP5116 SMPJ232 SMPJ310 SMPJ109 SMP4856 IF1330

SMPJ201 SMP4340 SMP5484 IFN5566 2N2609 2N3821 2N3823 2N3970 2N3971 2N3972 2N4091 2N4092 2N4093 2N4118 2N4118A 2N4220 2N4221 2N4221A 2N4338 2N4339