
CBR1-D020S SERIES

SURFACE MOUNT 1 AMP SILICON BRIDGE RECTIFIER





www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CBR1-D020S series types are silicon full wave bridge rectifiers mounted in a durable epoxy surface mount molded case, utilizing glass passivated chips.

NOTE: Also available in Fast Recovery, please contact factory for details.

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: (T _A =25°C unless otherwise noted)	SYMBOL	CBR1- D020S	CBR1- D040S	CBR1- D060S	CBR1- D080S	CBR1- D100S	UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	200	400	600	800	1000	V
DC Blocking Voltage	V_{R}	200	400	600	800	1000	V
RMS Reverse Voltage	V _{R(RMS)}	140	280	420	560	700	V
Average Forward Current (T _A =50°C)	IO			1.0			Α
Peak Forward Surge Current	IFSM			50			Α
Rating for Fusing (t<8.35ms)	I ² t			10			A^2s
Operating and Storage Junction Temperature	T _J , T _{stg}			-65 to +150)		°C

ELECTRICAL CHARACTERISTICS PER DIODE: (TA=25°C unless otherwise noted)


SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I_{R}	V_{R} =Rated V_{RRM}			10	μΑ
I_{R}	V _R =Rated V _{RRM} , T _A =125°C			0.5	mA
V_{F}	I _F =1.0A			1.1	V
CJ	V _R =4.0V, f=1.0MHz		25		pF

CBR1-D020S SERIES

SURFACE MOUNT 1 AMP SILICON BRIDGE RECTIFIER



SMDIP CASE - MECHANICAL OUTLINE



DIMENSIONS						
	INC	HES	MILLIMETERS			
SYMBOL	MIN	MAX	MIN	MAX		
Α	0.004	0.008	0.10	0.20		
В	0.040	0.060	1.02	1.52		
С	0.009		0.23			
D	0.290	0.310	7.37	7.87		
E	0.086	0.098	2.18	2.49		
F	0.038	0.042	0.97	1.07		
G	0.316	0.335	8.03	8.51		
Н	0.195	0.205	4.95	5.21		
J	0.245	0.255	6.22	6.48		
K	0.360	0.410	9.14	10.41		

SMDIP (REV: R1)

MARKING: FULL PART NUMBER

R3 (4-January 2010)



OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- · Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- · PbSn plating options
- · Package details
- · Application notes
- · Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (001)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Bridge Rectifiers category:

Click to view products by Central Semiconductor manufacturer:

Other Similar products are found below:

MB2510 MB252 MB356G MB358G 90MT160KPBF GBJ1504-BP GBU15J-BP GBU15K-BP GBU4A-BP GBU4D-BP GBU6B-E3/45
GSIB680-E3/45 DB101-BP DF01 DF10SA-E345 KBPC50-10S RS405GL-BP G5SBA60-E3/51 GBU10J-BP GBU6M GBU8D-BP
GBU8J-BP GSIB1520-E3/45 36MB140A TB102M MB1510 MB258 MB6M-G MB86 TL401G MDA920A2 TU602 TU810 BR1005-BP
BR101-BP BR84DTP204 BU2008-E3/51 36MB100A KBPC10/15/2501WP KBPC25-02 VS-2KBB60 DF06SA-E345 DF1510S VS40MT160PAPBF W02M GBL02-E3/45 GBU4G-BP GBJ2506-BP GBU6B-E3/51 GSIB15A80-E3/45