

ENHANCED SPECIFICATION SURFACE MOUNT HIGH SPEED SILICON SWITCHING DIODE





www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPD914E is an Enhanced version of the CMPD914 High Speed Switching Diode in a SOT-23 surface mount package, designed for high speed applications.

MARKING CODE: C5DE

FEATURED ENHANCED SPECIFICATIONS:

- ♦ BV_R from 100V min to 120V min. (150V TYP)
- ♦ V_F from 1.0V max to 0.85V max. (0.72V TYP)

MAXIMUM RATINGS: (T _A =25°C)	SYMBOL			UNITS
Continuous Reverse Voltage	V _R	7	5	V
Peak Repetitive Reverse Voltage	V _{RRM}	12	20	v
Continuous Forward Current	١ _F	25	50	mA
Peak Repetitive Forward Current	IFRM	25	50	mA
Peak Forward Surge Current, tp=1.0µs	IFSM	40	00	mA
Peak Forward Surge Current, tp=1.0ms	I _{FSM}	20	00	mA
Peak Forward Surge Current, tp=1.0s	IFSM	10	00	mA
Power Dissipation	PD	35	50	mW
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to	+150	°C
Thermal Resistance	Θ_{JA}	35	57	°C/W
ELECTRICAL CHARACTERISTICS: (T _A =25°C				
SYMBOL TEST CONDITIONS	MIN	TYP	MAX	UNITS
I _R V _R =20V			25	nA
I _R V _R =75V			5.0	μΑ

120 ♦ BV_R I_R=100μA 150 I_F=10mA 0.720 0.850 ٧F V_{F} I_F=100mA 0.915 0.970 CT V_R=0, f=1.0MHz 2.0 $I_{\mbox{\scriptsize R}} = I_{\mbox{\scriptsize F}} = 10 \mbox{\scriptsize mA}, \ \mbox{\scriptsize R}_{\mbox{\scriptsize L}} = 100 \mbox{\scriptsize \Omega}, \ \mbox{\scriptsize Rec.} \ \mbox{to} \ \ 1.0 \ \mbox{\scriptsize mA}$ 4.0 t_{rr}

• Enhanced specification.

♦ ♦ Additional Enhanced specification.

R3 (25-January 2010)

v

V

v

pF

ns





ENHANCED SPECIFICATION

Central[®] Semiconductor Corp.

SURFACE MOUNT HIGH SPEED SILICON SWITCHING DIODE

SOT-23 CASE - MECHANICAL OUTLINE





PIN CONFIGURATION

LEAD CODE: 1) Anode

2) No Connection3) Cathode

MARKING CODE: C5DE

DIMENSIONS						
	INCHES		MILLIMETERS			
SYMBOL	MIN	MAX	MIN	MAX		
А	0.003	0.007	0.08	0.18		
В	0.006	-	0.15	-		
С	-	0.005	-	0.13		
D	0.035	0.043	0.89	1.09		
Е	0.110	0.120	2.80	3.05		
F	0.075		1.90			
G	0.037		0.95			
Н	0.047	0.055	1.19	1.40		
	0.083	0.098	2.10	2.49		
J	0.014	0.020	0.35	0.50		

SOT-23 (REV: R3)

R3 (25-January 2010)

www.centralsemi.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by Central Semiconductor manufacturer:

Other Similar products are found below :

RD0306T-H BAV17-TR BAV19-TR 1N3611 NTE156A NTE525 NTE571 NTE574 NTE5804 NTE5806 NTE6244 1SS181-TP 1SS193,LF 1SS400CST2RA SDAA13 SHN2D02FUTW1T1G LS4151GS08 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR RFUH20TB3S BAS 28 E6327 BAV199-TP BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 LL4151-GS18 053684A SMMSD4148T3G 707803H NSVDAN222T1G SP000010217 CDSZC01100-HF BAV199E6433HTMA1 BAV70M3T5G SMBT2001T1G NTE5801 NTE5800 NTE5808 NTE6240 NTE6248 DLM10C-AT1 BAS28-7 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3