CSHD10-45L

SURFACE MOUNT SILICON POWER SCHOTTKY RECTIFIER 10 AMP, 45 VOLT



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CSHD10-45L is a silicon power Schottky rectifier designed for power applications requiring a low forward voltage drop.





 $\textbf{MAXIMUM RATINGS:} \ (T_{\hbox{\scriptsize C}} = 25 ^{\circ} \hbox{\scriptsize C} \ unless \ otherwise \ noted)$

	SYMBOL		UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	45	V
Average Rectified Forward Current (T _C =120°C)	IO	10	Α
Peak Forward Surge Current, tp=10ms	I _{FSM}	200	Α
Peak Repetitive Reverse Surge Current, tp=2.0µs	I _{RRM}	1.0	Α
Critical Rate of Rise of Reverse Voltage	dv/dt	10,000	V/µs
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to +150	°C
Thermal Resistance	ΘJC	3.5	°C/W

ELECTRICAL CHARACTERISTICS: $(T_C=25^{\circ}C \text{ unless otherwise noted})$


SYMBOL	TEST CONDITIONS	TYP	MAX	UNITS
I_{R}	V _R =45V	40	100	μΑ
I_{R}	V_R =45V, T_C =125°C		15	mA
V_{F}	I _F =10A	0.575	0.75	V
V_{F}	I _F =10A, T _C =125°C		0.55	V


CSHD10-45L

SURFACE MOUNT SILICON POWER SCHOTTKY RECTIFIER 10 AMP, 45 VOLT



DPAK CASE - MECHANICAL OUTLINE






LEAD CODE:

- 1) Anode
- 2) Cathode 3) Anode
- 4) Cathode

Pin 2 is common to the tab (4)

MARKING: FULL PART NUMBER



DIMENSIONS							
	INCHES		MILLIMETERS				
SYMBOL	MIN	MAX	MIN	MAX			
Α	0.083	0.108	2.10	2.75			
В	0.016	0.032	0.40	0.81			
С	0.035	0.063	0.89	1.60			
D	0.203	0.228	5.15	5.79			
E	0.020	-	0.51	-			
F	0.018	0.024	0.45	0.60			
G	0.051	0.071	1.30	1.80			
Н	0.248	0.268	6.30	6.81			
J	0.197	0.217	5.00	5.50			
K	0.209	0.245	5.30	6.22			
L	0.025	0.040	0.64	1.02			
M	0.090	0.115	2.30	2.91			
N	0.012	0.045	0.30	1.14			
Р	0.180		4.60				
R	0.090		2.30				
DPAK (REV: R0)							

R7 (21-January 2013)



OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- · Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- · PbSn plating options
- · Package details
- · Application notes
- · Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (001)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schottky Diodes & Rectifiers category:

Click to view products by Central Semiconductor manufacturer:

Other Similar products are found below:

CUS06(TE85L,Q,M) MA4E2039 D1FH3-5063 MBR0530L-TP MBR10100CT-BP MBR30H100MFST1G MMBD301M3T5G PMAD1103-LF PMAD1108-LF RB160M-50TR RB520S-30 RB551V-30 DD350N18K DZ435N40K DZ600N16K BAS16E6433HTMA1 BAS 3010S-02LRH E6327 BAT 54-02LRH E6327 IDL02G65C5XUMA1 NSR05F40QNXT5G NSVR05F40NXT5G JANS1N6640 SB07-03C-TB-H SB1003M3-TL-W SBAT54CWT1G SBM30-03-TR-E SBS818-TL-E SK32A-LTP SK33A-TP SK34A-TP SK34B-TP SMD1200PL-TP ACDBN160-HF SS3003CH-TL-E STPS30S45CW PDS3100Q-7 GA01SHT18 CRS10I30A(TE85L,QM MBR1240MFST1G MBRB30H30CT-1G BAS28E6433HTMA1 BAS 70-02L E6327 HSB123JTR-E JANTX1N5712-1 VS-STPS40L45CW-N3 DD350N12K SB007-03C-TB-E SB10015M-TL-E SB1003M3-TL-E SK110-LTP