

CF30
PVC
7,5 x d

PVC Power cable | CF30

- for high load requirements
- PVC outer jacket
- oil-resistant
- flame-retardant

Product improvement!

CFRIP
-technology

Strip cables 50% faster!

www.igus.eu/CFRIP



- Conductor** < 10 mm²: stranded conductor in especially bending-resistant version consisting of bare copper wires (following EN 60228). ≥ 10 mm²: conductor cable consisting of pre-leads (following EN 60228).
- Core insulation** Mechanically high-quality, especially low-capacitance TPE mixture.
- Core stranding** Cores stranded in short pitch lengths over a centre for high tensile stresses.
- Core identification** **Energy conductor:** Cores black with white numerals, one core green-yellow.
1. core: U / L1 / C / L+ 2. core: V / L2
3. core: W / L3 / D / L- 4. core: 4 / N
- Outer jacket** Low-adhesion, oil-resistant mixture on the basis of PVC, adapted to suit the requirements in energy chains® (following DIN VDE 0281 Part 13).
Colour: Jet black (similar to RAL 9005)
- CFRIP** Strip cables 50% faster! The tear strip is in the outer jacket (starting from manufacturing date 5/2013).
Video ▶ www.igus.eu/CFRIP
- Bending radius** **moved** minimum 7,5 x d
fixed minimum 4 x d
- Temperature** **moved** +5 °C to +70 °C for use in energy chains® with > 50.000 cycles
-5 °C to +70 °C following DIN EN 60811, part 1-4 chapter 8.2
fixed -20 °C to +70 °C
- v max. unsupported/gliding** 10 m/s, 5 m/s
- a max.** 80 m/s²
- Travel distance** Freely suspended travel distances and up to 100 m for gliding applications, Class 4
- Torsion** ± 90°, with 1 m cable length
- UV-resistant** Medium

Class 5.4.2 (5 high load requirements 4 travel distance up to 100 m 2 oil-resistant)

- Nominal voltage** 600/1000 V (following DIN VDE 0250).
- Testing voltage** 4000 V (following DIN VDE 0281-2).
- Oil** Oil-resistant (following DIN EN 50363-4-1), Class 2.
- Flame-retardant** According to IEC 60332-1-2, CEI 20-35, FT1, VW-1
- Silicon-free** Free from silicon which can affect paint adhesion (following PV 3.10.7 – status 1992).
- UL/CSA** Style 10492 and 2570, 1000 V, 80 °C
- NFPA** Following NFPA 79-2012 chapter 12.9
- CEI** Following CEI 20-35
- CE** Following 2006/95/EG
- Lead free** Following 2011/65/EC (RoHS-II)
- Clean room** According to ISO Class 2. Outer jacket material complies with CF5.10.07, tested by IPA according to standard 14644-1.
- CTP** Certified according to N° C-DE.PB49.V.00397
- EAC** Certified according to N° TC RU C-DE.ME77.B.00964

New! Guaranteed lifetime for this series according to the "chainflex® guarantee club" conditions ▶ Page 22-25

Double strokes*		5 million			7,5 million		10 million	
Temperature, from/to [°C]	v max. [m/s]	unsupported	gliding	a max. [m/s ²]	Travel distance [m]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
-5 / +5					≤ 100	10	11	12
+5 / +60	10		5	80		7,5	8,5	9,5
+60 / +70						10	11	12

* higher number of double strokes possible

Typical application area

- for high load requirements
- light oil influence
- preferably indoor applications, but also outdoor ones at temperatures > 5 °C
- freely suspended travel distances and up to 100 m for gliding applications
- Storage and retrieval units for high-bay warehouses, machining units/packages machines, quick handling, indoor cranes

CF30
PVC
7,5 x d



CF30
PVC
7,5 x d

PVC Power cable | CF30

Class 5.4.2 (5 high load requirements 4 travel distance up to 100 m 2 oil-resistant)

CF30
PVC
7,5 x d

Strip cables 50% faster!



Image exemplary.

Delivery program Part No.	Number of cores and conductor nominal cross section [mm ²]	External diameter max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF30.15.04	4 G 1,5	8,5	64	106
CF30.25.04	4 G 2,5	10,5	106	175
CF30.25.05	5 G 2,5	11,5	132	211
CF30.40.04	4 G 4,0	12,0	174	247
CF30.40.05	5 G 4,0	13,0	218	315
CF30.60.04	4 G 6,0	14,0	253	353
CF30.60.05	5 G 6,0	15,5	317	445
CF30.100.04	4 G 10,0	17,5	435	598
CF30.100.05	5 G 10,0	20,0	547	767
CF30.160.04	4 G 16,0	21,0	697	920
CF30.160.05	5 G 16,0	24,0	879	1166
CF30.250.04	4 G 25,0	25,5	1094	1420
CF30.350.04	4 G 35,0	29,0	1551	1786
CF30.500.04	4 G 50,0	35,0	2222	2768

Note: The mentioned external diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Paired Cables](#) category:

Click to view products by [Igus](#) manufacturer:

Other Similar products are found below :

[7-21000-9](#) [9805 060100](#) [1416402/M12MS/IP20/10](#) [9804 060100](#) [9808 060100](#) [9843 060100](#) [9873 060100](#) [190-038045-00](#) [44A0121-12-996CS2275](#)
[44A0121-20-09-MX](#) [55PC0211-14-9](#) [55PC0216-24-9](#) [55PC0221-22-2/6CS2756](#) [55PC0811-16-9](#) [55PC0811-24-9](#) [55PC1131-20-029-9](#) [Y60912](#)
[CW1922-000](#) [RI55D](#) [9157 060100](#) [2020D0309-0](#) [9774 060100](#) [8334 060100](#) [1350SB 0101000](#) [8342 060100](#) [8740 060U1000](#) [9505 060U1000](#)
[3613 003A1000](#) [44A0121-22-0/9-MX](#) [2412 009U1000](#) [82777 8771000](#) [9406 T35100](#) [3613 D151000](#) [1533R 0101000](#) [1533P 0101000](#) [9272](#)
[006U1000](#) [2413F D15A500](#) [9681 0601000](#) [44A0121-22-6/9-MX](#) [1533R 0061000](#) [RIT1000](#) [1533R 006A1000](#) [9812 060100](#) [2221 B59U1000](#)
[10GX13 D151000](#) [1874A 004A1000](#) [8340 060100](#) [8333 0601000](#) [1533R 0021000](#) [1583A 012U1000](#)