

JIANGSU CHANGJIANG ELECTRONICS TECHNOLOGY CO., LTD

SOD-323 Plastic-Encapsulate Diodes


BAS316 SWITCHING DIODE

FEATURES

- Very Small Plastic Package
- High Switching Speed

APPLICATIONS

• High-Speed Switching in e.g. Surface Mounted Circuits




MARKING: A6"


MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)


Symbol	Parameter	Value	Unit	
V_{RRM}	Peak Repetitive Reverse Voltage	85	V	
V_R	DC Blocking Voltage	75		
lo	Continuous Forward Current 250		mA	
P _D	Power Dissipation	250	mW	
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	500	°C/W	
Tj	Junction Temperature	150	℃	
T _{stg}	Storage Temperature	-55~+150	°C	


ELECTRICAL CHARACTERISTICS(Ta=25℃ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Тур	Max	Unit
Reverse voltage	$V_{(BR)}$	I _R =100μA	100			V
Reverse current	I _R	V _R =25V			30	nA
		V _R =75V			1	μA
	V _F	I _F =1mA			0.715	V
Compard voltage		I _F =10mA			0.855	
Forward voltage		I _F =50mA			1	
		I _F =150mA			1.25	
Total capacitance	C _{tot}	V _R =0V,f=1MHz			1.5	pF
Reverse recovery time	t _{rr}	I _F = I _R =10mA, I _{rr} =0.1×I _R			4	ns









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by Changjiang manufacturer:

Other Similar products are found below:

MMBD3004S-13-F RD0306T-H DSE010-TR-E BAV17-TR BAV19-TR 1N3611 NTE156A NTE574 NTE6244 1SS181-TP 1SS193,LF 1SS400CST2RA SDAA13 SHN2D02FUTW1T1G LS4151GS08 FC903-TR-E 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR 1SS226-TP RFUH20TB3S D291S45T BAV300-TR BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 LL4151-GS18 053684A SMMSD4148T3G 707803H NSVDAN222T1G CDSZC01100-HF LL4150-M-08 1N4454-TR BAV199E6433HTMA1 BAS28-7 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3 NSVM1MA152WKT1G RGP30D-E3/73 BAV99TQ-13-F BAS21DWA-7 NTE6250 NTE582-4 NTE582-6