

# Ultra Clear Protective Lacquer

## Material Safety Data Sheet



Chemtools

Unit 4, 3 Pullman Place  
Emu Plains NSW 2750

Ph: 02 4735 3126

Fax: 02 4735 3746

[info@chemtools.com.au](mailto:info@chemtools.com.au)

[www.chemtools.com.au](http://www.chemtools.com.au)

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** ChemTools Ultra Clear Protective Lacquer Aerosol  
**Part Numbers:** CT-LQR400  
**Product Type:** Protective lacquer for industrial use.  
**Company Address:** ChemTools Pty. Ltd., PO Box 4319, Penrith, NSW 2750  
Ph: 02 4635 3746  
**EMERGENCY PHONE:** Australia: Poisons Information Centre 13 1126  
International: Infotrac (708) 918 1900

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components	CAS #	%	HSIS TWA	HSIS STEL
toluene	108-88-3	10 - 30	50ppm (191mg/m <sup>3</sup> )	150ppm (574mg/m <sup>3</sup> )
acetone	67-64-1	10 - 30	500ppm (1185mg/m <sup>3</sup> )	1000ppm (2375mg/m <sup>3</sup> )
hydrocarbon propellant	68476-85-7	10 - 30	1000ppm (1800mg/m <sup>3</sup> )	-

### 3. HAZARDS IDENTIFICATION

**Hazard Classification:** Hazardous Substance, Dangerous Goods. According to the criteria of SafeWork Australia  
**F, Xi, Xn**

**Risk Phrases:**  
R11 – Highly flammable  
R20/22 - Harmful by inhalation and if swallowed.  
R36/38 – Irritating to eyes and skin.  
R65 – Harmful: may cause lung damage if swallowed.  
R67 – Vapours may cause drowsiness and dizziness.

**Safety Phrases:**  
S2 – Keep out of reach of children  
S7/9 – Keep container tightly closed and in a well ventilated place  
S21 – When using do not smoke  
S23 – Do not breathe vapour.  
S51 – Use only in well ventilated areas.  
S24/25 – Avoid contact with skin and eyes.  
S36/37 – Wear suitable protective clothing and gloves  
S62 - If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

**Overview:** POISON! DANGER! HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. VAPOR HARMFUL. FLAMMABLE LIQUID AND VAPOR. MAY AFFECT LIVER, KIDNEYS, BLOOD SYSTEM, OR CENTRAL NERVOUS SYSTEM. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

**Relevant routes of exposure:** Skin, Inhalation, Eyes

**Potential Health Effects**  
**Inhalation:** May cause respiratory tract irritation. High concentrations of vapours may cause headache, fatigue, drowsiness and dizziness.  
**Skin contact:** May cause allergic skin reaction. May cause skin irritation. Product has a defatting effect on skin.  
**Eye contact:** Prolonged contact may cause dryness of skin.  
**Eye contact:** Contact with eyes will cause irritation.

### 4. FIRST AID MEASURES

**Inhalation:** Remove to fresh air. If symptoms develop and persist, get medical attention.  
**Skin contact:** Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.  
Get medical attention if symptoms occur.  
**Eye contact:** Check for and remove any contact lenses. Immediately flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time.  
Get medical attention.  
**Ingestion:** Do not induce vomiting. Give large quantities of water Rinse mouth thoroughly. Loosen any tight clothing. Keep individual calm. Obtain medical attention. If there are signs of intoxication (drunkenness) then serious health effects may follow (depending on the amount swallowed or inhaled). Treat unconsciousness by placing the person in the coma position. Apply artificial respiration if breathing stops. Immediate medical attention should be sought and the affected person transferred and accompanied to the care of a doctor or hospital.

# Ultra Clear Protective Lacquer

## Material Safety Data Sheet



Chemtools

Unit 4, 3 Pullman Place  
Emu Plains NSW 2750

Ph: 02 4735 3126

Fax: 02 4735 3746

[info@chemtools.com.au](mailto:info@chemtools.com.au)

[www.chemtools.com.au](http://www.chemtools.com.au)

### 5. FIRE-FIGHTING MEASURES

Flash point:	-81°C (Closed Cup) Propellant
Autoignition temperature:	N/A
Flammable/Explosive limits-lower %:	N/A
Flammable/Explosive limits-upper %:	N/A
Extinguishing media:	Alcohol resistant foam, dry chemical or carbon dioxide.
Special fire fighting procedures:	Use water to cool exposed containers. Heating can cause expansion or decomposition leading to violent ruptures of containers. If safe to do so, remove containers from path of fire. Spills and leaks may be washed away with copious volumes of water, fog, or spray. For major fires or where the atmosphere is oxygen deficient or contains unacceptable levels of combustion products, fire-fighters must wear self contained breathing apparatus with full face mask and protective clothing.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Keep run-off water out of sewers and water sources.
Hazchem Code:	2[Y]

### 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:	Extinguish all ignition sources. Ventilate well. Use approved respirator if air contamination is above accepted level. Prevent product from entering drains or open waters.
Clean-up methods:	Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

### 7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Avoid breathing vapour and mist. Wash thoroughly after handling.
Storage:	For safe storage, store at or below 38°C (100°F). Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.
Incompatible products:	Refer to Section 10.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	No specific ventilation requirements noted, but forced ventilation may still be required if concentrations exceed occupational exposure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves, butyl rubber gloves.
Eye/face protection:	Safety goggles or safety glasses with side shields. Eye wash facilities should be provided in all areas where the product is handled.
See Section 2 for exposure limits.	

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol.
Colour:	Clear, colourless.
Odour:	Organic, Aromatic.
pH:	Not available
Boiling point/range:	56-110°C. Bulk
Melting point/range:	-95°C Bulk
Specific gravity:	0.8 at 20°C. Bulk
Vapour density:	3.14 at 20°C (air=1) Bulk
Evaporation rate:	2.24 (ASTM D-3539, nBuAc=1) Bulk
Solubility in water:	Partially soluble.

### 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of use.
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Oxides of carbon.
Incompatibility:	Strong oxidizers. Strong acids. Chlorine, Nitrogen tetroxide
Conditions to avoid:	See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

### 11. TOXICOLOGICAL INFORMATION

Product toxicity data:	
toluene	Oral: LD <sub>50</sub> 636 mg/Kg (rat). Skin: LD <sub>50</sub> 14,100mg/Kg (rabbit) Inhalation LC <sub>50</sub> :49g/m <sup>3</sup> /4hr (rat)

# Ultra Clear Protective Lacquer

## Material Safety Data Sheet

acetone  
Hydrocarbon propellant

Irritation Data: 500mg (skin rabbit), Moderate. 2mg/24hr (eye rabbit) Severe.  
Has shown some evidence of reproductive effects in laboratory animals IARC Category 3  
Oral: LD<sub>50</sub> 5800 mg/Kg (rat). Inhalation LC<sub>50</sub>: 50,100mg/Kg (rat)  
Irritation: 20mg severe (eye rabbit Standard Draize).  
Investigated as a tumorigen, mutagen, reproductive effector

N/A

### 12. ECOLOGICAL INFORMATION

**Acute Toxicity**  
**Mobility:**  
**Persistence/degradability:**  
**Environmental Fate:**

Fish: LC<sub>50</sub> 10-100mg/l/96hr  
Partly dissolves in water  
If product enters soil, it will be highly mobile and may contaminate groundwater  
Biodegradable and volatile.  
When released into the soil, this material may evaporate to a moderate extent.  
When released into the soil, this material is expected to leach into groundwater.  
When released into the soil, this material may biodegrade to a moderate extent.  
When released into water, this material may evaporate to a moderate extent.  
When released into water, this material may biodegrade to a moderate extent.  
When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life of less than 1 day. This material is not expected to significantly bioaccumulate. This material has a log octanol-water partition coefficient of less than 3.0. Bioconcentration factor = 13.2 (eels)

### 13. DISPOSAL CONSIDERATIONS

**Recommended method of disposal:** Recover or recycle if possible. Dispose of according to Federal, State and local governmental regulations.

**Container disposal:** Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Recycle if possible.

### 14. TRANSPORT INFORMATION

**ADG:**  
**Proper shipping name:** Aerosols  
**UN No.:** 1950  
**Class:** 2.1  
**Hazchem code:** 2[Y]  
**Packing group:** none



**IMDG:**  
**Proper shipping name:** Aerosols  
**Identification No.:** 1950  
**Class:** 2  
**Packing group:** none  
**Marine pollutant:** No

**IATA (country variations may occur):**  
**Proper shipping name:** Aerosols  
**Identification No.:** UN 1950  
**Class:** 2.1  
**Packing group:** none

### 15. REGULATORY INFORMATION

**Poisons Schedule (SUSDP):** Schedule S6 Poison

### 16. OTHER INFORMATION

**Abbreviations/Acronyms:** ACGIH – American Conference of Government Industrial Hygienists.  
ADG – Australian Dangerous Goods.  
HSIS – Hazardous Substances Information System.  
IARC – International Agency for Research on Cancer.  
NIOSH – National Institute of Occupational Health and Safety.  
PEL – Permissible Exposure Limit.  
STEL – Short Term Exposure Limit.  
SUSDP – Standard for the Uniform Scheduling of Drugs and Poisons.  
TLV – Threshold Limit Value.



**Chemtools**

Unit 4, 3 Pullman Place  
Emu Plains NSW 2750

Ph: 02 4735 3126

Fax: 02 4735 3746

[info@chemtools.com.au](mailto:info@chemtools.com.au)

[www.chemtools.com.au](http://www.chemtools.com.au)

# Ultra Clear Protective Lacquer

TWA – Time Weighted Average.

**Date of MSDS**

June 2010

## **DISCLAIMER:**

The information contained within this MSDS applies only to the ChemTools product to which the sheet relates. The information provided is based on our best knowledge at the time of issue.

The information contained within this MSDS is believed to be accurate and is given in good faith. However, no warranty is made, either expressed or implied, regarding its accuracy or any liability arising out of the use of the information herein or the product supplied.

When used in other preparations, formulations, or in mixtures, it is necessary to ascertain whether the classifications of the hazards have changed. The attention of the user is drawn to the possibility of creating other hazards when the product is used for purpose other than that for which it was recommended. In such cases, a reassessment may be necessary and should be made by the user.

This safety data sheet should only be used and reproduced in order that the necessary measures are taken relating to the protection of health and safety at work.

It is the responsibility of the handlers to pass on the totality of the information contained within this document to any subsequent person(s) who will come in to contact with, handle or use this product in any way.

They should check the adequacy of the information provided within this MSDS before passing it on to their customers/staff.

**End of MSDS**

**Material Safety Data Sheet**



**Chemtools**

Unit 4, 3 Pullman Place  
Emu Plains NSW 2750

**Ph:** 02 4735 3126

**Fax:** 02 4735 3746

[info@chemtools.com.au](mailto:info@chemtools.com.au)

[www.chemtools.com.au](http://www.chemtools.com.au)

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [chemtools](#) manufacturer:*

Other Similar products are found below :

[CT-FRGP1L](#) [WKNC-4-25](#) [CT-ISO1L](#) [CT-PCBW5L](#) [CT-ACC400](#) [WKNC-1-5](#) [CT-FRGP300](#) [CT-CC350](#) [CT-CBC300](#) [8401-20](#) [WKNC-2-5](#)  
[WKNC-5-5](#) [CT-PCBW20L](#) [CT-NC-DP](#) [WKNC-4-5](#) [WKNC-3-5](#)