# Solder Wick

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** ChemTools Solder Wick

**Product Type:** Cupronickel braid for solder removal

**WKNC** Part Number:

Available Sizes: 5 Feet & 25 Feet

Available Colours: White, Yellow, Green, Blue, Brown

Company Address: ChemTools Pty. Ltd.,

PO Box 463, Emu Plains, NSW 2750

Ph: 02 4735 3126

**EMERGENCY PHONE:** Australia: Poisons Information Centre 13 1126

International: Infotrac (708) 918 1900

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components	CAS#	%	TWA(NOHSC)	STEL
Copper	7440-50-8	45	0.2mg/m³ (fume)	-
Nickel	7440-02-0	54	1mg/m <sup>3</sup>	-
Modified Rosin	8050-097	1	0.1mg/m³ (rosin core solder pyrolysis products (as formaldehyde))	

### 3. HAZARDS IDENTIFICATION

Relevant routes of exposure: Harmful by inhalation, in contact with skin and if swallowed.

Potential Health Effects

Inhalation: Fumes and/or dusts produced by this product may be hazardous in case of inhalation.

Skin contact: This product may be hazardous in the case of skin contact (irritant, sensitiser).

Eye contact: This product maybe hazardous in the case of eye contact (irritant).

Ingestion: This product may be hazardous in case of ingestion.

### 4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical attention if symptoms occur. Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the

time. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Keep individual calm.

Obtain medical attention. Wire strands could cause internal digestive tract bleeding.

### 5. FIRE-FIGHTING MEASURES

Flash point: Non-flammable Autoignition temperature: Not available Flammable/Explosive limits-lower %: Not available Flammable/Explosive limits-upper %: Not available

Small fire: Use dry chemical powder. Large fire: Use water spray, fog or foam. Extinguishing media:

Special fire fighting procedures: None Unusual fire or explosion hazards:

Hazardous combustion products: Oxides of carbon. Irritating organic vapours. Some metallic oxides



### Chemtools

Unit 4, 3 Pullman Place Emu Plains NSW 2750

Ph: 02 4735 3126 Fax: 02 4735 3746 info@chemtools.com.au www.chemtools.com.au

## **6. ACCIDENTAL RELEASE MEASURES**

**Environmental precautions:** Prevent product from entering drains or open waters. Clean-up methods: Store in a partly filled, closed container until disposal.

### 7. HANDLING AND STORAGE

Avoid contact with eyes, skin and clothing. When using do not eat, drink or smoke. Avoid breathing vapour and mist. Wash thoroughly after handling. Ensure sufficient ventilation of the area.

Storage: Keep in a cool, well ventilated area. Keep container tightly closed until ready for use.

Incompatible products: Refer to Section 10.

# Solder Wick

## ing controls:

# Material Safety Data Shee

tibility:

### - Delayed effects



Chemtools

Unit 4, 3 Pullman Place Emu Plains NSW 2750

Ph: 02 4735 3126 Fax: 02 4735 3746 info@chemtools.com.au www.chemtools.com.au

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ensure there is sufficient ventilation of the area, forced ventilation may still be required if concentrations exceed occupational

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

Safety goggles or safety glasses with side shields.

Neoprene gloves. butyl rubber gloves. Natural rubber gloves.

Eye/face protection: See Section 2 for exposure limits.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid (metallic braid with fine crystalline resin layer)

Colour: Metallic, Brown

Odour: None Not applicable pH:

Melting point/range: 1100°C Boiling point/range: 2562°C Vapour density: Not available **Evaporation rate:** Not available Solubility in water: Negligible

### 10. STABILITY AND REACTIVITY

Stability: Stable. Hazardous polymerization: Will not occur.

Hazardous decomposition products: Oxides of carbon. Irritating and toxic organic vapours.

Strong oxidizers. Strong acids.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

### 11. TOXICOLOGICAL INFORMATION

Skin Exposure:

- Symptoms: Possible allergic rash reaction. See Section 4, this document

- Immediate Effects - Delayed effects - Chronic Effects - Special Health effects

Eye Contact:

- Symptoms: Possible danger of metal fragments. See Section 4, this document

- Immediate Effects - Delayed effects - Chronic Effects - Special Health effects

Inhalation:

- Symptoms:

- Immediate Effects If the product is exposed to temperatures in excess of 82 °C, local ventilation

must be used.

- Delayed effects - Chronic Effects

- Special Health effects

Ingestion:

- Symptoms: - Immediate Effects

May be moderately irritating to stomach lining. Induce vomiting if instructed by medical personnel.

 Chronic Effects - Special Health effects

### 12. ECOLOGICAL INFORMATION

Not applicable. Mobility: Not applicable. Persistance and Biodegradability: **Bioaccumulative Potential:** Not applicable. Other Adverse Effects: Not applicable.

### 13. DISPOSAL CONSIDERATIONS

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

# **Solder Wick**

### 14. TRANSPORT INFORMATION

ADR / RID:

UN No: Harmonised Tariff Code: #7408.22.1000

ADR Class:

Road & Sea Freight Classification Cupronickel wire coated with resin flux

Hazard ID No: Labelling:

Packing group: Validated license # / General license symbol: "NLR"

**Classification Code:** 

Water Transportation (IMO/IMDG):

UN No: Class:

Packing group:

EmS:

Labelling:

International Air Transportation (ICAO/IATA):

UN No: Labelling: Packing group: Packing Instructions:

### 15. REGULATORY INFORMATION

Hazard Symbols: This product does not require warning labels due to Hazards Classification as designated in Section 3

Risk Phrases: R36/37/38: Irritating to eyes, respiratory system, skin

Safety Phrases: S14: Keep away from children

S22: Do not breath dust S39: Wear eye/face protection

### **DISCLAIMER:**

The information contained within this MSDS applies only to the ChemTools product to which the sheet relates.

The information provided is based on our best knowledge at the time of issue.

The information contained within this MSDS is believed to be accurate and is given in good faith. However, no warranty is made, either expressed or implied, regarding its accuracy or any liability arising out of the use of the information herein or the product supplied.

When used in other preparations, formulations, or in mixtures, it is necessary to ascertain whether the classifications of the hazards have changed. The attention of the user is drawn to the possibility of creating other hazards when the product is used for purpose other than that for which it was recommended. In such cases, a reassessment may be necessary and should be made by the user.

This safety data sheet should only be used and reproduced in order that the necessary measures are taken relating to the protection of health and safety at work.

It is the responsibility of the handlers to pass on the totality of the information contained within this document to any subsequent person(s) who will come in to contact with, handle or use this product in any way.

They should check the adequacy of the information provided within this MSDS before passing it on to their customers/staff.

Date of issue: July 2009



**Chemtools** 

Unit 4, 3 Pullman Place Emu Plains NSW 2750

Ph: 02 4735 3126 Fax: 02 4735 3746 info@chemtools.com.au www.chemtools.com.au

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for chemtools manufacturer:

Other Similar products are found below:

<u>CT-FRGP1L WKNC-4-25 CT-CBC300 CT-ISO1L CT-PCBW5L CT-ACC400 WKNC-1-5 CT-FRGP300 CT-CC350 8401-20 WKNC-2-5 WKNC-5-5 CT-PCBW20L CT-NC-DP WKNC-4-5 WKNC-3-5</u>