CHEMTRONICS Technical Data Sheet

CW7270

CircuitWorks® Silicone Free Heat Sink Grease

PRODUCT DESCRIPTION

CircuitWorks[®] Silicone Free Heat Sink Grease facilitates heat transfer away from electrical/electronic components and into heat sinks. This silicone-free compound shows no creep or migration over a wide temperature range. Thickened with a proprietary thermally conductive zinc oxide ceramic, the CircuitWorks[®] Silicone Free Heat Sink Grease creates an effective heat sink interface in electrical/electronic equipment.

- Exceeds MIL-C-47113 for thermal conductivity
- Noncorrosive
- High dielectric strength
- Low migration
- Stable from -15°C to 200°C
- Nonflammable

TYPICAL APPLICATIONS

CircuitWorks® Silicone Free Heat Sink Grease may be used for electronics applications including:

- Effective Thermal Coupler for any Heat Sink Device
- Nonflammable Protective Coating
- High Voltage Corona Protection
- Excellent for Improving Readings on Contact Type Thermocouples
- Ideal for Silicone Sensitive Environments

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

Color	White
Specific Gravity @ 25°C (77°F)	2.4
Usable Temperature	5°F (-15°C) to
Range	392°F (200°C)
Dielectric Strength, volts/mil	500
Dielectric Constant @ 100 Hz	4.4
Dissipation Factor @ 100 Hz	0.005
Volume Resistivity, ohm-cm	1×10^{14}
Arc Resistance, seconds	120
Thermal Conductivity,	
Cal-cm/sec-cm ² -°C	1.7×10^{-3}
BTU-in/hr-ft ² -°F	4.92
W/m°K	0.71
Shelflife	5 years
RoHS Compliant	ROHS WEEE Compliant

COMPATIBILITY

CircuitWorks® Silicone Free Heat Sink Grease is generally compatible with most materials used in printed circuit board fabrication.

Material	Compatibility
Ceramic	Good
Clean Metals	Good
Glass	Good
Silicone Resins	Good
Painted Surfaces	Good
Plastic Surfaces	Good
Vulcanized Silicone Rubber	Good

USAGE INSTRUCTIONS

For industrial use only. Read MSDS carefully prior to use.

Application:

Apply CircuitWorks[®] Silicone Free Heat Sink Grease directly to surface or use the application tip. Remove cap from syringe and gently depress the plunger. Spread the material in a thin layer on all mounting and threaded surfaces of the device and the chassis.

Clean-Up: Wipe away excess material using a Chemtronics[®] ControlWipesTM and thoroughly clean the surface using Chemtronics[®] Electro-Wash[®] PX.

TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

AVAILABILITY CW7270

8 gm / 0.28 oz syringe

ENVIRONMENTAL IMPACT DATA				
ODP	None	VOC	None	
HCFC	None	HFC	None	

Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. Hydrochlorofluorocarbons (HCFCs) are regulated under the Montreal Protocol as Class II ozone depleting substances. Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s). Hydrofluorocarbons (HFCs) are not currently regulated.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

CHEMTRONICS 8125 COBB CENTER DRIVE KENNESAW, GA 30152 1-770-424-4888 REV. C (08/13)

Chemtronics®, Electro-Wash® and CircuitWorks® are registered trademarks of Chemtronics. All rights reserved. ControlWipes™ is a trademark of Chemtronics. All rights reserved.

DISTRIBUTED BY:	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Chemicals category:

Click to view products by Chemtronics manufacturer:

Other Similar products are found below:

DP-605NS 3045-QT 3125-9S 3748-Q-58"x8" FO-25DT S1009-KIT-A-CS8606 DP100-200ML 1743-2FP 152-KA-NC 826-450G 9729

9223 9945 7000000275 1601 8330-19G 842AR-15ML 841AR-150ML 842AR-P 843WB-15ML 8462-85ML 4354-1L 838AR-P 838AR
15ML 419D-P-BK 419D-P-GR 419D-P-WH 8MT-450 8MT-25 832HD-25ML 832FX-450ML 834ATH-375ML 832HD-400ML 8617-1P

843AR-340G 843ER-800ML 9310-300ML 847-1P 4228-225ML 419D-55ML 8800-375ML 8810-375ML 8820-2.55L 419E-340G 842UR
12ML 419D-1L CW3300WHITE CW2205 10447 9620-945ML