## CHEMTRONICS Technical Data Sheet

## **TDS #CW8500**

# **CircuitWorks<sup>®</sup> No-Clean Tacky Flux**

#### **PRODUCT DESCRIPTION**

CircuitWorks<sup>®</sup> No-Clean Tacky Flux is a Type ROL0 formulation designed for BGA rework requiring high-reliability, stability and cleanliness. CircuitWorks<sup>®</sup> No-Clean Tacky Flux gel composition holds the BGA component in position even with board movement. Its lower viscosity allows easy application and contains no ionic material. CircuitWorks<sup>®</sup> No-Clean Tacky Flux is suitable for clean room applications.

- Excellent wetting ability
- Long tack time
- Noncorrosive, halide and halogen free
- Meets IPC requirements for ROL0, No Clean
- Excellent consistency
- Stable viscosity
- Conforms to ISO 9454
- Meets Bellcore TR-NWT-000078 requirements
- Meets DIN EN 29454-1 1.1.3.C classification

#### **TYPICAL APPLICATIONS**

CircuitWorks<sup>®</sup> No-Clean Tacky Flux may be used for electronics applications including:

- BGA rework and repair
- Sphere attachment to BGA
- Surface Mount Device Pads
- Switches
- Sockets

#### TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

#### **Properties**

Flux Type	No-Clean ROL0	
Flash Point (TCC)	>140°C (284°F)	
Appearance	Light Tan to Dark Brown	
Odor	Slight	
Shelf life	2 years	
<b>RoHS Compliant</b>		

#### COMPATIBILITY

CircuitWorks<sup>®</sup> No-Clean Tacky Flux is generally compatible with most materials used in the electronics industry. As with any cleaning agent, material compatibility should be determined on a non-critical area prior to use.

#### **USAGE INSTRUCTIONS**

For industrial use only. Read MSDS carefully prior to use.

**Flux Application:** CircuitWorks<sup>®</sup> No-Clean Tacky Flux should only be applied to BGA rework areas on the circuit board, and not the entire board. Remove cap from syringe and gently depress the plunger. Spread the material over the BGA application area. Use a Control Wipe<sup>TM</sup> dry wipe to remove flux buildup from applicator tip.

**Cleaning:** No-Clean Tacky Flux residue does not need to be removed after reflow, but can be removed if required. Chemtronics Flux-Off<sup>®</sup> No Clean Plus is an ideal cleaner for effective flux removal.

#### TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.** 

#### AVAILABILITY

 CW8500
 3.5 gm (0.12 oz) Syringe

 CW8510
 12 gm EFD Dispenser

ENVIRONMENTAL IMPACT DATA				
ODP	None	VOC	No	
HCFC	None	HFC	None	

Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. Hydrochlorofluorocarbons (HCFCs) are regulated under the Montreal Protocol as Class II ozone depleting substances. Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s). Hydrofluorocarbons (HFCs) are not currently regulated.

**NOTE:** This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly.

CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

#### CHEMTRONICS 8125 COBB CENTER DRIVE KENNESAW, GA 30152 1-770-424-4888 Rev. C (08/13)

Chemtronics Flux-Off<sup>®</sup> and CircuitWorks<sup>®</sup> are registered trademarks of Chemtronics. All rights reserved. ControlWipe<sup>™</sup> is a trademark of Chemtronics. All rights reserved.

#### **DISTRIBUTED BY:**

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Soldering Flux category:

Click to view products by Chemtronics manufacturer:

Other Similar products are found below :

 8351-1L
 8351-125ML
 051-0001
 051-0002
 051-0007
 051-0009
 051-0010
 053-1001
 053-1002
 053-1003
 8342-50G

 ART.AGT-088
 270WR
 ART.AGT-089
 ART.AGT-094
 ART.AGT-179
 CW8100
 SSS500ML
 63-0000-0186
 63-0000-0951
 63-0000-0977

 63-0000-1544
 83-1000-0186
 83-1000-0951
 83-1097-2331
 8341-10ML
 835-100ML
 SF-02
 CW8700
 FL22W
 SMD291SNL50T3

 SMD291AX50T3
 SMD291/30CC
 CQ2LF
 CQ4LF
 CQ4LF-0.5
 CQ4LF-1.0
 SMD291
 SMD291AX
 SMD291AX
 SMD291AX10