

此商品编号对应的规格参数是: 100uF 10V 5*5

此商品的实物图片为:





KF Series

5mmL(高), +105°C


FEATURES

 Super miniature, 5mmL, high temperature, suitable for use in electronic circuit of high density assembly of videocorder, remote controller, VCD etc.



Item	Performance Characteristics								
Operating Temperature Range	-40 to +105°C								
Rated Working Voltage Range	4 to 50V								
Nominal Capacitance Range	0.1 to 330μF								
Capacitance Tolerance	±20% (120Hz, +20°C)								
Leakage Current	I ≤ 0.01CV or 3(μA) whichever is greater me	≤ 0.01CV or 3(µA) whichever is greater measured after 2 minutes application of rated working voltage at +20 C							
tan δ (120Hz, +20°C)	Working Voltage (V)	4	6.3	10	16	25	35	50	
	tan δ (max.)	0.37	0.28	0.24	0.20	0.16	0.13	0.12	
Low Temperature Characteristics	Impedance ratio max. at 120Hz								
	Working Voltage (V)	4	6.3	10	16	25	35	50	
	Z-25°C / Z+20°C	6	3	3	2	2	2	2	
	Z-40°C / Z+20°C	12	8	5	4	3	3	3	
High Temperature Loading	Test conditions Duration : 1000 Ambient temp. : +105 Applied voltage : Rate with	Post test requirements at +20°C Leakage current : ≤ Initial specified value Cap. change : within ±20% of initial measured value (4V: within ±30%) tan δ : ≤200% of initial specified value				measured value			
Shelf Life	Test conditions	Post test requirements at +20°C							
	Duration : 1000	Leal	kage curre	t:≤Initial specified value					
	Ambient temp. : +105	Cap	. change	: within $\pm 20\%$ of initial measured value					
	Applied voltage : (Non				(4V: within± 30%)				
				tan 8	5	:≤200% of	initial speci	fied value	
Others	JIS C - 5101 (IEC 60384)								

CASE SIZE TABLE



φD	4	5	6.3	8
F	1.5	2.0	2.5	2.5
φd		0.	45	

RIPPLE CURRENT MULTIPLIER

Frequency Coefficient						
Cap(µF) Coefficient Freq.(Hz)	50	120	300	1k	10k~	
≤ 47	0.75	1.00	1.35	1.57	2.00	
68~330	0.80	1.00	1.23	1.34	1.50	



KF Series

5mmL(高), +105°C

STANDARD RATINGS

Voltag	e (Code)	4V	(0G)	6.3V (0J)		10V (1A)		16V (1C)	
Сар.(µF)	Code	Case Size	Ripple Current	Case Size	Ripple Current	Case Size	Ripple Current	Case Size	Ripple Curren
0.1	104								
0.22	224								
0.33	334								
0.47	474								
1	105								
2.2	225								
3.3	335								
4.7	475								
10	106							4 x 5	18
22	226	4 x 5	22	4 x 5	22	4 x 5	24	5 x 5	30
33	336	5 x 5	30	5 x 5	30	5 x 5	35	6.3 x 5	40
47	476	5 x 5	36	5 x 5	36	6.3 x 5	46	6.3 x 5	50
100	107	6.3 x 5	60	6.3 x 5	60	6.3 x 5	67	6.3 x 5	73
220	227			8 x 5	103	8 x 5	116	8 x 5	126
330	337			8 x 5	127				

Maximum Allowable Ripple Current (mA rms) at 105°C 120Hz

Case Size ¢D x L(mm)

Voltag	ge (Code)	25\	/ (1E)	35\	/ (1V)	50\	/ (1H)	
Cap.(µF)	Code	Case Size	Ripple Current	Case Size	Ripple Current	Case Size	Ripple Current	
0.1	104					4 x 5	1.0	
0.22	224					4 x 5	2.6	
0.33	334					4 x 5	3.2	
0.47	474					4 x 5	3.8	
1	105					4 x 5	6.2	
2.2	225			4 x 5	7	4 x 5	11	
3.3	335			5 x 5	11	4 x 5	14	
4.7	475	4 x 5	13	4 x 5	15	5 x 5	19	
10	106	5 x 5	20	5 x 5	25	6.3 x 5	30	
22	226	6.3 x 5	38	6.3 x 5	48	8 x 5	52	
33	336	6.3 x 5	48	6.3 x 5	59	8 x 5	63	
47	476	6.3 x 5	58	8 x 5	82			
100	107	8 x 5	97					

Maximum Allowable Ripple Current (mA rms) at 105°C 120Hz

Case Size $\phi D \times L(mm)$

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Aluminium Electrolytic Capacitors - Radial Leaded category:

Click to view products by Chengxing manufacturer:

Other Similar products are found below:

NRELS102M35V16X16C.140LLF ESRG160ETC100MD07D 227RZS050M 335CKR250M 476CKH100MSA 477CKR100M 107CKR010M 107CKH063MSA RJH-25V222MI9# RJH-35V221MG5# B43827A1106M8 RJH-50V221MH6# EKYA500ELL470MF11D B41022A5686M6 ESRG250ELL101MH09D EKMA160EC3101MF07D RJB-10V471MG3# ESMG160ETD221MF11D EKZH160ETD152MJ20S RJH-35V122MJ6# EGXF630ELL621ML20S RBD-25V100KE3#N EKMA350ELL100ME07D ESMG160ETD101ME11D ELXY100ETD102MJ20S EGXF500ELL561ML15S EKMG350ETD471MJ16S 35YXA330MEFC10X12.5 RXW471M1ESA-0815 ELXZ630ELL221MJ25S ERR1HM1R0D11OT LPE681M30060FVA LPL471M22030FVA HFE221M25030FVA LKMD1401H221MF B41888G6108M000 EKMA160ETD470MF07D UHW1J102MHD6 EKMG500ETD221MJC5S LKMK2502W101MF LKMD1401H181MF LKMI2502G820MF LKMJ2001J122MF LKML2501C472MF LKMJ4002C681MF 450MXH330MEFCSN25X45 450MXK330MA2RFC22X50 63ZLH560MEFCG412.5X30 ELH2DM331O25KT ELH2DM471P30KT