


ALUMINIUM ELECTROLYTIC CAPACITORS SPECIFICATION FOR APPROVAL 铝电解电容规格承认书			
CUSTOMER 客户		MANUFACT 供货方	
USED SPEC 通用规格	470uf/25V	KD SCODE 品名	铝电解电容
TYPE'S DIMENSIONS(MM) 型状及尺寸 		D:	8
		L:	12
		F:	3.5
SPECIFICATIONS 规格			
OPERATING TEMPERATURE RANGE 使用温度		-40~105℃	
RATED VOLTAGE 额定电压		25V	
NOMINAL CAPACITANCE 标称容量		470uf	
CAPACITY TOLERANCE 电容量允许偏差		±20%	
LEAKAGE CURRENT 漏电流		小于 117.5uA (加额定电压两分钟后读数)	
TANGENT OF LOSS ANGLE (20±5℃ 120Hz) 损耗角正切		<0.14	
ENDURANCE (105℃ 2000h) 耐久性		1. I<初始规定值 2. ΔC/C<30% 3. tga<150 初始规定值	
OTHERS 其他			
CUSTOMER'S SIGNATURE 贵公司承认栏			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - Radial Leaded](#) category:

Click to view products by [Chengxing](#) manufacturer:

Other Similar products are found below :

[NRELS102M35V16X16C.140LLF](#) [ESRG160ETC100MD07D](#) [227RZS050M](#) [335CKR250M](#) [476CKH100MSA](#) [477CKR100M](#)
[107CKR010M](#) [107CKH063MSA](#) [RJH-25V222MI9#](#) [RJH-35V221MG5#](#) [B43827A1106M8](#) [RJH-50V221MH6#](#) [EKYA500ELL470MF11D](#)
[B41022A5686M6](#) [ESRG250ELL101MH09D](#) [EKMA160EC3101MF07D](#) [RJB-10V471MG3#](#) [ESMG160ETD221MF11D](#)
[EKZH160ETD152MJ20S](#) [RJH-35V122MJ6#](#) [EGXF630ELL621ML20S](#) [RBD-25V100KE3#N](#) [EKMA350ELL100ME07D](#)
[ESMG160ETD101ME11D](#) [ELXY100ETD102MJ20S](#) [EGXF500ELL561ML15S](#) [EKMG350ETD471MJ16S](#) [35YXA330MEFC10X12.5](#)
[RXW471M1ESA-0815](#) [ELXZ630ELL221MJ25S](#) [ERR1HM1R0D11OT](#) [LPE681M30060FVA](#) [LPL471M22030FVA](#) [HFE221M25030FVA](#)
[LKMD1401H221MF](#) [B41888G6108M000](#) [EKMA160ETD470MF07D](#) [UHW1J102MHD6](#) [EKMG500ETD221MJC5S](#) [LKMK2502W101MF](#)
[LKMD1401H181MF](#) [LKMI2502G820MF](#) [LKMJ2001J122MF](#) [LKML2501C472MF](#) [LKMJ4002C681MF](#) [450MXH330MEFCSN25X45](#)
[450MXK330MA2RFC22X50](#) [63ZLH560MEFCG412.5X30](#) [ELH2DM331O25KT](#) [ELH2DM471P30KT](#)