

Liquid Flux No-Clean in 10ml (0.34oz) Pen w/tip

Product Highlights

A liquid flux that is non-flammable
No-Clean
Water-Based, leaves no residues
VOC Free, Halide Free, Rosin Free
Ideal for all rework, solder, and de-solder applications
Excellent wetting
Easily cleaned with isopropyl alcohol (IPA)
Can be used with Leaded and Lead-Free applications

RoHS 3 and REACH compliant



Specifications

| | |
|----------------------|--|
| Flux Type: | No-Clean Liquid Flux (for Leaded and Lead-Free applications) |
| Flux Classification: | ORL0 |
| VOC Content: | VOC Free |
| Specific Gravity: | 1.01 |
| Packaging: | 10ml Pen |
| Shelf Life: | Refrigerated >24 months, Unrefrigerated >24 months |

Dispensing

Gently press tip into work piece (depress tip) to dispense.

Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

Cleaning

This is a no-clean liquid flux, post-use cleaning is not required.

Conforms to the following Industry Standards:

| | |
|--|-----|
| J-STD-004B, Amendment 1 (Solder Fluxes): | Yes |
| RoHS 3 Directive 2015/863/EU: | Yes |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Soldering Flux](#) category:

Click to view products by [Chip Quik](#) manufacturer:

Other Similar products are found below :

[8351-1L](#) [8351-125ML](#) [051-0001](#) [051-0002](#) [051-0003](#) [051-0007](#) [051-0008](#) [051-0009](#) [053-1000](#) [053-1001](#) [053-1002](#) [053-1003](#) [8342-50G](#)
[ART.AGT-088](#) [270WR](#) [ART.AGT-089](#) [ART.AGT-094](#) [ART.AGT-179](#) [CW8100](#) [SSS500ML](#) [63-0000-0186](#) [63-0000-0977](#) [63-0000-1544](#)
[83-1000-0186](#) [83-1000-0951](#) [83-1097-2331](#) [8341-10ML](#) [835-100ML](#) [SF-01](#) [SF-02](#) [CW8700](#) [FL22W](#) [SMD291SNL50T3](#) [SMD291AX50T3](#)
[SMD291/30CC](#) [CQ2LF](#) [CQ4LF](#) [CQ4LF-0.5](#) [CQ4LF-1.0](#) [SMD291](#) [SMD29175G](#) [SMD291AX](#) [SMD291AX10](#) [SMD291AX250T3](#)
[SMD291NL](#) [SMD291ST2CC6](#) [SMD291ST8CC](#) [SMD4300TF](#) [CW8100](#) [CW8200](#)