

REH1 Water-Soluble Nickel Tack Flux in 5cc/5g Syringe w/plunger and tips

Product Highlights

Water-Soluble Tacky Flux for Nickel Soldering

Higher Activity (REH1)

Better Wetting

Designed for Hard to Solder Surfaces including:

- Nickel
- Nickel Plated Copper
- Copper

Water-Soluble, Remove with Hot Water (60°C+) after soldering

RoHS 3 and REACH compliant



Specifications

Flux Type:	Synthetic Water-Soluble (for Leaded and Lead-Free applications)
Flux Classification:	REH1 (Must be cleaned off post-use using Hot Water (60°C+), Flux Remover or IPA)
Flux Activation Temperature:	140°C (284°F)
Packaging:	5cc/5g Luer Lock Manual Syringe
Shelf Life:	Refrigerated >24 months, Unrefrigerated >24 months

Stencil Life

>8 hours @ 20-50% RH 22-28°C (72-82°F)

>4 hours @ 50-70% RH 22-28°C (72-82°F)

Stencil Cleaning

Automated stencil cleaning systems for both stencil and misprinted boards. Manual cleaning using isopropyl alcohol (IPA).

Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). Do not freeze. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

Conforms to the following Industry Standards:

J-STD-004B, Amendment 1 (Solder Fluxes):

Yes

RoHS 3 Directive (EU) 2015/863:

Yes

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Solder](#) category:

Click to view products by [Chip Quik](#) manufacturer:

Other Similar products are found below :

[701-2758](#) [707-1811](#) [91362-6](#) [13-217-3-01](#) [P10695](#) [SN63WRAP3-.022-1-LB](#) [599Z](#) [707-0441-26](#) [707-1810](#) [601Y](#) [24-9574-7619](#) [24-4060-2437](#) [T0051387299](#) [5760140](#) [1152](#) [EC2002M-1](#) [760-2028](#) [389289](#) [570027](#) [811035](#) [811036](#) [811018](#) [ALPHA VACULOY SNCX PLUS 07 1](#) [KG](#) [15704](#) [15808](#) [0008752](#) [0401-08-000460](#) [04-6040-0050](#) [H560103-BULK](#) [H560106-BULK](#) [H562159-BULK](#) [5601365](#) [BON-102F](#) [BON-102K](#) [BON-102S](#) [BR-102F](#) [560006BA](#) [560048](#) [560069W-LF](#) [5601034](#) [5601053](#) [5601056](#) [5601058](#) [5601129](#) [5601157](#) [5601161](#) [5601166](#) [5601167](#) [5601170](#) [8001092](#)