

Datasheet revision 1.1

www.chipquik.com

Chip Quik Removal Alloy (4.5ft. In 9-6.5in. Lengths) lead-free

Product Highlights Easily remove SMD parts with Chip Quik® removal alloy Reduce heat and reduce damage to circuit boards and SMD parts during removal Use with SMD291 flux RoHS II and REACH compliant

Specifications

Alloy: Melting Point: Chip Quik® lead-free 79-91°C (174-195°F)

Chip Quik® Instructions		
	1	Apply Chip Quik flux to all leads of SMD with syringe or flux applicator.
	2	Melt Chip Quik low temperature alloy uniformly on all pins of SMD. Maintain alloy in molten state long enough for complete reflow.
	3	Lift chip from board with dental pick or vacuum pen.
	4	Thoroughly clean site with swab dipped in flux while applying heat. Clean thoroughly with alcohol pad.

SMD Removal

(With solder iron or warm air bath)

- Apply flux to all leads.
- Melt CHIP QUIK® uniformly on all pins.
- Maintain alloy in molten state long enough to release chip.
- Lift chip from board with dental pick or vacuum pen.

CLEAN UP

- While molten, use cotton swab and flux to move excess to an unused section of board.
- While applying heat, polish each pad with a swab and flux until thoroughly clean.
- At room temperature, clean residue with alcohol pad.
- You are now ready to install the new chip.

2.5 ft of Chip Quik® material, removes 1250 to 1500 SMD pins.

Conforms to the following Industry Standards:J-STD-006C, Amendments 1 & 2 (Solder Alloys and Fluxed/Non-Fluxed Solders):YesRoHS 2 Directive 2011/65/EU:Yes

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Desoldering Braid / Solder Removal category:

Click to view products by Chip Quik manufacturer:

Other Similar products are found below :

 532505-2
 DS03-910-5
 T0054487199
 T0054486999
 DP-CC
 STDC-102
 T0054465499N
 T0058741815N
 T0054465299N
 T0051320399N

 T0051351199
 T0051352700
 4036S
 6961
 9057
 9970
 9976
 DS104
 DS115T
 DS117T
 DS204
 DS206
 DS60
 ETBB
 HE80
 MP135
 MP136

 MP137
 MP138
 MT6
 UTC234
 T0054460273
 T0053411299N
 17538
 S1069
 1811-5F
 1830-10F
 50-3-100
 1813-5F
 1833-10F
 1810-25F

 1823-25F
 1824-25F
 CL7984
 33397-AA
 33398-AA
 0320705
 0320800
 0320903