

Indium Solder Ribbon (In52/Sn48) 0.002" x 1.69" x 5.71"

Product Highlights

Low Temperature Melts at 118°C (244°F)

Lead-Free

RoHS 3 compliant

REACH compliant

This eutectic alloy is excellent for low temperature soldering and sealing. It can be stamped and cut into preforms.



Specifications

Alloy:	In52/Sn48
Tensile Strength:	11.9 N/mm ² (at 20°C)
Dimensions:	1.69" x 5.71" (43mm x 145mm)
Thickness:	0.002" (0.05mm)
Melting Point:	118°C (244°F)
Purity:	Conforms to all IPC J-STD-006C soldering alloy impurity levels
Packaging:	Spool
Shelf Life:	Indefinite. Solid solder ribbon has no limited shelf life as long as it is stored in a non-corrosive, dry environment. The surface may lose its shine and appear dull grey. This is a surface phenomenon and is not detrimental to product functionality.

Storage and Handling

Store in a non-corrosive, dry environment.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Solder](#) category:

Click to view products by [Chip Quik](#) manufacturer:

Other Similar products are found below :

[701-2758](#) [707-1811](#) [91362-6](#) [13-217-3-01](#) [P10695](#) [SN63WRAP3-.022-1-LB](#) [599Z](#) [707-0441-26](#) [707-1810](#) [601Y](#) [24-9574-7619](#) [24-4060-2437](#) [T0051387299](#) [5760140](#) [1152](#) [EC2002M-1](#) [760-2028](#) [389289](#) [570027](#) [811035](#) [811036](#) [811018](#) [ALPHA VACULOY SNCX PLUS 07 1](#) [KG](#) [15704](#) [15808](#) [0008752](#) [0401-08-000460](#) [04-6040-0050](#) [H560103-BULK](#) [H560106-BULK](#) [H562159-BULK](#) [5601365](#) [BON-102F](#) [BON-102K](#) [BON-102S](#) [BR-102F](#) [560006BA](#) [560048](#) [560069W-LF](#) [5601034](#) [5601053](#) [5601056](#) [5601058](#) [5601129](#) [5601157](#) [5601161](#) [5601166](#) [5601167](#) [5601170](#) [8001092](#)