

Sn95.5/Ag4.0/Cu0.5 .031" Solder Wire 1oz Spool (Solid Core) SAC405 (Tin/Silver/Copper)

Product Highlights

Lead Free Solder Wire SAC405 Sn95.5/Ag4.0/Cu0.5 .031 1oz solid core.

Lead-Free

RoHS 3 compliant

REACH compliant

Specifications

Alloy:	Sn95.5/Ag4.0/Cu0.5
Wire diameter:	0.031" (0.8mm)
Flux Core:	No flux core, solid solder wire
Melting Point:	217°C (423°F)
Packaging:	1 oz spool
Shelf Life:	>60 months



Recommended Accessory Flux

Recommended to use with Chip Quik® SMD291NL flux.

Storage and Handling

Store in a non-corrosive, dry environment.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Solder](#) category:

Click to view products by [Chip Quik](#) manufacturer:

Other Similar products are found below :

[701-2758](#) [707-1811](#) [91362-6](#) [13-217-3-01](#) [P10695](#) [SN63WRAP3-.022-1-LB](#) [599Z](#) [707-0441-26](#) [707-1810](#) [601Y](#) [24-9574-7619](#) [24-4060-2437](#) [T0051387299](#) [5760140](#) [1152](#) [EC2002M-1](#) [760-2028](#) [389289](#) [570027](#) [811035](#) [811036](#) [811018](#) [ALPHA VACULOY SNCX PLUS 07 1](#) [KG](#) [15704](#) [15808](#) [0008752](#) [0401-08-000460](#) [04-6040-0050](#) [H560103-BULK](#) [H560106-BULK](#) [H562159-BULK](#) [5601365](#) [BON-102F](#) [BON-102K](#) [BON-102S](#) [BR-102F](#) [560006BA](#) [560048](#) [560069W-LF](#) [5601034](#) [5601053](#) [5601056](#) [5601058](#) [5601129](#) [5601157](#) [5601161](#) [5601166](#) [5601167](#) [5601170](#) [8001092](#)