

Solder Wire SAC305 No-Clean with 2.2% Flux Core 1/2 lb Spool

Product Highlights

No-Clean Water-Washable Synthetic Flux Core

The clear, non-corrosive, non-conductive residue is meant to be left on the board. Residues that do remain are water soluble if you want to remove them. Clean with hot water at 60°C (140°F) minimum.

2.2% flux core

Halogen content: None

RoHS II and REACH compliant

Specifications

| | |
|----------------------|-----------------------------------|
| Alloy: | Sn96.5/Ag3.0/Cu0.5 |
| Wire Diameter: | 0.020" (0.5mm) |
| Flux Type: | No-Clean Water-Washable Synthetic |
| Flux Classification: | ROL0 |
| Melting Point: | 217-220°C (423-428°F) |
| Packaging: | 1/2 lb (8oz) spool |

Test Results

| Test J-STD-004 or other requirements as stated | Test Requirement | Result |
|--|--|--|
| Copper Mirror | IPC-TM-650: 2.3.32 | L: No breakthrough |
| Corrosion | IPC-TM-650: 2.6.15 | L: No corrosion |
| Quantitative Halides | IPC-TM-650: 2.3.28.1 | L: <0.5% |
| Electrochemical Migration | IPC-TM-650: 2.6.14.1 | L: <1 decade drop (No-clean) |
| Surface Insulation Resistance 85°C, 85% RH @ 168 Hours | IPC-TM-650: 2.6.3.7 | L: ≥100MΩ (No-clean) |
| Visual | IPC-TM-650: 3.4.2.5 | Clear and free from precipitation |
| Conflict Minerals Compliance | Electronic Industry Citizenship Coalition (EICC) | Compliant |
| REACH Compliance | Articles 33 and 67 of Regulation (EC) No 1907/2006 | Contains no substance >0.1% w/w that is listed as a SVHC or restricted for use in solder materials |

Conforms to the following Industry Standards:

| | |
|---|-----|
| J-STD-004B, Amendment 1 (Solder Fluxes): | Yes |
| J-STD-006C, Amendments 1 & 2 (Solder Alloys and Fluxed/Non-Fluxed Solders): | Yes |
| RoHS 2 Directive 2011/65/EU: | Yes |

ChipQuik® Solder Wire Orderable Part Numbers:

| Flux Core | Alloy | Melting Point | Diameter | Size | Orderable Part Number | |
|---|-----------|-----------------------|----------------|---------------|-----------------------|-----------------|
| No-Clean Water-Washable Synthetic Flux Core 2.2% (Except .006" and .008" diameter wire which are 1.2%) | Sn63/Pb37 | 183°C (361°F) | .015" (0.38mm) | 100g (3.5oz) | SMDSW.015 100g | |
| | | | | 0.4 oz | SMDSW.020 .4OZ | |
| | | | .020" (0.5mm) | 1 oz | SMDSW.020 1OZ | |
| | | | | 2 oz | SMDSW.020 2OZ | |
| | | | | 4 oz | SMDSW.020 4OZ | |
| | | | | 1/2 lb | SMDSW.020 8OZ | |
| | | | | 1 lb | SMDSW.020 1LB | |
| | | | .031" (0.8mm) | 0.7 oz | SMDSW.031 .7OZ | |
| | | | | 1 oz | SMDSW.031 1OZ | |
| | 2 oz | SMDSW.031 2OZ | | | | |
| | 4 oz | SMDSW.031 4OZ | | | | |
| | 1/2 lb | SMDSW.031 8OZ | | | | |
| | 1 lb | SMDSW.031 1LB | | | | |
| | Sn60/Pb40 | 183-188°C (361-370°F) | .015" (0.38mm) | 100g (3.5oz) | SMD2SW.015 100g | |
| | | | | 0.4 oz | SMD2SW.020 .4OZ | |
| | | | .020" (0.5mm) | 1 oz | SMD2SW.020 1OZ | |
| | | | | 2 oz | SMD2SW.020 2OZ | |
| | | | | 4 oz | SMD2SW.020 4OZ | |
| | | | | 1/2 lb | SMD2SW.020 8OZ | |
| | | | | 1 lb | SMD2SW.020 1LB | |
| | | | .031" (0.8mm) | 0.7 oz | SMD2SW.031 .7OZ | |
| | | | | 1 oz | SMD2SW.031 1OZ | |
| | | | | 2 oz | SMD2SW.031 2OZ | |
| | | | | 4 oz | SMD2SW.031 4OZ | |
| | | | | 1/2 lb | SMD2SW.031 8OZ | |
| | | | | 1 lb | SMD2SW.031 1LB | |
| | | | Sn62/Pb36/Ag2 | 179°C (354°F) | .015" (0.38mm) | 100g (3.5oz) |
| 0.4 oz | | | | | | SMD3SW.020 .4OZ |
| .020" (0.5mm) | 1 oz | SMD3SW.020 1OZ | | | | |
| | 2 oz | SMD3SW.020 2OZ | | | | |
| | 4 oz | SMD3SW.020 4OZ | | | | |
| | 1/2 lb | SMD3SW.020 8OZ | | | | |
| | 1 lb | SMD3SW.020 1LB | | | | |
| .031" (0.8mm) | 0.7 oz | SMD3SW.031 .7OZ | | | | |
| | 1 oz | SMD3SW.031 1OZ | | | | |
| | 2 oz | SMD3SW.031 2OZ | | | | |
| | 4 oz | SMD3SW.031 4OZ | | | | |
| | 1/2 lb | SMD3SW.031 8OZ | | | | |
| | 1 lb | SMD3SW.031 1LB | | | | |

Continued on next page

ChipQuik® Solder Wire Orderable Part Numbers:

Continued from previous page

| Flux Core | Alloy | Melting Point | Diameter | Size | Orderable Part Number |
|---|--------------------|-----------------------|-----------------|-------------------|-----------------------|
| No-Clean Water-Washable Synthetic Flux Core 2.2% (Except .006" and .008" diameter wire which are 1.2%) | Sn96.5/Ag3.0/Cu0.5 | 217-220°C (423-428°F) | .006" (0.15mm) | 50g (1.8oz) | SMDSWLF.006 50g |
| | | | .008" (0.20mm) | 50g (1.8oz) | SMDSWLF.008 50g |
| | | | .015" (0.38mm) | 0.3 oz | SMDSWLF.015 .3OZ |
| | | | | 1 oz | SMDSWLF.015 1OZ |
| | | | | 2 oz | SMDSWLF.015 2OZ |
| | | | | 4 oz | SMDSWLF.015 4OZ |
| | | | | 1/2 lb | SMDSWLF.015 8OZ |
| | | | | 1 lb | SMDSWLF.015 1LB |
| | | | .020" (0.5mm) | 0.4 oz | SMDSWLF.020 .4OZ |
| | | | | 1 oz | SMDSWLF.020 1OZ |
| | | | | 2 oz | SMDSWLF.020 2OZ |
| | | | | 4 oz | SMDSWLF.020 4OZ |
| | | | | 1/2 lb | SMDSWLF.020 8OZ |
| | | | | 1 lb | SMDSWLF.020 1LB |
| | | | .031" (0.8mm) | 0.7 oz | SMDSWLF.031 .7OZ |
| | 1 oz | SMDSWLF.031 1OZ | | | |
| | 2 oz | SMDSWLF.031 2OZ | | | |
| | 4 oz | SMDSWLF.031 4OZ | | | |
| | 1/2 lb | SMDSWLF.031 8OZ | | | |
| | 1 lb | SMDSWLF.031 1LB | | | |
| | Sn99.3/Cu0.7 | 227°C (441°F) | .012" (0.3mm) | 100g (3.5oz) | SMD2SWLF.012 100g |
| | | | .015" (0.38mm) | 0.3 oz | SMD2SWLF.015 .3OZ |
| | | | | 1 oz | SMD2SWLF.015 1OZ |
| | | | | 2 oz | SMD2SWLF.015 2OZ |
| | | | | 4 oz | SMD2SWLF.015 4OZ |
| | | | | 1/2 lb | SMD2SWLF.015 8OZ |
| | | | | 1 lb | SMD2SWLF.015 1LB |
| .020" (0.5mm) | | | 0.4 oz | SMD2SWLF.020 .4OZ | |
| | | | 1 oz | SMD2SWLF.020 1OZ | |
| | | | 2 oz | SMD2SWLF.020 2OZ | |
| | | | 4 oz | SMD2SWLF.020 4OZ | |
| | | | 1/2 lb | SMD2SWLF.020 8OZ | |
| | | | 1 lb | SMD2SWLF.020 1LB | |
| .031" (0.8mm) | | | 0.7 oz | SMD2SWLF.031 .7OZ | |
| | | | 1 oz | SMD2SWLF.031 1OZ | |
| | 2 oz | SMD2SWLF.031 2OZ | | | |
| | 4 oz | SMD2SWLF.031 4OZ | | | |
| | 1/2 lb | SMD2SWLF.031 8OZ | | | |
| | 1 lb | SMD2SWLF.031 1LB | | | |
| Solid Wire (No Flux) | Sn42/Bi57/Ag1 | 138°C (281°F) | .030" (0.762mm) | 32 feet | SMDSWLTLP32 |
| | In100 | 157°C (315°F) | .031" (0.8mm) | 10 feet | SMDIN100 |
| | In52/Sn48 | 118°C (244°F) | .031" (0.8mm) | 10 feet | SMDIN52SN48 |
| | In97/Ag3 | 143°C (289°F) | .031" (0.8mm) | 10 feet | SMDIN97AG3 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Solder](#) category:

Click to view products by [Chip Quik](#) manufacturer:

Other Similar products are found below :

[600YSY](#) [701-2758](#) [707-1746](#) [707-1748](#) [707-1811](#) [707-1813](#) [707-1831](#) [707-1840](#) [707-1850](#) [707-1852](#) [13-217-3-01](#) [P10695](#) [SN63WRAP3-.022-1-LB](#) [24-6040-0007](#) [DAC-061](#) [701-2089](#) [707-0285](#) [707-0366](#) [707-0441-26](#) [707-1774](#) [707-1810](#) [24-6337-9727](#) [601Y](#) [24-9574-7619](#) [24-4060-2437](#) [14-6040-0125](#) [04-0595-0000](#) [5901003](#) [631960](#) [SW02-10](#) [S2626-O-T](#) [8055](#) [5760140](#) [TRWR-204](#) [1152](#) [EC2002M-1](#) [WPT17](#) [WS6016](#) [760-2028](#) [8001115](#) [8001073](#) [8001495](#) [41-096-0203N](#) [ART.AGT-030](#) [389289](#) [54068](#) [ECO 1 \(SNCU1\) FLUX B2.1 0,8 MM 250G](#) [ECO3 \(SNCU3\) FLUX B2.1 0,8 MM 250 G.](#) [ECO3 \(SNCU3\) FLUX B2.1 0,8 MM 1000 G.](#) [ECO4 \(SNAG3CU0.5\) FLUX B2.1 0,8 MM 1000G](#)