


**SPECIFICATIONS**

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: -25℃~ +85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100mΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Wafer Nylon46 UL94-VO  
Pin Brass Tin-plated

Circuit	PA-XXrt NO.	Dimensions mm	
		A	B
2	XD-1.25-2AW-XX	1.25	4.25
3	XD-1.25-3AW-XX	2.50	5.50
4	XD-1.25-4AW-XX	3.75	6.75
5	XD-1.25-5AW-XX	5.00	8.00
6	XD-1.25-6AW-XX	6.25	9.25
7	XD-1.25-7AW-XX	7.50	10.50
8	XD-1.25-8AW-XX	8.75	11.75
9	XD-1.25-9AW-XX	10.00	13.00
10	XD-1.25-10AW-XX	11.25	14.25
11	XD-1.25-11AW-XX	12.50	15.50
12	XD-1.25-12AW-XX	13.75	16.75
13	XD-1.25-13AW-XX	15.00	18.00
14	XD-1.25-14AW-XX	16.25	19.25
15	XD-1.25-15AW-XX	17.50	20.50
16	XD-1.25-16AW-XX	18.75	21.75

**Ordering Information**



			GENERAL TOLERANCE	制图 DRAWING	02	<b>深圳讯答科技有限公司</b> ShenzhenXuntaTechnology Co.,Ltd			
			DIM    TOL	审核 CHECK					产品名称 TITLE
			X.X    ±0.30	批准 APPROVAL		产品料号 PART NO.	XD-1.25-NAW-XX	单位 UNITS	mm
			X.XX    ±0.20	比例 SCALE		材料 MATERIAL		页次 SHEET	1/1
			X.XXX    ±0.10	投影 Projection					
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle ±3.0°						

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [chxunda](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-](#)  
[002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#) [820-22-008-30-001101](#)  
[821-22-002-10-001101](#) [821-22-003-10-002101](#)