


- SPECIFICATIONS
1. Current Rating: 2A AC, DC
 2. Voltage Rating: 250V AC, DC
 3. Temperature Range: -25°C~ +85°C
 4. Contact Resistance: 20mΩ Max
 5. Insulation Resistance: 1000mΩ Min
 6. Withstanding Voltage: 1000V AC/minute
 7. Material: Wafer Nylon66 UL94-VO
Pin Brass Tin-plated

| Circuit | Part NO. | Dimensions mm | |
|---------|-----------------|---------------|-------|
| | | A | B |
| 2 | XD-HY-2AW-X-XX | 2.00 | 6.00 |
| 3 | XD-HY-3AW-X-XX | 4.00 | 8.00 |
| 4 | XD-HY-4AW-X-XX | 6.00 | 10.00 |
| 5 | XD-HY-5AW-X-XX | 8.00 | 12.00 |
| 6 | XD-HY-6AW-X-XX | 10.00 | 14.00 |
| 7 | XD-HY-7AW-X-XX | 12.00 | 16.00 |
| 8 | XD-HY-8AW-X-XX | 14.00 | 18.00 |
| 9 | XD-HY-9AW-X-XX | 16.00 | 20.00 |
| 10 | XD-HY-10AW-X-XX | 18.00 | 22.00 |
| 11 | XD-HY-11AW-X-XX | 20.00 | 24.00 |
| 12 | XD-HY-12AW-X-XX | 22.00 | 26.00 |
| 13 | XD-HY-13AW-X-XX | 24.00 | 28.00 |
| 14 | XD-HY-14AW-X-XX | 26.00 | 30.00 |
| 15 | XD-HY-15AW-X-XX | 28.00 | 32.00 |
| 16 | XD-HY-16AW-X-XX | 30.00 | 34.00 |

Ordering Information



| GENERAL TOLERANCE | | | 制图 DRAWING | 02 | 深圳讯答科技有限公司 ShenzhenXunDaTechnology Co.,Ltd | | | |
|-------------------|------------------------|-------------------|----------------|------------------|---|-------------------|-------------|-----|
| | | | 审核 CHECK | | 产品名称 TITLE | HY (2.00) 单排带扣 弯针 | 版本 REV. | A |
| | | | 批准 APPROVAL | | 产品料号 PART NO. | XD-HY-NAW-X-XX | 单位 UNITS | mm |
| 1 | 初版发行 | | 比例 SCALE | | 材料 MATERIAL | | 页次 SHEET | 1/1 |
| 序号 No. | 变更内容 MODIFY CONTENT | 日期 MODIFY DATE | Angle ±3.0° | 投影 Projection | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [chxunda](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)