


- SPECIFICATIONS**
1. Current Rating: 3A AC, DC
  2. Voltage Rating: 250V AC, DC
  3. Temperature Range: -25°C~ +85°C
  4. Contact Resistance: 20mΩ Max
  5. Insulation Resistance: 1000mΩ Min
  6. Withstanding Voltage: 1000V AC/minute
  7. Material: Wafer Nylon66 UL94-VO (2)  
Pin Brass Tin-plated

Circuit	Part NO.	Dimensions mm	
		A	B
2	XD-XH-2A-L	2.50	7.50
3	XD-XH-3A-L	5.00	10.00
4	XD-XH-4A-L	7.50	12.50
5	XD-XH-5A-L	10.00	15.00
6	XD-XH-6A-L	12.50	17.50
7	XD-XH-7A-L	15.00	20.00
8	XD-XH-8A-L	17.50	22.50
9	XD-XH-9A-L	20.00	25.00
10	XD-XH-10A-L	22.50	27.50
11	XD-XH-11A-L	25.00	30.00
12	XD-XH-12A-L	27.50	32.50
13	XD-XH-13A-L	30.00	35.00
14	XD-XH-14A-L	32.50	37.50
15	XD-XH-15A-L	35.00	40.00
16	XD-XH-16A-L	37.50	42.50



		GENERAL TOLERANCE	制图 DRAWING	10
		DIM TOL	审核 CHECK	
		X.X ±0.30	批准 APPROVAL	
1	初版发行	X.XX ±0.20	比例 SCALE	
		X.XXX ±0.10	投影 Projection	
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE		

**XD** 深圳讯答科技有限公司  
ShenzhenXunDaTechnology Co.,Ltd

产品名称 TITLE	XH (2.50) 单排 直针 蓝色	版本 REV.	A
产品料号 PART NO.	XD-XH-NA-L	单位 UNITS	mm
材料 MATERIAL		页次 SHEET	1/1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [chxunda](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)