



**SPECIFICATIONS**

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 100V AC, DC
- 3、Temperatuer Range: -25℃~ +85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 500mΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Housing Nylon66 UL94-VO

| Circuit | Part NO.  | Dimensions mm |       |
|---------|-----------|---------------|-------|
|         |           | A             | B     |
| 2       | XD-ZH-2Y  | 1.50          | 4.50  |
| 3       | XD-ZH-3Y  | 3.00          | 6.00  |
| 4       | XD-ZH-4Y  | 4.50          | 7.50  |
| 5       | XD-ZH-5Y  | 6.00          | 9.00  |
| 6       | XD-ZH-6Y  | 7.50          | 10.50 |
| 7       | XD-ZH-7Y  | 9.00          | 12.00 |
| 8       | XD-ZH-8Y  | 10.50         | 13.50 |
| 9       | XD-ZH-9Y  | 12.00         | 15.00 |
| 10      | XD-ZH-10Y | 13.50         | 16.50 |
| 11      | XD-ZH-11Y | 15.00         | 18.00 |
| 12      | XD-ZH-12Y | 16.50         | 19.50 |
| 13      | XD-ZH-13Y | 18.00         | 21.00 |
| 14      | XD-ZH-14Y | 19.50         | 22.50 |
| 15      | XD-ZH-15Y | 21.00         | 24.00 |
| 16      | XD-ZH-16Y | 22.50         | 25.50 |

**Ordering Information**

XD - ZH - N \*\*\* - \*

Pin Type Colour  
 1.50 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 6.00 6.50 7.00 7.50 8.00 8.50 9.00 9.50 10.00 10.50 11.00 11.50 12.00 12.50 13.00 13.50 14.00 14.50 15.00 15.50 16.00 16.50 17.00 17.50 18.00 18.50 19.00 19.50 20.00 20.50 21.00 21.50 22.00 22.50 23.00 23.50 24.00 24.50 25.00 25.50

|                   |                        |                   |                  |    |  |          |             |               |
|-------------------|------------------------|-------------------|------------------|----|--|----------|-------------|---------------|
| GENERAL TOLERANCE |                        |                   | 制图<br>DRAWING    | 02 | <b>深圳讯答科技有限公司</b><br>ShenzhenXunDaTechnology Co.,Ltd |          |             |               |
| DIM TOL           |                        |                   | 审核<br>CHECK      |    |  |          |             | 产品名称<br>TITLE |
| X.X ±0.30         |                        |                   | 批准<br>APPROVAL   |    | 产品料号<br>PART NO.                                     | XD-ZH-NY | 单位<br>UNITS | mm            |
| X.XX ±0.20        |                        |                   | 投影<br>Projection |    | 材料<br>MATERIAL                                       |          | 页次<br>SHEET | 1/1           |
| X.XXX ±0.10       |                        |                   |                  |    |  |          |             |               |
| 1                 | 初版发行                   |                   |                  |    |  |          |             |               |
| 序号<br>No.         | 变更内容<br>MODIFY CONTENT | 日期<br>MODIFY DATE | Angle ±3.0°      |    |  |          |             |               |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [chxunda](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)