



CHB50W SERIES

33 TO 50 WATT WIDE INPUT DC-DC CONVERTERS

SINGLE OUTPUT



FEATURES

- * 33-50W Isolated Output
- * Efficiency to 87%
- * 300KHz Switching Frequency
- * 4:1 Input Range
- * Regulated Outputs
- * Continuous Short Circuit Protection
- * Five-Sided Shield Metal Case
- * Half-Brick Size Meet Industrial Standard
- * UL60950-1 Approval (Except 28 Vout)
- * Safety Meets IEC/EN/UL62368-1



MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT		INPUT CURRENT		% EFF.	CAPACITOR LOAD MAX.
			MIN.	MAX.	NO LOAD	FULL LOAD		
CHB50W-24S33	9-36 VDC	3.3 VDC	0 mA	10 A	50 mA	1740 mA	79	10000uF
CHB50W-24S05	9-36 VDC	5 VDC	0 mA	10 A	50 mA	2570 mA	81	10000uF
CHB50W-24S12	9-36 VDC	12 VDC	0 mA	4.16 A	50 mA	2510 mA	83	4160uF
CHB50W-24S15	9-36 VDC	15 VDC	0 mA	3.33 A	50 mA	2448 mA	85	3330uF
CHB50W-24S24	9-36 VDC	24 VDC	0 mA	2.08 A	50 mA	2476 mA	84	2080uF
CHB50W-24S28	9-36 VDC	28 VDC	0 mA	1.78 A	50 mA	2510 mA	83	1780uF
CHB50W-24S48	9-36 VDC	48 VDC	0 mA	1.04 A	50 mA	2506 mA	83	1040uF
CHB50W-48S33	18-75 VDC	3.3 VDC	0 mA	10 A	50 mA	848 mA	81	10000uF
CHB50W-48S05	18-75 VDC	5 VDC	0 mA	10 A	50 mA	1255 mA	83	10000uF
CHB50W-48S12	18-75 VDC	12 VDC	0 mA	4.16 A	50 mA	1223 mA	85	4160uF
CHB50W-48S15	18-75 VDC	15 VDC	0 mA	3.33 A	50 mA	1196 mA	87	3330uF
CHB50W-48S24	18-75 VDC	24 VDC	0 mA	2.08 A	50 mA	1209 mA	86	2080uF
CHB50W-48S28	18-75 VDC	28 VDC	0 mA	1.78 A	50 mA	1223 mA	85	1780uF
CHB50W-48S48	18-75 VDC	48 VDC	0 mA	1.04 A	50 mA	1238 mA	84	1040uF

NOTE: 1. Nominal Input Voltage 24, 48VDC

SPECIFICATIONS

All Specifications Typical At Nominal Line, Full Load, and 25°C Unless Otherwise Noted

INPUT SPECIFICATIONS:

Input Voltage Range..... 24V 9 – 36V

48V 18 – 75V

Input Surge Voltage (100ms max.) 24V 50Vdc max.

48V 100Vdc max.

Under Voltage Lockout:

24Vin power up 8.8V, power down 8V

48Vin power up 17V, power down 16V

Positive Logic Remote On/Off (note3&4)

Input Filter Pi Type

OUTPUT SPECIFICATIONS:

Voltage Accuracy (note7) ±1.0% max.

Transient Response: 25% Step Load Change <500µs

External Trim Adj. Range ±10%

Ripple & Noise, 20MHz BW (note5)

3.3V&5V 40mV RMS max., 100mV pk-pk max.

12V&15V 60mV RMS max., 150mV pk-pk max.

24V 100mV RMS max., 240mV pk-pk max.

28V 100mV RMS max., 280mV pk-pk max.

48V 200mV RMS max., 480mV pk-pk max.

Temperature Coefficient ±0.03%/°C max.

Short Circuit Protection Continuous

Line Regulation (note1&7) ±0.2% max.

Load Regulation (note2&7) ±0.2% max.

Over Voltage Protection Trip Range, % Vo nom. 115-140%

Current Limit 110% -160% Nominal Output

Start up Time 5ms typ.

GENERAL SPECIFICATIONS:

Efficiency See Table

Isolation Voltage ... Input/Output, Input/Case, Output/Case ... 1500VDC min.

Isolation Resistance 10⁷ ohm min.

Isolation Capacitance 1000pF typ.

Switching Frequency 300KHz typ.

Operating Case Temperature -40°C to 100°C

Storage Temperature -55°C to +105°C

Thermal Shutdown Case Temp. 100°C typ.

Humidity 95% RH max. Non Condensing

MTBF MIL-HDBK-217F, GB, 25°C, Full Load 1000Khrs typ.

Dimensions 2.28x2.40x0.50 inches (57.9x61.0x12.7 mm)

Case Material Aluminum

Weight 94g

NOTE:

1. Measured from high line to low line.

2. Measured from full load to zero load.

3. Logic compatibility open collector ref to -input

Module on >3.5VDC to 75VDC or open circuit
Module off 0 to <0.8VDC


4. Suffix "N" to the model number with negative logic remote on/off.

Module on 0 to <0.8VDC
Module off >3.5VDC to 75VDC or open circuit


5. Output ripple and noise measured with 10uF tantalum and 1uF ceramic capacitor across output. (48V: 1uF ceramic cap. only)

6. Suffix "-C" to the model number with clear mounting insert (3.2mm DIA.)


7. Require a 47uF aluminum capacitor connected between +Vout and -Vout for 48Vout models.



REMOTE ON/OFF CONTROL



EXTERNAL OUTPUT TRIM



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Isolated DC/DC Converters](#) category:

Click to view products by [Cincon manufacturer:](#)

Other Similar products are found below :

[ESM6D044440C05AAQ](#) [FMD15.24G](#) [PSL486-7LR](#) [Q48T30020-NBB0](#) [18362](#) [JAHW100Y1](#) [SPB05C-12](#) [SQ24S15033-PS0S](#) [19-130041](#)
[CE-1003](#) [RDS180245](#) [MAU228](#) [J80-0041NL](#) [DFC15U48D15](#) [XGS-0512](#) [XGS-1205](#) [XGS-1212](#) [XGS-2412](#) [XGS-2415](#) [XKS-1215](#) [06322](#)
[NCT1000N040R050B](#) [SPB05B-15](#) [SPB05C-15](#) [L-DA20](#) [DCG40-5G](#) [QME48T40033-PGB0](#) [XKS-2415](#) [XKS-2412](#) [XKS-1212](#) [XKS-1205](#)
[XKS-0515](#) [XGS-2405](#) [XGS-1215](#) [XGS-0515](#) [73-551-5038I](#) [AK1601-9RT](#) [VI-R5022-EXWW](#) [PSC128-7iR](#) [RPS8-350ATX-XE](#)
[DAS1004812](#) [PQA30-D24-S24-DH](#) [VI-M5F-CQ](#) [VI-LN2-EW](#) [VI-PJW01-CZY](#) [CK2540-9ERT](#) [AK-1615-7R](#) [700DNC40-CON-KIT-8G](#)
[350DNC40-CON-KIT-9G](#) [088-101348-G](#)