

## DLAS-24D3



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I<sub>max</sub>
- ↳ 5kA I<sub>imp</sub>
- ↳ 5kA I<sub>n</sub>
- ↳ Modular with Fault Indicator
- ↳ 2W+SHIELD+G



| Electrical Characteristics                                 |                  |  |
|--|------------------|--|
| Insertion loss   |                  | < 1 dB   |
| Max. load current  | IL               | 300 mA   |
| Protection mode(s)   |                  | Common/Differential mode                           |
| Impulse current (2 x 10/350µs Test - D1 Category)          | I <sub>imp</sub> | 5 kA   |
| Nominal discharge current (8/20µs Test x 10 - C2 Category) | I <sub>n</sub>   | 5 kA   |
| DATA SPD TYPE  |                  | UL497B LISTED                                      |
| VOLTS  | (V)              | 24   |
| WIRES  |                  | 2W+SHIELD+GROUND                                   |
| LINE CURRENT MAX   | (A)              | 0.3  |
| AMBIENT MIN  | (C)              | -50  |
| AMBIENT MAX  | (C)              | +85  |
| RESIDUAL VOLTAGE   | (V)              | 40   |
| MCOV   | (V)              | 28/72/72   |
| IN (10 impulses 8/20µs)                                    | (kA)             | 5.0000   |
| IMAX (8/20µs)  | (kA)             | 20   |
| DATA SPEED   | (bps)            | 10/100   |
| Mechanical Characteristics                                 |                  |  |
| Weight   |                  | 0.064 kg   |
| TECHNOLOGY   |                  | SAD-GDT  |
| NETWORK CONFIGURATION                                      |                  | 1 Channel (2W+SHIELD+G)                            |
| CONNECTION METHOD  |                  | Screw Terminal (16-22AWG)                          |
| MOUNTING   |                  | DIN RAIL   |
| MATERIAL   |                  | Thermoplastic UL94-V0                              |
| NEMA RATING (IP RATING)                                    |                  | NEMA 2 (IP20)                                      |
| DIMENSIONS   |                  | See diagram (mm)                                   |
| WEIGHT   |                  | 0.30 lbs   |
| SPARE PART   |                  | DLASM-24D3   |
| Standards  |                  |  |
| Certification  |                  | UL / EAC   |
| UL STANDARD  |                  | UL497B   |
| UL CATEGORY  |                  | QVGG   |
| UL FILE NUMBER   |                  | E184939  |
| STANDARDS  |                  | IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993 |
| ENVIRONMENTAL STANDARDS                                    |                  | ROHS   |
| Part number  |                  |  |
| <b>641303</b>  |                  |  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Surge Suppressors](#) category:*

*Click to view products by [Citel](#) manufacturer:*

Other Similar products are found below :

[GUS1](#) [GUS12](#) [BSPM1A600D600LVR](#) [2800521](#) [29-2053](#) [GUS11](#) [GUS2](#) [GUS3](#) [GUS4](#) [30460](#) [SRA64C060X](#) [PC642C015](#) [1810-15-A3](#)  
[2713175](#) [4B06B-EC1-150LF](#) [SRA6LC](#) [BPMA75D100LV](#) [CX06M](#) [CCTV1](#) [GUS13](#) [GUS14](#) [GUS5](#) [GUS6](#) [VAL-MS 320/3+0-FM](#) [VAL-US-](#)  
[120/40/1+1-FM](#) [VAL-US-120/65/1+1-FM](#) [VAL-US-480D/30/3+0-FM](#) [VAL-US-120/40/1+0-FM](#) [STCHSP121BT1RU](#) [LP-BFDN-CW](#) [LP-](#)  
[STRL-NFF](#) [LP-STRL-DFE](#) [GUS22](#) [0804111](#) [5053609](#) [5053201](#) [SPD2-150-1P0](#) [SPD2-550-1P0](#) [6720005416](#) [6720005417](#) [1-2191595-2](#)  
[STC-CAT6-P0E-I](#) [SPD2-350-1P0](#) [FLT-CP-350-ST](#) [TTC-6P-3-HF-F-M-12DC-UT-I](#) [SMTPA200](#) [2800989](#) [2906776](#) [2906810](#) [2906847](#)