

# LS12T2-T



## 特徴 Features

1. **水平タイプ、小型・薄型**  
Horizontal type, compact and thin
2. **防塵・防水構造**  
Dust- and waterproof mechanism

## 用途 Application


- ・ **スマートフォン、携帯端末**  
Smartphone, mobile device
- ・ **各種AV機器**  
Various AV devices

(Ta 25°C)

### ● 電氣的・機械的特性 Electrical and Mechanical Characteristics


Item	スイッチ作動力 Switch operating force
	1.57N
最大定格 Maximum rating	DC12V 20mA
接続抵抗 Contact resistance	100mΩ以下 100mΩ or less
絶縁抵抗 Insulation resistance	100MΩ以上 100MΩ or more
耐電圧 Withstanding voltage	AC250V 1分間 AC250V for one minute
バウンス Bounce	20ms以下 20ms or less
ストローク Stroke	0.20mm
作動力 Operating force	1.57±0.49N
動作寿命 Operating life (times)	10万回以上 100,000 or more

### ● 製品コード Product code



TACTILE SWITCH共通番号  
Common for TACTILE SWITCHes

### ● 外形寸法図 Outline drawing



包装数量: 3,000個 × 1リール (φ330mm) Loaded quantity: 3,000 pcs. × 1 reel (φ330mm)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Tactile Switches](#) category:*

*Click to view products by [Citizen](#) manufacturer:*

Other Similar products are found below :

[5GTH92001](#) [5GTH9202242](#) [6407-250V-25273P](#) [ADTSA62NV](#) [ADTSA62RV](#) [B3F-3123](#) [1977177-8](#) [1977266-1](#) [ADTSA63NV](#)  
[ADTSM21NSVTR](#) [ADTSM25RVTR](#) [ADTSM32NVTR](#) [ADTSMW64RV](#) [FSMRA4JHA04](#) [GS4.70F300QP](#) [3ESH9R](#) [KSC241J](#) [SP DELTA](#)  
[LFS](#) [3FTL600RAS](#) [3FTL640RAS](#) [Y96K132V0FPLFS](#) [5GTH9658222](#) [ADTSM31NVTR](#) [EVQ-P1D05K](#) [2-1977120-7](#) [TSJW-5.2-260-TR](#)  
[KMT011MNGJLHS](#) [70-201.0](#) [ADTSG648NV](#) [ADTSM62KSVTR](#) [ADTSM648NV](#) [95C06E3RAT](#) [5GTH96561](#) [3ATH9Q](#) [FSM4JSMLXTR](#)  
[FSM4JSMXL](#) [FSMRA8JHA04](#) [HARS0073](#) [Y97HS12A5RAFP](#) [Y97BT23B2HAFP](#) [Y33R411N9FPLFT](#) [Y31C01402FPLFS](#)  
[PTS645SK50SMTR92](#) [ADTSM32NVB](#) [KMS233GPWTLFG](#) [Y78B42324FP](#) [Y33R21116FPLFT](#) [Y31B43131FPLFG](#) [Y78B64124FP](#)  
[Y71243251FP](#) [Y33R31119FPLFT](#)