



JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD

TO-3PK Plastic-Encapsulate Thyristors

BTA41 3Q TRIACs

MAIN CHARACTERISTICS


$I_{T(RMS)}$		40A
V_{DRM}/V_{RRM}	BTA41-600(C/B)W	600V
	BTA41-800(C/B)W	800V
V_{TM}		1.55V

FEATURES

- NPNPN 5-layer Structure TRIACs
- Mesa Glass Passivated Technology
- Multi Layers Metal Electrodes
- High Junction Temperature
- Good Commutation Performance
- High dV/dt and dl/dt
- Insulating Voltage=2500V_(RMS)

APPLICATIONS

- Heater Control
- Motor Speed Controller
- Mixer



MARKING



BTA41:Series Code
600CW:Depends on V_{DRM} and IGT
XXX:Internal Code

ABSOLUTE RATINGS ($T_a=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test condition		Value		Unit
V_{DRM}/ V_{RRM}	Repetitive peak off-state voltage	$T_j=25^\circ\text{C}$	BTA41-600(C/B)W	600		V
			BTA41-800(C/B)W	800		V
$I_{T(RMS)}$	RMS on-state current	TO-3PK($T_c \leq 80^\circ\text{C}$), Fig. 1,2		40		A
I_{TSM}	Non repetitive surge peak on-state current	Full sine wave , $T_j(\text{init})=25^\circ\text{C}$, tp=20ms; Fig. 3,5		400		A
I^2t	I^2t value	tp=10ms		1000		A^2s
dI_T/dt	Critical rate of rise of on-state current	$I_G=2*I_{GT}$, tr≤10ns, F=120Hz, $T_j=125^\circ\text{C}$		I - II - III	50	$\text{A}/\mu\text{s}$
I_{GM}	Peak gate current	tp=20μs, $T_j=125^\circ\text{C}$		8		A
$P_{G(AV)}$	Average gate power	$T_j=125^\circ\text{C}$		1		W
T_{STG}	Storage temperature			-40~+150		°C
T_j	Operating junction temperature			-40~+125		


ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test condition	Value		Unit
			CW	BW	
I_{GT}	Gate trigger current	$V_D=12\text{V}$, $R_L=33\Omega$, $T_j=25^\circ\text{C}$, Fig. 6	≤ 35	≤ 50	mA
V_{GT}	Gate trigger voltage		≤ 1.3		V
V_{GD}	Non-triggering gate voltage	$V_D=V_{DRM}$, $T_j=125^\circ\text{C}$	≥ 0.2		V
I_H	Holding current	$I_T=500\text{mA}$, Fig. 6	≤ 50	≤ 75	mA
I_L	Latching current	$I_G=1.2I_{GT}$, Fig. 6	≤ 60	≤ 80	mA
			≤ 80	≤ 100	mA
dV_D/dt	Critical rate of rise of off-state	$V_D=67\%V_{DRM}$, Gate Open $T_j=125^\circ\text{C}$	≥ 500	≥ 1000	V/ μs
V_{TM}	On-state Voltage	$I_{TM}=60\text{A}$, $t_p=380\mu\text{s}$, Fig. 4	≤ 1.55		V
I_{DRM} / I_{RRM}	Repetitive peak off-state current	$V_D=V_{DRM}/V_{RRM}$, $T_j=25^\circ\text{C}$	≤ 5	≤ 5	μA
		$V_D=V_{DRM}/V_{RRM}$, $T_j=125^\circ\text{C}$	≤ 4.0	≤ 4.0	mA

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th} (j-c)$	Junction to case (AC)	0.9	$^\circ\text{C/W}$
$R_{th} (j-a)$	Junction to ambient	50	$^\circ\text{C/W}$

PART NUMBER



CHARACTERISTICS CURVES

FIG.1: Maximum power dissipation versus RMS on-state current (full cycle)




FIG.2: RMS on-state current versus case temperature (full cycle)




FIG.3: Surge peak on-state current versus number of cycles




FIG.4: On-state characteristics (maximum values)




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$






FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature (typical values)



TO-3PK PACKAGE OUTLINE DIMENSIONS



DIM.	Unit(mm)		Unit(inch)	
	Min	Max	Min	Max
A	14.9	15.35	0.586	0.604
B	4.1	4.65	0.161	0.183
C	2.5	3.2	0.098	0.125
D	1.12	1.32	0.044	0.051
E	4.12	4.31	0.162	0.169
F	20.21	20.75	0.795	0.816
G	15.02	15.55	0.591	0.612
H	5.35	5.62	0.210	0.221
I	4.38	4.65	0.172	0.183
J	1.42	1.62	0.055	0.063
K	7.85	8.22	0.309	0.323
L	2.71	2.92	0.106	0.114
M	0.52	0.68	0.020	0.026

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Triacs](#) category:

Click to view products by [CJ manufacturer](#):

Other Similar products are found below :

[T2035H-6G](#) [BT137-600-0Q](#) [Z0409MF0AA2](#) [Z0109NA 2AL2](#) [ACST1635T-8FP](#) [BCR20RM-30LA#B00](#) [CMA60MT1600NHR](#) [NTE5611](#)
[NTE5612](#) [NTE5613](#) [NTE5621](#) [NTE5623](#) [NTE5629](#) [NTE5638-08](#) [NTE5688](#) [NTE5689](#) [NTE5690](#) [T1235T-8I](#) [BTA312-600CT.127](#) [T1210T-8G-TR](#) [Z0109NN0,135](#) [T2535T-8I](#) [T2535T-8T](#) [TN4050-12WL](#) [MAC4DLM-1G](#) [BT137-600E,127](#) [BT137X-600D](#) [BT148W-600R,115](#)
[BT258-500R,127](#) [BTA08-800BW3G](#) [BTA140-800,127](#) [BTA30-600CW3G](#) [BTA30-600CW3G](#) [BTB08-800BW3G](#) [BTB16-600CW3G](#)
[BTB16-600CW3G](#) [Z0410MF0AA2](#) [Z0109MN,135](#) [T825T-6I](#) [T1635T-6I](#) [T1220T-6I](#) [NTE5638](#) [TYN612MRG](#) [TYN1225RG](#) [TPDV840RG](#)
[ACST1235-8FP](#) [ACS302-6T3-TR](#) [BT134-600D,127](#) [BT134-600G,127](#) [BT136X-600E,127](#)