



JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD

TO-252-2LK Plastic-Encapsulate Thyristors

CT304D 3Q TRIACs

MAIN CHARACTERISTICS

$I_{T(RMS)}$		4A
V_{DRM}/V_{RRM}	CT304D-600T/S	600V
	CT304D-800T/S	800V
V_{TM}		1.55V


FEATURES

- NPNPN 5-layer Structure TRIACs
- Mesa Glass Passivated Technology
- Multi Layers Metal Electrodes
- High Junction Temperature
- Good Commutation Performance
- High dV/dt and dl/dt


APPLICATIONS

- Heater Control
- Motor Speed Controller
- Mixer

TO-252-2LK



MARKING



CT304D:Series Code
600S:Depends on V_{DRM} and I_{GT}
XXX:Internal Code

ABSOLUTE RATINGS ($T_a=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test condition		Value		Unit
V_{DRM}/ V_{RRM}	Repetitive peak off-state voltage	$T_j=25^\circ\text{C}$	CT304D-600T/S	600		V
			CT304D-800T/S	800		V
$I_{T(RMS)}$	RMS on-state current	TO-252-2LK ($TC \leq 110^\circ\text{C}$), Fig. 1,2		4		A
I_{TSM}	Non repetitive surge peak on-state current	Full sine wave, $T_j(\text{init})=25^\circ\text{C}$, $tp=20\text{ms}$; Fig. 3,5		40		A
I^2t	I^2t value	$tp=10\text{ms}$		8		A^2s
dl_t/dt	Critical rate of rise of on-state current	$I_G=2*I_{GT}$, $tr \leq 10\text{ns}$, $F=120\text{Hz}$, $T_j=125^\circ\text{C}$		I - II - III	50	$\text{A}/\mu\text{s}$
				IV	n/a	
I_{GM}	Peak gate current	$tp=20\mu\text{s}$, $T_j=125^\circ\text{C}$		4		A
$P_{G(AV)}$	Average gate power	$T_j=125^\circ\text{C}$		1		W
T_{STG}	Storage temperature			$-40 \sim +150$		$^\circ\text{C}$
T_j	Operating junction temperature			$-40 \sim +125$		


ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test condition	Value		Unit
			T	S	
I_{GT}	Gate trigger current	$V_D=12\text{V}$, $I_T = 1\text{A}$, $T_j=25^\circ\text{C}$, Fig. 6	≤ 5	≤ 10	mA
			n/a	n/a	
V_{GT}	Gate trigger voltage	I - II - III	≤ 1.3		V
V_{GD}	Non-triggering gate voltage	$V_D=V_{DRM}$, $T_j=125^\circ\text{C}$		≥ 0.2	
I_H	Holding current	$V_D=12\text{V}$, $I_{GT}=0.1\text{A}$, $T_j=25^\circ\text{C}$, Fig. 6	I - II - III	≤ 10	≤ 15
I_L	Latching current		I - III	≤ 10	≤ 25
			II	≤ 15	≤ 30
dV_D/dt	Critical rate of rise of off-state	$V_D=67\%V_{DRM}$, Gate Open $T_j=125^\circ\text{C}$		≥ 20	≥ 40
V_{TM}	On-state Voltage	$I_{TM}=6\text{A}$, $t_p=380\mu\text{s}$, Fig. 4		≤ 1.55	
I_{DRM} / I_{RRM}	Repetitive peak off-state current	$V_D=V_{DRM}/V_{RRM}$, $T_j=25^\circ\text{C}$		≤ 5	≤ 5
		$V_D=V_{DRM}/V_{RRM}$, $T_j=125^\circ\text{C}$		≤ 1	≤ 1
				mA	

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th} (j-c)$	Junction to case (AC)	2.6	$^\circ\text{C/W}$
$R_{th} (j-a)$	Junction to ambient	70	$^\circ\text{C/W}$

PART NUMBER



CHARACTERISTICS CURVES

FIG.1: Maximum power dissipation versus RMS on-state current (full cycle)




FIG.2: RMS on-state current versus case temperature (full cycle)




FIG.3: Surge peak on-state current versus number of cycles




FIG.4: On-state characteristics (maximum values)




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$






FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature (typical values)



TO-252-2LK PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters	
	Min.	Max.
A	2.100	2.500
A1	0.000	0.127
B	1.070	1.470
b	0.710	0.810
C	0.700	0.900
D	3.400	3.800
e	2.250	2.350
el	2.250	2.350
L	10.000	10.400
L1	2.600	3.000
L2	1.400	1.700
L3	0.600	1.000

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Triacs](#) category:

Click to view products by [CJ manufacturer](#):

Other Similar products are found below :

[T2035H-6G](#) [BT137-600-0Q](#) [Z0409MF0AA2](#) [Z0109NA 2AL2](#) [ACST1635T-8FP](#) [BCR20RM-30LA#B00](#) [CMA60MT1600NHR](#) [NTE5611](#)
[NTE5612](#) [NTE5613](#) [NTE5621](#) [NTE5623](#) [NTE5629](#) [NTE5638-08](#) [NTE5688](#) [NTE5689](#) [NTE5690](#) [T1235T-8I](#) [BTA312-600CT.127](#) [T1210T-8G-TR](#) [Z0109NN0,135](#) [T2535T-8I](#) [T2535T-8T](#) [TN4050-12WL](#) [MAC4DLM-1G](#) [BT137-600E,127](#) [BT137X-600D](#) [BT148W-600R,115](#)
[BT258-500R,127](#) [BTA08-800BW3G](#) [BTA140-800,127](#) [BTA30-600CW3G](#) [BTA30-600CW3G](#) [BTB08-800BW3G](#) [BTB16-600CW3G](#)
[BTB16-600CW3G](#) [Z0410MF0AA2](#) [Z0109MN,135](#) [T825T-6I](#) [T1635T-6I](#) [T1220T-6I](#) [NTE5638](#) [TYN612MRG](#) [TYN1225RG](#) [TPDV840RG](#)
[ACST1235-8FP](#) [ACS302-6T3-TR](#) [BT134-600D,127](#) [BT134-600G,127](#) [BT136X-600E,127](#)