

RAFIX 22 FS - Contact block with quick-connect terminals, silver contacts

1.20.126.304/0000



General information	
Lamp optional	LED-Clip
Dimensions	
Diameter	17.3 mm
Recommended key grid	30 mm
Mounting depth	27 mm
Mechanical design	
Mounting	snap on actuator
Contact system	bridge-contact self cleaning
Contact materials	Ag
Contact arrangement	2 NC
NC contact forcibly actuated acc. to IEC 60947-5-1	yes
Terminals	quick connect terminals 2.8 x 0.8 mm
Robustness	100 N
Nobusiness	100 14
Electrical characteristics acc. to IEC 60947, AC-1	5, DC-13
Rated insulation voltage AC/DC	250 V
Rated peak voltage	2500 V
Rated operating current I _E , AC15 B300	3 A/120 V; 1.5 A/240 V; I _{the} : 5 A
Rated operating current I _E , DC13 Q300	550 mA/120 V; 270 mA/240 V; I _{the} : 2.5 A
Other specifications	
Operating life / B10 at 250V / 1A	1,000,000
Operating life / B10 at 250V / 2A	100,000
Operating life / B10 Wert at 250V / 4A	30,000
Switching reliability at 24V/5mA DC	10 x 10 ⁻⁶
Storage temperature min.	-40
Ambient temp. operating min.	-25
Ambient temp. operating max.	+70
Storage temperature max.	+80
Color of plunger	red
Robustness	acc. to IEC 60947-5-5 (TÜV)
Shock resistance acc. to IEC 60068-2-27	15 g at 11 ms, amplitude half sinusoidal
Resistance to vibrations acc. to IEC 60068-2-6	5 g at 10 500 Hz
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78



V 0
yes
Universal
black
yes
yes

E-stop, silver contacts, 1 NC + 1 NO



Universal, Ag contacts, 2 NO



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by C&K manufacturer:

Other Similar products are found below:

61-8770.17 M2SA-7010 704.905.2 704.915.5 84-8512.2320 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505-001 190-17508-001 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-003 190-17509-005 GLZ304 51401 BS010 BST-D HW-S01 XESP2021 61-8480.22 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 84-8511.5320 A3CA-7121 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17507-002 190-17500-006 190-17510-001 1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment Kit25-Value Added