### 1.30.070.001/1403



# RAFIX 16, illuminated pushbutton, flat bezel, square collar, bezel vellow



#### fields of application

- > Measurement-control-regulation
- > Electrical engineering
- > Mechanical and system engineering
- > Industrial robots

#### special features

- > Robust also suitable for operation with gloves
- Optimal for switching large currents (max. 250 V / 6 A)
- > Actuators can be arranged in close rows, as wiring is required axially from behind
- > Degree of protection: IP 65 on front side
- > Switching elements with silver contacts (max. 250 V / 6 A) or gold contacts (max. 35 V / 0.25 A)
- > Connection types: screw connection, plug-in connection, PCB plug-in socket
- > Mounting diameter 16.2 mm
- Illumination with LED possible, socket: W 2 x 4.6d







#### description

With RAFIX 16 actuating elements, you can choose between three collar types: round, square or square, in which the push-buttons can be arranged in a seamless row. The mounting diameter is in accordance with the standard 16.2 mm.

#### technical data

> general

•	
illuminated	Yes
Bezel color	yellow
Collar shape	square
Operating temperature, min.	-25 °C
Operating temperature, max.	70 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	85 °C
Packaging	Box
Packaging unit	10 pcs.
net weight	6.3 g

IEC 60068-2-14 IEC 60068-2-30 direct links

> RAFI eCatalog

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights.

3 weeks

RAFI GmbH & Co. KG

standard delivery time

Environment resistance

## 1.30.070.001/1403



IEC 60068-2-33 IEC 60068-2-78

IP65

Operating life 2,000,000 Cycles

Degree of protection, front side,

according to DIN EN 60529

RoHS compliant Yes **REACH** compliant Yes MOQ order 10

#### > mounting diameters

Mounting hole 16.2 mm Mounting depth 44.7 mm Installation height 7.15 mm Grid, min. 25 x 25 mm Outside dimension, length 24.95 mm Outside dimension, width 24.95 mm Outside dimension, height 26.35 mm

Collar dimension 24,95 x 24,95 mm

#### > mechanical data

Operating force, max. 100 N Operating travel, max. 3 mm

Fixing Threaded ring

Threaded ring torque, max. 1.2 Nm

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Actuators category:

Click to view products by C&K manufacturer:

Other Similar products are found below:

LW1B-A0L LW1B-M0 680-4000-00 704.012.618 704.096.0 704.411.018I 704.412.0 704.633.1 704.730.1 704.733.0 862.8102 G6083

9PA24 A0107X A019307 ADC-418G 12MA7 ASDHHY-B HW1F-3G HW1M-L2222 HW4S-31L 200-.704-00 JS-10008 JS-10083 JS
10118 JS-10133 JS-10277 JS-10389 JS-150 JS-552 JS-555 JS-68 JS-6-B JS-91 JS-94 22-211.011 9001KXSDC 92-458.500 SAPT654133

2PA3 SW53AA2 302561 LW2L-A0 3E-10.4 468-10243-001 51-030.005 JM-13 JS-10120 JS-138-B JS-143-B