RF 19 H - Tactile switch, fully illuminated, silver contacts

3.14.002.642/0000



RR/


▲


Color of lens	areen
Recommended key grid	green 24 mm
Recommended key gnd	27 11111
Dimensions	
Length	19.05 mm
Width	19.05 mm
Overall height	12.5 mm
Mechanical design	
Mounting	soldering in PCB
Terminals	тнт
Contact system	snap-action contact
Contact arrangement	1 NO
Contact materials	Ag
Illumination	fully illuminated 2 LED
LED color	green
LED type	2 mm
Mechanical characteristics	
Operating force max.	2.9 ^{±0.6} N
Switching travel	0.5 ^{+0.2} mm
Robustness max.	with through-plated PCB 100 N
Electrical characteristics	
Rated voltage min.	Au: 0.02 V, Ag: 3 V
Rated voltage max.	35 V
Rated current min.	Au: 0.01 mA, Ag: 0.1 mA
Rated current max.	Au: 100 mA, Ag: 250 mA
Rated power max. (ohmic load)	Au: 2 W, Ag: 12.5 W
Contact resistance when new max.	100 mΩ
Insulation resistance	10 ⁹ Ω
Other specifications	
Ambient temp. operating min.	-25 °C
Ambient temp. operating max.	+70 °C
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Operating life min. (operations)	1,000,000 cycle
Solderability / solder heat resistance	according to DIN EN 60068-2-20
Wave soldering	260 °C max.
Manual soldering	350 °C / 5 sec. max.

Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.



ROHS compliant	yes
REACH compliant	yes





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tactile Switches category:

Click to view products by C&K manufacturer:

Other Similar products are found below :

5GTH92001 1-1977120-4 ADTSA62NV ADTSA62RV ADTSA63KV ADTSA644NV ADTSMW66NV ADTSMW67RV B3F-3123 B3F-6055A B3F-B32-01-KIT 1977177-8 1977266-1 ADTS644KV ADTSA61RV ADTSA62KV ADTSA63NV ADTSA63RV ADTSM21NSVTR ADTSM32NVTR ADTSM63SVTR ADTSM644KVTR ADTSMW64RV ADTSMW69NV FSMRA4JHA04 GS4.70F300QP 3ESH9R 506E00201 MJTP1164TR 3FTL600RAS 3FTL640RAS Y96K132V0FPLFS 101-TS5022T1601-EV 5GSH92001 KSJ0A231 80SH LFG ADTSM31NVTR EVQ-P1D05K MJTP1162TR ADTSM63KV 2-1977120-7 TSJW-5.2-260-TR KMT011MNGJLHS B3WN6002S ADTSA648RV 70-201.0 ADTSG648NV ADTSM62KSVTR ATA600VTR ADTSG66RV ADTS61NV