

## RF 15 H - Tactile switch, fully illuminated, gold contacts

## 3.14.200.731/0000





| General information                    |  |
|--|--|
| Color of lens                          | red                                      |
| Recommended key grid                   | 20 mm                                    |
| D                                      |  |
| Dimensions                             | 45                                       |
| Length                                 | 15 mm                                    |
| Width                                  | 15 mm                                    |
| Overall height                         | 12.5 mm                                  |
| Mechanical design                      |  |
| Mounting                               | soldering in PCB                         |
| Terminals                              | THT                                      |
| Contact system                         | snap-action contact                      |
| Contact arrangement                    | 1 NO                                     |
| Contact materials                      | Au                                       |
| Illumination                           | fully illuminated 2 LED                  |
| LED color                              | red                                      |
| LED type                               | 2 mm                                     |
|  |  |
| Mechanical characteristics             | 2 2+0 6                                  |
| Operating force max.                   | 2.9 <sup>±0.6</sup> N                    |
| Switching travel                       | 0.5 <sup>+0.2</sup> mm                   |
| Robustness max.                        | with through-plated PCB 100 N            |
| Electrical characteristics             |  |
| Rated voltage min.                     | Au: 0.02 V, Ag: 3 V                      |
| Rated voltage max.                     | 35 V                                     |
| Rated current min.                     | Au: 0.01 mA, Ag: 0.1 mA                  |
| Rated current max.                     | Au: 100 mA, Ag: 250 mA                   |
| Rated power max. (ohmic load)          | Au: 2 W, Ag: 12.5 W                      |
| Contact resistance when new max.       | 100 mΩ                                   |
| Insulation resistance                  | 10 <sup>9</sup> Ω                        |
|  |  |
| Other specifications                   | 05.00                                    |
| Ambient temp. operating min.           | -25 °C                                   |
| Ambient temp. operating max.           | +70 °C                                   |
| Environmental restistance              | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Operating life min. (operations)       | 1,000,000 cycle                          |
| Solderability / solder heat resistance | according to DIN EN 60068-2-20           |
| Wave soldering                         | 260 °C max.                              |
| Manual soldering                       | 350 °C / 5 sec. max.                     |



| ROHS compliant  | yes |
|-----------------|-----|
| REACH compliant | yes |









## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tactile Switches category:

Click to view products by C&K manufacturer:

Other Similar products are found below:

5GTH92001 1-1977120-4 ADTSA62NV ADTSA62RV ADTSA63KV ADTSA644NV ADTSMW66NV ADTSMW67RV B3F-3123 B3F-6055A B3F-B32-01-KIT 1977177-8 1977266-1 ADTS644KV ADTSA61RV ADTSA62KV ADTSA63NV ADTSA63RV ADTSM21NSVTR ADTSM32NVTR ADTSM63SVTR ADTSM644KVTR ADTSMW64RV ADTSMW69NV FSMRA4JHA04 GS4.70F300QP 3ESH9R 506E00201 MJTP1164TR 3FTL600RAS 3FTL640RAS Y96K132V0FPLFS 101-TS5022T1601-EV 5GSH92001 KSJ0A231 80SH LFG ADTSM31NVTR EVQ-P1D05K MJTP1162TR ADTSM63KV 2-1977120-7 TSJW-5.2-260-TR KMT011MNGJLHS B3WN6002S ADTSA648RV 70-201.0 ADTSG648NV ADTSM62KSVTR ATA600VTR ADTSG66RV ADTSG1NV