

RF 15 H - Tactile switch, fully illuminated, gold contacts

3.14.200.739/0000





General information	
Color of lens	blue
Recommended key grid	20 mm
Dimensions	
Dimensions	45
Length	15 mm
Width	15 mm
Overall height	12.5 mm
Mechanical design	
Mounting	soldering in PCB
Terminals	THT
Contact system	snap-action contact
Contact arrangement	1 NO
Contact materials	Au
Illumination	fully illuminated 1 LED
LED color	blue
LED type	3 mm
Mechanical characteristics	2 2+0 6
Operating force max.	2.9 ^{±0.6} N
Switching travel	0.5 ^{+0.2} mm
Robustness max.	with through-plated PCB 100 N
Electrical characteristics	
Rated voltage min.	Au: 0.02 V, Ag: 3 V
Rated voltage max.	35 V
Rated current min.	Au: 0.01 mA, Ag: 0.1 mA
Rated current max.	Au: 100 mA, Ag: 250 mA
Rated power max. (ohmic load)	Au: 2 W, Ag: 12.5 W
Contact resistance when new max.	100 mΩ
Insulation resistance	10 ⁹ Ω
Other specifications	
Ambient temp. operating min.	25 °C
Ambient temp. operating max.	+70 °C
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Operating life min. (operations)	1,000,000 cycle
Solderability / solder heat resistance	according to DIN EN 60068-2-20
Wave soldering	260 °C max.
Manual soldering	350 °C / 5 sec. max.



ROHS compliant	yes
REACH compliant	yes









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tactile Switches category:

Click to view products by C&K manufacturer:

Other Similar products are found below:

KMR633NG LFG 5GTH9202242 6426-201-11343 MJ1226 MJTP1109B MJTP1138EAUTR MJTP1230BL MJTPSHW GS6.90F300QP 11977223-0 1-1977120-4 ADTSA62NV ADTSA62RV ADTSA63KV ADTSA644NV ADTSM24NVTR ADTSMW66NV ADTSMW67RV

ATM533VTR 1571300-3 B3F-3123 B3F-6055A B3F-B32-01-KIT 1977177-8 1977266-1 2-1977223-4 2-1977223-7 ADTS644KV

ADTSA61RV ADTSA62KV ADTSA63NV ADTSA63RV ADTSA65NV ADTSM21NSVTR ADTSM25RVTR ADTSM31RVTR

ADTSM32NVTR ADTSM61YVTR ADTSM63SVTR ADTSM644KVTR ADTSMW64RV ADTSMW69NV FSMRA4JHA04

GS4.70F300QP D38999/20JJ37SA TL1105B TL1105J ATH447K2Q ATM534VTR MJ1215