

RAFIX 22 QR - Contact block with silver contacts, without coupling, screw terminals, 2 NC 5.00.100.141/0000



Dimensions	
Dimensions with coupling	39.5 x 49.9 x 30 mm
Mounting depth without cable	56.4 mm
Mechanical design	
Mounting	snap on coupling and actuator
Contact system	bridge-contact self cleaning
Contact materials	Ag
Contact arrangement	2 NC
NC contact forcibly actuated acc. to IEC 60947-5-1	yes
Terminals	screw terminals
Terminal marking	color encoded
Robustness	100 N
Wire range solid wires without wire end sleeves	2 x 0.75 2.5 mm²
Wire range stranded wires without end sleeves	2 x 1.01.5 (2 x 0.08 2.5) mm ²
Stripping length, solid or stranded	8 mm
Wire range with wire end sleeves	2 x 0.75 1.5 mm²
Electrice characteristics acc. to IEC 60947	
Rated insulation voltage AC/DC	400 V
Rated peak voltage	6,000 V
Rated operating current I _e AC 12 / DC 12	10.4
Dated appraising ourrent L AC 15	10 A
Rated operating current I _e AC-15	125 V/10 A, 250 V/6 A, 400 V/3.5 A
Rated operating current I _e DC-13 Q300	24V/2.75A, 60V/1.1A, 125V/0.55A, 250V/0.275A
Degree of pollution	3
Positive opening travel	3 mm
Operating speed	5 1000 mm/c
Electrice characteristics acc. to IEC 61058	
Resistive load AC	10 A /250 V; 7.5 A / 400 V
Motor load AC	6 A / 250 V; 4 A / 400 V (5 A / 250 V)
Peak input current filament lamp AC	36 A
Peak capacity input current AC	100 A
Protection class	II
Lamp characteristics	24.0
Lamp characteristics	BA 9 s




Other specifications	
Operating life at 10 A/250 V AC	70,000 (10A), 200,000 (5A)
Switching reliability at 24V/5mA DC	10 x 10 ⁻⁶
Robustness	acc. to IEC 60947-5-5
Corresponding to CE	acc. EU-guideline NSR 72/73
Shock resistance acc. to IEC 60068-2-27	15 g at 11 ms, amplitude half sinusoidal
Resistance to vibrations acc. to IEC 60068-2-6	5 g at 10 500 Hz
Ambient temp. operating min.	-25 °C
Ambient temp. operating max.	+70°C (+50°C)
Storage temperature min.	-40 °C
Storage temperature max.	+80 °C
Flame class acc. to UL 94	V 0
Hot wire ignition acc. to IEC 60695-2-1	yes
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
ROHS compliant	yes
REACH compliant	yes

Silver contacts, 1 NO, quick connector



with contact block



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by C&K manufacturer:

Other Similar products are found below:

61-8770.17 M2SA-7010 704.905.2 704.915.5 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505-001 190-17508-001 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-003 190-17509-005 GLZ304 51401 BS010 BST-D HW-S01 XESP2021 61-8480.22 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 84-8511.5320 A3CA-7121 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17507-002 190-17500-006 190-17510-001 1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment Kit25-Value Added GLZ336