Features/Benefits

- IP66/IP68 versatile rating to withstand harsh outdoor environments, intense, wet weather, wind blown rain, dirt
- UL 61058-1 certified has global acceptance with no additional testing needed
- Integrated panel seal for extra protection
- Superior oil and fuel resistance
- High strength, heat resistant housing designed for demanding applications subjected to vibration and harsh conditions

Typical Applications

- Off-road, Construction/Agricultural vehicles
- Material handling equipment
- Articulating, scissor, and bucket lift controls
- **Outdoor industrial equipment**
- Lift gate controls



Specifications

UL ELECTRICAL RATINGS: UL 61058-1

MAINTAINED FUNCTIONS: 15A GP, 277VAC 50/60Hz T85

15(4)A, 277VAC 50/60Hz T85 1/2 hp, 125VAC 50/60Hz T85 1 hp, 250VAC 50/60Hz T85

MOMENTARY FUNCTIONS: 10A GP, 277VAC 50/60Hz T85

10(4)A, 277VAC 50/60Hz T85 1/4hp, 125VAC 50/60Hz T85 1/2 hp, 250VAC 50/60Hz T85

ELECTRICAL LIFE: 10,000 cycles DC ELECTRICAL RATINGS: Resistive Loads ALL FUNCTIONS: Up to 25A, 24VDC

> 0.75A, 125VDC 0.5A, 250VDC

MAINTAINED FUNCTIONS: 15A, 28VDC MOMENTARY FUNCTIONS: 10A, 28VDC

2500V min. initial (terminal to toggle) DIELECTRIC STRENGTH:

INSULATION RESISTANCE: 1000 M Ω min. initial

CONTACT RESISTANCE: 50 mΩ max. initial(terminal to toggle)

OPERATING AND STORAGE

-40°C to +85°C TEMPERATURE: IP RATINGS: IP66/IP68 Versatile **Materials**

HARDWARE:

CASE: Thermoset **ACTUATOR:** Stainless Steel PIVOT PIN: Stainless Steel **BUSHING:** Zinc Die Cast SEAL: Silicone

MOVEABLE CONTACT(S): Copper alloy, silver plated

BUTTON: Silver Cadmium

TERMINALS: Brass for Quick connect, silver plated

brass for solder and screw terminals


Hex nut & locking ring: brass, nickel plated Screws: brass

Lock washer: brass, nickel plated

PACKAGING: Trays

Build-A-Switch

To order, simply select desired option from each category and place in the appropriate box. Available options are shown and described on pages F-53 thru F-56. For additional options not shown in catalog, consult Customer Service Center.




Dimensions are shown: mm Specifications and dimensions subject to change

www.ckswitches.com

SP

	NO. POLES	MODEL NO.	SWITCH FUNCTION			CONNECTED TERMINALS			
30° P-2 P-1 P-3			POS.1	POS.2	POS.3	POS.1	POS.2	POS.3	SCHEMATIC
	SP	PT101	ON	NONE	ON	2-3	N/A	2-1	SPDT
		PT102*	ON	NONE	OFF	2-3	N/A	OPEN	3
		PT103	ON	OFF	ON	2-3	OPEN	2-1	(COMMON) 0—1
		PT105	MOM	OFF	MOM				
		PT107	ON	OFF	MOM				
		PT108	ON	NONE	MOM	2-3	N/A	2-1	


^{*} PT102 OMIT TERMINAL 1





DP

			SWITCH FUNCTION			CONNECTED TERMINALS			
			P05.1	P05.2	P05.3	POS.1	P05.2	P05.3	
730° P-2 / P-3	NO. POLES	MODEL NO.							SCHEMATIC
(\\id		PT201	ON	NONE	ON	2-3,5-6	N/A	2-1,4-5	DPDT O— 3 NC
	DP	PT202*	ON	NONE	0FF	2-3,5-6	N/A	OPEN	2 —0 :
		PT203	ON	0FF	ON	2-3,5-6	OPEN	2-1,4-5	(COMMON) : O-1 NO
		PT205	MOM	0FF	MOM				-O— 6 NC
		PT207	ON	0FF	MOM				5 —0
		PT208	ON	NONE	MOM	2-3,5-6	N/A	2-1,4-5	(COMMON) 0—4 NO

* PT202 OMIT TERMINAL 1 AND 4













ACTUATOR









TERMINALS










MODEL PT101SS SHOWN




MODEL PT201SS SHOWN


MODEL PT201SO SHOWN






Z SOLDER TERMINAL SP









MODEL PT201SZ SHOWN

MOUNTING HARDWARE





PART NO. 707200201

NIICKEL PLATED WITH KEYWAY

Note: Standard hardware shipped with each switch is 1 pc each



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Toggle Switches category:

Click to view products by C&K manufacturer:

Other Similar products are found below:

8928K478 8A1-C-222 020017-13 60012L 6006L CS115W CS120W 6663 7101SPDV30BE 7103SDV30BE 7105D 7108P3YAV2BE
71YY50282 7300K36 7301K38 7306K36 7310K36 7506K4 7592K6 7660K12 7691K14 7700K1 8391K108 8396K108 8811K17
8812K14 8824K14 8828K13 8835K3 8858K44 PS83-121G 1-1825192-0 A201SCWZB04 A207SYCB04 A208J61ZQ0004 A221T1TCQ
A323S1CWZQ A423S1CWZG-M8 1201W 12156AX408 12147AGKX679 12246X778 12TW49-3D 130312 13037L 13001X
AE101MD1W4B04 AE208SD1W4B04 MS24659-22D MS27407-5