

REV	A	10/11-2012	REVISE CONTENT
DATE			According to the customer drawing, need to include approvals UL and cUL.

- NOTE:
1. Hi-Pot Test : 1500V/1Sec ; <0.5mA.
  2. Insulation Resistance Test : DC 500/m>100 meg-ohm.
  3. Continuity & Polarization Test : No short circuit, break circuit, displacement.
  4. Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
  5. Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
  6. All material according to Non-toxic standard.(Material must be RoHS compliant).

線材印字 (Wire Printed)		Approval No. : E77975, E322763		DRAWN		Customer Approval	
包裝方式 (Packaging)		See Hank Detail		DATE		Customer Approval	
(Wire Printed)		Approval No. : E77975, E322763		10/11-2012		Customer Approval	
綠材印字 (Un-filers, Printing Ink)		Approval No. : E77975, E322763		DATE		Customer Approval	
Tied Hank		See Hank Detail		P/N No.		Customer Approval	
Carton Size		480 x 320 x 250		800-12-32D-BL-0010F		Customer Approval	
Pack Number		25pcs/UL Laster Labels		MATERIAL		Customer Approval	
Carton Print		See Purchase Order		PVC		Customer Approval	
TYPE		IEC 60320, C20 to IEC 60320, C19, 20A		UNIT		Customer Approval	
DRAWNING NO.		067MM229		REV		Customer Approval	
		REV		A		Customer Approval	

FM-320 (IEC 60320, C20, 20A 250V~)

(Dimensions of Inlets Face)

26±0.15

34±1.5

8±0.15

13±0.15

5/2X

(L) Black

(N) White

(E) Green

SJT 12AWGx3C剖面圖 (Wire Cross-Section)

Overall Diameter 10.8±0.25mm

PVC Jacket Thickness 1.15mm (>1.04mm)

Copper Conductor 65/0.254±0.003mm Diameter 2.37mm (Approx.)

PVC Insulation Thickness 0.79 (>0.71mm)

Overall Diameter 3.95±0.10mm

FM-319 (IEC 60320, C19, 20A 250V~)

(Dimensions of Connector Face)

27.2±1.5

19.5±0.25

8±0.15

13±0.15

6/2X

(L) Black

(N) White

(E) Green

B-C3 扎線圖示 (Tied Loop Hank Detail)

250±30

顏色(Color)	零件描述(Component)	Qty.	內剝(R.OJ)	外剝(R.OJ)	顏色(Color)	規格描述(Instruction)	Qty.	顏色(Color)	
(Black)	35P 黑色 FM-320 (IEC 60320, C20, 20A 50Hz 250V~)	1	6±1	6±1	黑/Black(L)	FM-319 (IEC 60320, C19, 20A 50Hz 250V~)	1	35P 黑(Black)	
(Black)	2.0x6.0方形端子(GEM 97607-1)	1	6±1	6±1	白/White(N)	C19 單粒方型端子(GEM 98735-1)	3	鍍銀(Nickel-Plated)	
(Nickel-Plated)	2.0x5.0方形端子(GEM 97606-1)	2	6±1	20±2	白/White(N)	C19 Loose Receptacle Terminal)	3	鍍銀(Nickel-Plated)	
(Nickel-Plated)	2.0x5.0 (Computer Solid Blades)	2	6±1	20±2	綠/Green(E)	GA-033兩件式內模 (2.0x4.0 Serial Housing)	1	黑色(Black)	
(Black)	033 兩件式內模 (C20 Inner Body)	1	6±1	20±2	綠/Green(E)		1	黑色(Black)	
插頭部件 (Plug Component)		頭部剝皮尺寸 (Dimensions)		線材規格 (Wire Styls)		尾部剝皮尺寸 (Dimensions)		尾插部件 (Connector Component)	
Qty.		內剝(Strip)		SJT 12AWGx3C		內剝(Strip)		外剝(R.OJ)	
1		6±1		105°C 黑色 (BLACK)		5±1		20±2	
1		6±1		Length : 3009.9±50.8 (118.5"±2")		5±1		20±2	
1		6±1				5±1		20±2	

品管校閱：

業務校閱：

8

7

6

5

4

3

2

1

8

7

6

5

4

3

2

1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [cnc manufacturer](#):*

Other Similar products are found below :

[741-20010-00500](#) [DL-5468](#) [2725-2828-01000-T](#) [300-30-40-GR-0250F](#) [743-60012-00300](#) [302-28-50-GR-0250F](#) [302-28-10-GR-0100F](#)  
[3020-10-0300-00-TR](#) [FM-213-4](#) [FM-214-4](#) [302-28-26-GR-0250F](#) [302-28-40-GR-0250F](#) [304-28-26-MC-0250F](#) [304-28-40-MC-0250F](#)  
[302-28-09-GR-0250F](#) [1002-003-02000](#) [302-28-37-GR-0250F](#) [302-28-25-GR-0250F](#) [3020-10-0300-00](#) [300-30-14-GR-0250F](#) [302-28-14-GR-](#)  
[0250F](#) [300-30-04-GR-0250F](#) [300-30-26-GR-0250F](#) [304-28-16-MC-0250F](#) [304-28-26-MC-0100F](#) [302-28-10-GR-0250F](#) [800-1401-2-SJT0-](#)  
[BL-00200](#) [300-30-20-GR-0250F](#) [304-28-14-MC-0250F](#) [800-1800-2-SVT0-BL-00100](#) [741-20010-01000](#) [CNC-99-16](#) [302-28-20-GR-0100F](#)  
[302-28-26-GR-0100F](#) [304-28-40-MC-0100F](#) [600218](#) [510-26-6600-WH-0007F](#) [610230](#) [3010-10-003-13-00](#) [304-28-14-MC-0100F](#) [302-28-50-](#)  
[GR-0100F](#) [3030-16-0102-00](#) [3221-10-0300-00](#) [304-28-16-MC-0100F](#) [610234](#) [302-28-37-GR-0100F](#) [800-12-32D-BL-0008F](#) [FM-215-8](#) [DL-](#)  
[1006](#) [304-28-20-MC-0250F](#)