承 认 书

REAcH　　RoHs

SPECIFICATIONFORAPPROVAL

品　　名:	共模电感
客户料号:	
我司料号:	10306230033H
品名规格:	T16X12X8-C
制作日期:	2019-08-16
制作版本:	A-（01）

承制方确认			客户端确认		
工　程	审　核	批　准	工　程	审　核	批　准

CND-TEK
深圳磁联达电子有限公司
深圳市南山区西丽牛城村221号5楼西侧
Tel:0755-27652992　Fax:0755-27652977

客　户		品　名	环型电感
我司料号		制作日期	2019-08-16

历 史 变 更 记 录 表

序号	日　期	版本	变更前	变更后	备　注
1	2019-08-16				



NOTE:
1).两绕组分开绕，中间用1mm电木板或PCB板隔开
2).外包18mm胶布2Ts

工　程	批　准	版　本
		01

客　户		品　名	环型电感
我司料号		制作日期	2019-06-16

2.原理结构图:



绕线顺序	起尾线		线型/规格	匝　比	胶　布	绕线要求		备注说明
	起始	结尾	线径/铜箔	圈　数	圈数/宽度	绕　法		
N1	1	2	Φ0.50(金色)	65TS（外）		制	实绕65Ts	
N2	3	4	Φ0.50(金色)	65TS（外）		制	实绕65Ts	

绕制事项说明：需含浸:

工　程	批　准	版　本
		01

客　户		品　名	环型电感
我司料号		制作日期	2019-08-16

电性测试要求为:(频率是:　1.0KHz　　0.25V)

测试端子	电　感	漏　感	测试仪器
1----2	11mH min		
3----4	11mH min		

耐压测试

初级----次级	AC 600V/1mA	

样 品 测 试 记 录 表

测试项目	Lx 1-2	Lx 3-4	Hi-TOP P-S	Hi-TOP S-C	Hi-TOP P-C	Hi-TOP P-P	TURNS N1-N2	绝缘电阻 500DC/100Ω MIN	DCR -	DCR -	DCR -	判　定
测试仪器	1062A	1062A	CC2670A	CC2670A	CC2670A	CC2670A	3250A	CC2670A	3250A	3250A	3250A	QA
1#	13	13	OK				OK	OK				OK
2#	12.3	12.2	OK				OK	OK				OK
3#	12.5	12.4	OK				OK	OK				OK
4#	12.4	12.6	OK				OK	OK				OK
5#	13	13.2	OK				OK	OK				OK

外 观 尺 寸 测 量 记 录 表

测试项目	长(00mmMAX)	宽(00mmMAX)	高(00mmMAX)	脚　距	PIN　距	PIN　长	PIN　径
1#							
2#							
3#							
4#							
5#							

工　程	批　准	版　本
		01

客　户		品　名	环型电感
我司料号		制作日期	2019-08-16

材 料 清 单

NO	ITET	DESERIPTION	TMP CLASS	SUPPL　IERS	UL
1	0		155℃	0	E5948(S)
2	磁芯	T16X12X8-C	200℃	富思源	
3	铜线	2UEWΦ0.50mm	130℃	深港	E239508
4	铜线		130℃	0	E3058803
5	0	无		深港	
6	0	无	130℃	永好	E317896
7	0	无	130℃		E317896
8	0	无	260℃	德昌	
9	绝缘漆	F8093--2		德昌	
10	无铅锡条	Sn(99.3)Cu(0.7)		弘星威	
11	0	XD--611/XD--603		弘星威	
12	稀释剂	TF--805			E175982
13	0	无	130℃		E228349
14	0	DE536	130℃		
15					

材料禁用物质检测表

NO	ITET	CGC REF NO	六大有害物质含量（PPM）						有效期（一年）
			Pb	Hg	Cd	Cr6+	PBBs	PBDEs	
1		CE/2008/B3672	ND	ND	ND	ND	ND	ND	2019.11.20
2		SH20018217/CHEM	ND	ND	ND	Negative	ND	ND	2019.01.09
3	磁芯	CANE0803444901	ND	ND	ND	ND	ND	ND	2019.06.29
4	铜线	CANE0990072230l	ND	ND	ND	ND	ND	ND	2019.03.03
5		KA/2009/31318	ND	ND	ND	ND	ND	ND	2019.03.17
6		CANE0805742202	ND	ND	ND	ND	ND	ND	2019.03.07
7		CANE0990082950l	ND	ND	ND	ND	ND	ND	2019.03.04
8		CANE0990082950l	ND	ND	ND	ND	ND	ND	2019.11.24
9	稀释剂	RL:SHB000073950001C	ND	ND	ND	ND	ND	ND	2019.05.31
10	绝缘漆	RL:SHB000073950001C	ND	ND	ND	ND	ND	ND	2019.05.31
11	无铅锡条	CANE0806088902	ND	ND	ND	Negative	ND	ND	2019.11.11
12	助焊剂	CANE0990016401	ND	ND	ND	ND	ND	ND	2019.10.14
13		ASR0901122109106-A	ND	ND	ND	ND	ND	ND	2019.01.09
14		CE/2008/21452/A	ND	ND	ND	ND	ND	ND	2019.3.15
15									

工　程	批　准	版　本
		01

1.SCHEMATIC



2.VIEW



NOTE:
1).两绕组分开绕，中间用1mm电木板或PCB板隔开
2).外包18mm胶布2Ts

3.电气特性
3.1 电感 (CH-3250 AT 1.0KHz/0.25V)
Lp(1-2)&(3-4):11mH MIN
3.2 耐压测试
PIN 1.2 对 PIN 3.4:600Vac IS 1mA MAX

4.材料
4.1 磁芯:T16X12X8-C R10K OR EQIU;
4.2 铜线:2UEW
4.3 胶布:PZ280.

ROHS

版次	日期	变更内容	变更者
A/1	20090709	首次制作	J.G.J

CND-TEK　深圳磁联达电子有限公司

物料名称	环型电感	适用机种	页次: 1 of 1
单位:mm	公差:未注公差±0.2mm		编制:
审核:	开发工程师确认:	核准:	验证组:
物料编码:625-011m00-000	文件编号:K-DZ		比例: 1:1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Common Mode Chokes / Filters ***category:***

Click to view products by CND-tek ***manufacturer:***

Other Similar products are found below :

RGCMF1210900H3T B82722A2102N001 UAL21V07012500 UAL24VR06500CH UALSC0220G0000 UALSC058000000 UALSC0580J0000 UALSC1520JH000 UALSU10VR15019 UALSU10VR20010 UALSU16VD30030 UALSU16VD40010 UALSU9H0305000 UALSU9HF030600 UALSU9HF060300 UALSU9HR050340 UALSU9VD070100 UALSU9VR070170 5701610000 CM7060M132R-10 UALW21HS200290 UALW21HS072450 UALSU9VD070400 UALSU9V0701000 UALSU9HR030900 UALSU9HF050500 UALSU9H0701000 UALSU9H0208000 UALSU9H0110000 UALSCF25081300 UALSC0305GS000 UALSC0120G0000 UAL24VK06450CH UAL11VL1105000 RN112-3.6-02-0M4 RN114-1.2-02-10M RN122-0.6-02-47M RN122-3-02-4M5 RN142-1-02-33M RN214-2.5-02-3M3 RN112-2-02-1M0 RN143-6-02-1M8 RN214-0.8-02-27M RN242-1.4-02-27M EXC-X4CH120X DLW5BTM102TQ2L CMF16-153131 CMF23H-273141 744252510 B82793C0253N201