

产品承认书

SPECIFICATION FOR APPROVAL

CUSTOMER:	
CUSTOMER P/N:	
CND-TEK P/N. :	CB0679S
DESCRIPTION:	BMS Signal Transformer
REF NO:	QTC-002
REV/NO:	A/0
DATE:	2023/03/02

ATTACHMENT:		
<input checked="" type="checkbox"/>	SPECIFICATION	
<input checked="" type="checkbox"/>	SAMPLE	Q'TY OF SAMPLES PCS

	√	CUSTOMER'S SIGNATURE	REMARK
FULL APPROVED			
CONDITIONAL APPROVED			
REJECTED			



CB0679S

BMS Signal Transformer

V1.0.2 Feb 2,2023



深圳磁联达电子有限公司

Shenzhen CND-TEK Electronics Co.,Ltd

公司地址: 深圳市南山区西丽镇街道百旺社区牛城村牛城路221号505

TEL: 86-755-29016433 FAX:86- 755-27652977



Email: sales2@cd-tek.com

Http: //www.cd-tek.com



1. FEATURES:

- 1.1 One channel with choke
- 1.2 Supports serial daisy chain / IsoSPI
- 1.3 Operating temperature: -40 to +125 °C
- 1.4 Storage temperature: -50 to +125 °
- 1.5 800 Vdc for 15 Years working voltage
- 1.6 Hi-Pot: 4300 Vdc
- 1.7 AEC-Q200 compliant
- 1.8 RoHS compliant


2. DIMENSIONS & MARKING



SUGGESTED LAND PATTERN




3. SCHEMATICS:



4.ELECTRICAL SPECIFICATIONS @25°C


4.1 Inductance OCL(-40°C~+125°C):	60μH Min @ 100KHz 0.1V
4.2 DC Resistance:	Transformer Side: 0.45Ω max. CM Choke Side: 0.85 Ω max.
4.3Turns Ratio:	1CT : 1CT±2%
4.4 Insertion Loss:	4 MHz -0.30dB Max
4.5 Return Loss (Z out = 100 ohms):	4 MHz 20dB Min
4.6 Common Mode Rejection Ratio:	1-10 MHz -35dB TYP 10-1000 MHz -20dB TYP
4.7 Leakage Inductance:	0.5uH max @100KHz,0.1V
4.8 Design Construcyion:	Funcyional Insulation
4.9 Polarity:	PER Schematic
4.10 Hi-Pot:	4300 VDC 1 mA, 60 sec.
4.11 Insulation Resistance:	400 Megaohms Min
4.12 Working Voltage:	800 Vdc
4.13 Qualification:	PER AEC-Q200
4.14 Operating Temperature Range:	-40°C~+125°C
4.15 Storage Temperature Range:	-50°C~+125°C

5. Recommended Lead Free IR Reflow Soldering Curve :




5.1 Profile Feature	Pb Free Assembly
5.2 Average Ramp Rate (TSmax to TP)	3°C/second max.
5.3 Preheat- Temperature Min. (TSmin)	150°C
5.4 Preheat- Temperature Max. (TSmax)	200°C
5.5 Preheat- Time (tsmin to tsmax)	60seconds
5.6 Time Maintained Above - Temperature (TL) Time	217°C
5.7 Maintained Above - Time (tL)	60 seconds
5.8 Peak Temperature (Tp)	245°C MAX
5.9 Time within 5 °C of Actual Peak Temperature (tp)	20-40 seconds
5.10 Ramp-Down Rate	6°C/second max.
5.20 Time 25 °C to Peak Temperature	8 minutes max.



Packaging Specifications



ITEM	W	P	A ₀	B ₀	K	T	C	D ₀	E	F	P ₀
DIM	16	12	9.65	8.28	6.6	0.40		1.5	1.75	7.5	4.0



	A	B	C	D	N	W ₁	W ₂	W ₃	W ₃
Tolerance		min.	±0.8	min.	min.	+2.0	max.	min.	max.
Tape width mm	330.00	1.50	13.00	20.20	100.00	16.4	18.4	16.4	18.39



ALL DIMENSIONS ARE IN MILLIMETERS WITH THE FOLLOWING TOLERANCES: ±0.10

COMPONENTS PER REEL: 400 pcs

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Power Transformers](#) category:

Click to view products by [CND-tek](#) manufacturer:

Other Similar products are found below :

[F-181U](#) [F-204U](#) [F-206U](#) [F-227X](#) [F-23U](#) [F-264U](#) [F-267U](#) [F-35U](#) [F-412X](#) [F-55X-1](#) [F-68U](#) [F-71U](#) [F-72Z](#) [F-74U](#) [F-83A](#) [F-84AC](#) [F-85U](#) [F-86U](#) [F-9U](#) [PCT-02](#) [PCT-03](#) [PCT6630](#) [PF2.5-20](#) [PPC-14](#) [PPC-46](#) [PPC-58](#) [PSD4-36](#) [GSD-150](#) [11E009H](#) [11E012H](#) [DSW-2120](#) [DSW-224](#) [DSW-228](#) [DSW-310](#) [DSW-3120](#) [DSW-356](#) [DSW-412](#) [DSW-4120](#) [DSW-424](#) [DSW-448](#) [DSW-456](#) [DSW-528](#) [DSW-556](#) [DSW-610](#) [DSW-6120](#) [DSW-624](#) [DSWC-712](#) [EN216B](#) [N-39X](#) [N-49X](#)